
beem Documentation

Release 0.23.7

Holger Nahrstaedt

May 12, 2020

Contents

1 About this Library	3
2 Quickstart	5
3 General	7
4 Indices and tables	201
Python Module Index	203
Index	205

Steem/Hive is a blockchain-based rewards platform for publishers to monetize content and grow community.

It is based on *Graphene* (tm), a blockchain technology stack (i.e. software) that allows for fast transactions and a scalable blockchain solution. In case of Steem/Hive, it comes with decentralized publishing of content.

The beem library has been designed to allow developers to easily access its routines and make use of the network without dealing with all the related blockchain technology and cryptography. This library can be used to do anything that is allowed according to the Steem/Hive blockchain protocol.

CHAPTER 1

About this Library

The purpose of *beem* is to simplify development of products and services that use the Steem blockchain. It comes with

- its own (bip32-encrypted) wallet
- RPC interface for the Blockchain backend
- JSON-based blockchain objects (accounts, blocks, prices, markets, etc)
- a simple to use yet powerful API
- transaction construction and signing
- push notification API
- *and more*

CHAPTER 2

Quickstart

Note:

All methods that construct and sign a transaction can be given the `account=` parameter to identify the user that is going to be affected by this transaction, e.g.:

- the source account in a transfer
- the account that buys/sells an asset in the exchange
- the account whose collateral will be modified

Important, If no account is given, then the `default_account` according to the settings in config is used instead.

```
from beem import Steem
steem = Steem()
steem.wallet.unlock("wallet-passphrase")
account = Account("test", steem_instance=steem)
account.transfer("<to>", "<amount>", "<asset>", "<memo>")
```

```
from beem.blockchain import Blockchain
blockchain = Blockchain()
for op in blockchain.stream():
    print(op)
```

```
from beem.block import Block
print(Block(1))
```

```
from beem.account import Account
account = Account("test")
print(account.balances)
for h in account.history():
    print(h)
```

```
from beem.steem import Steem
stm = Steem()
stm.wallet.wipe(True)
stm.wallet.create("wallet-passphrase")
stm.wallet.unlock("wallet-passphrase")
stm.wallet.addPrivateKey("512345678")
stm.wallet.lock()
```

```
from beem.market import Market
market = Market("SBD:STEEM")
print(market.ticker())
market.steem.wallet.unlock("wallet-passphrase")
print(market.sell(300, 100) # sell 100 STEEM for 300 STEEM/SBD
```

CHAPTER 3

General

3.1 Installation

The minimal working python version is 2.7.x. or 3.4.x

beem can be installed parallel to python-steem.

For Debian and Ubuntu, please ensure that the following packages are installed:

```
sudo apt-get install build-essential libssl-dev python-dev curl
```

For Fedora and RHEL-derivatives, please ensure that the following packages are installed:

```
sudo yum install gcc openssl-devel python-devel
```

For OSX, please do the following:

```
brew install openssl
export CFLAGS="-I$(brew --prefix openssl)/include $CFLAGS"
export LDFLAGS="-L$(brew --prefix openssl)/lib $LDFLAGS"
```

For Termux on Android, please install the following packages:

```
pkg install clang openssl-dev python-dev
```

Install pip (<https://pip.pypa.io/en/stable/installing/>):

```
curl https://bootstrap.pypa.io/get-pip.py -o get-pip.py
python get-pip.py
```

Signing and Verify can be fasten (200 %) by installing cryptography. Install cryptography with pip:

```
pip install -U cryptography
```

Install beem with pip:

```
pip install -U beem
```

Sometimes this does not work. Please try:

```
pip3 install -U beem
```

or:

```
python -m pip install beem
```

3.1.1 Manual installation

You can install beem from this repository if you want the latest but possibly non-compiling version:

```
git clone https://github.com/holgern/beem.git  
cd beem  
python setup.py build  
  
python setup.py install --user
```

Run tests after install:

```
pytest
```

3.1.2 Installing beem with conda-forge

Installing beem from the conda-forge channel can be achieved by adding conda-forge to your channels with:

```
conda config --add channels conda-forge
```

Once the conda-forge channel has been enabled, beem can be installed with:

```
conda install beem
```

Signing and Verify can be fasten (200 %) by installing cryptography:

```
conda install cryptography
```

3.1.3 Enable Logging

Add the following for enabling logging in your python script:

```
import logging  
log = logging.getLogger(__name__)  
logging.basicConfig(level=logging.INFO)
```

When you want to see only critical errors, replace the last line by:

```
logging.basicConfig(level=logging.CRITICAL)
```

3.2 Quickstart

3.2.1 Hive/Steem blockchain

Nodes for using beem with the Hive blockchain can be set by the command line tool with:

```
beempy updatenodes --hive
```

Nodes for the Steem blockchain are set with

```
beempy updatenodes
```

Hive nodes can be set in a python script with

```
from beem import Steem
from beem.nodelist import NodeList
nodelist = NodeList()
nodelist.update_nodes()
nodes = nodelist.get_nodes(hive=True)
hive = Steem(node=nodes)
print(hive.is_hive)
```

Steem nodes can be set in a python script with

```
from beem import Steem
from beem.nodelist import NodeList
nodelist = NodeList()
nodelist.update_nodes()
nodes = nodelist.get_nodes(hive=False)
hive = Steem(node=nodes)
print(hive.is_hive)
```

3.2.2 Steem

The steem object is the connection to the Steem/Hive blockchain. By creating this object different options can be set.

Note: All init methods of beem classes can be given the `steem_instance=` parameter to assure that all objects use the same steem object. When the `steem_instance=` parameter is not used, the steem object is taken from `get_shared_steam_instance()`.

`beem.instance.shared_steam_instance()` returns a global instance of steem. It can be set by `beem.instance.set_shared_steam_instance()` otherwise it is created on the first call.

```
from beem import Steem
from beem.account import Account
stm = Steem()
account = Account("test", steem_instance=stm)
```

```
from beem import Steem
from beem.account import Account
from beem.instance import set_shared_steam_instance
stm = Steem()
```

(continues on next page)

(continued from previous page)

```
set_shared_steam_instance(stm)
account = Account("test")
```

3.2.3 Wallet and Keys

Each account has the following keys:

- Posting key (allows accounts to post, vote, edit, resteem and follow/mute)
- Active key (allows accounts to transfer, power up/down, voting for witness, ...)
- Memo key (Can be used to encrypt/decrypt memos)
- Owner key (The most important key, should not be used with beem)

Outgoing operation, which will be stored in the steem blockchain, have to be signed by a private key. E.g. Comment or Vote operation need to be signed by the posting key of the author or upvoter. Private keys can be provided to beem temporary or can be stored encrypted in a sql-database (wallet).

Note: Before using the wallet the first time, it has to be created and a password has to set. The wallet content is available to beempy and all python scripts, which have access to the sql database file.

Creating a wallet

`steem.wallet.wipe(True)` is only necessary when there was already an wallet created.

```
from beem import Steem
steem = Steem()
steem.wallet.wipe(True)
steem.wallet.unlock("wallet-passphrase")
```

Adding keys to the wallet

```
from beem import Steem
steem = Steem()
steem.wallet.unlock("wallet-passphrase")
steem.wallet.addPrivateKey("xxxxxx")
steem.wallet.addPrivateKey("xxxxxx")
```

Using the keys in the wallet

```
from beem import Steem
steem = Steem()
steem.wallet.unlock("wallet-passphrase")
account = Account("test", steem_instance=steem)
account.transfer("<to>", "<amount>", "<asset>", "<memo>")
```

Private keys can also set temporary

```
from beem import Steem
steem = Steem(keys=["xxxxxxxxxx"])
account = Account("test", steem_instance=steem)
account.transfer("<to>", "<amount>", "<asset>", "<memo>")
```

3.2.4 Receiving information about blocks, accounts, votes, comments, market and witness

Receive all Blocks from the Blockchain

```
from beem.blockchain import Blockchain
blockchain = Blockchain()
for op in blockchain.stream():
    print(op)
```

Access one Block

```
from beem.block import Block
print(Block(1))
```

Access an account

```
from beem.account import Account
account = Account("test")
print(account.balances)
for h in account.history():
    print(h)
```

A single vote

```
from beem.vote import Vote
vote = Vote(u"@gtg/ffdhu-gtg-witness-log|gandalf")
print(vote.json())
```

All votes from an account

```
from beem.vote import AccountVotes
allVotes = AccountVotes("gtg")
```

Access a post

```
from beem.comment import Comment
comment = Comment("@gtg/ffdhu-gtg-witness-log")
print(comment["active_votes"])
```

Access the market

```
from beem.market import Market
market = Market("SBD:STEEM")
print(market.ticker())
```

Access a witness

```
from beem.witness import Witness
witness = Witness("gtg")
print(witness.is_active)
```

3.2.5 Sending transaction to the blockchain

Sending a Transfer

```
from beem import Steem
steem = Steem()
steem.wallet.unlock("wallet-passphrase")
account = Account("test", steem_instance=steem)
account.transfer("null", 1, "SBD", "test")
```

Upvote a post

```
from beem.comment import Comment
from beem import Steem
steem = Steem()
steem.wallet.unlock("wallet-passphrase")
comment = Comment("@gtg/ffdhu-gtg-witness-log", steem_instance=steem)
comment.upvote(weight=10, voter="test")
```

Publish a post to the blockchain

```
from beem import Steem
steem = Steem()
steem.wallet.unlock("wallet-passphrase")
steem.post("title", "body", author="test", tags=["a", "b", "c", "d", "e"], self_
→vote=True)
```

Sell STEEM on the market

```
from beem.market import Market
from beem import Steem
steem.wallet.unlock("wallet-passphrase")
market = Market("SBD:STEEM", steem_instance=steem)
print(market.ticker())
market.steem.wallet.unlock("wallet-passphrase")
print(market.sell(300, 100)) # sell 100 STEEM for 300 STEEM/SBD
```

3.3 Tutorials

3.3.1 Bundle Many Operations

With Steem, you can bundle multiple operations into a single transactions. This can be used to do a multi-send (one sender, multiple receivers), but it also allows to use any other kind of operation. The advantage here is that the user can be sure that the operations are executed in the same order as they are added to the transaction.

A block can only include one vote operation and one comment operation from each sender.

```

from pprint import pprint
from beem import Steem
from beem.account import Account
from beem.comment import Comment
from beem.instance import set_shared_steam_instance

# not a real working key
wif = "5KQwrPbwL6PhXujxW37FSSQZ1JiwsST4cqQzDeyXtP79zkvFD3"

stm = Steem(
    bundle=True, # Enable bundle broadcast
    # nobroadcast=True, # Enable this for testing
    keys=[wif],
)
# Set stm as shared instance
set_shared_steam_instance(stm)

# Account and Comment will use now stm
account = Account("test")

# Post
c = Comment("@gtg/witness-gtg-log")

account.transfer("test1", 1, "STEEM")
account.transfer("test2", 1, "STEEM")
account.transfer("test3", 1, "SBD")
# Upvote post with 25%
c.upvote(25, voter=account)

pprint(stm.broadcast())

```

3.3.2 Use nobroadcast for testing

When using `nobroadcast=True` the transaction is not broadcasted but printed.

```

from pprint import pprint
from beem import Steem
from beem.account import Account
from beem.instance import set_shared_steam_instance

# Only for testing not a real working key
wif = "5KQwrPbwL6PhXujxW37FSSQZ1JiwsST4cqQzDeyXtP79zkvFD3"

# set nobroadcast always to True, when testing
testnet = Steem(
    nobroadcast=True, # Set to false when want to go live
    keys=[wif],
)
# Set testnet as shared instance
set_shared_steam_instance(testnet)

# Account will use now testnet
account = Account("test")

pprint(account.transfer("test1", 1, "STEEM"))

```

When executing the script above, the output will be similar to the following:

```
Not broadcasting anything!
{'expiration': '2018-05-01T16:16:57',
 'extensions': [],
 'operations': [[{'transfer':
      {'amount': '1.000 STEEM',
       'from': 'test',
       'memo': '',
       'to': 'test1'}}]],
 'ref_block_num': 33020,
 'ref_block_prefix': 2523628005,
 'signatures': [
 ↪'1f57da50f241e70c229ed67b5d61898e792175c0f18ae29df8af414c46ae91eb5729c867b5d7dcc578368e7024e414c23
 ↪']]}
```

3.3.3 Clear BlockchainObject Caching

Each BlockchainObject (Account, Comment, Vote, Witness, Amount, ...) has a glocal cache. This cache stores all objects and could lead to increased memory consumption. The global cache can be cleared with a `clear_cache()` call from any BlockchainObject.

```
from pprint import pprint
from beem.account import Account

account = Account("test")
pprint(str(account._cache))
account1 = Account("test1")
pprint(str(account._cache))
pprint(str(account1._cache))
account.clear_cache()
pprint(str(account._cache))
pprint(str(account1._cache))
```

3.3.4 Simple Sell Script

```
from beem import Steem
from beem.market import Market
from beem.price import Price
from beem.amount import Amount

# Only for testing not a real working key
wif = "5KQwrPbwL6PhXujxW37FSSQZ1JiwsST4cqQzDeyXtP79zkvFD3"

#
# Instantiate Steem (pick network via API node)
#
steem = Steem(
    nobroadcast=True,    # <<---- set this to False when you want to fire!
    keys=[wif]          # <<---- use your real keys, when going live!
)

#
# This defines the market we are looking at.
```

(continues on next page)

(continued from previous page)

```
# The first asset in the first argument is the *quote*
# Sell and buy calls always refer to the *quote*
#
market = Market("SBD:STEEM",
                 steem_instance=steem
)
#
# Sell an asset for a price with amount (quote)
#
print(market.sell(
    Price(100.0, "STEEM/SBD"),
    Amount("0.01 SBD")
))
```

3.3.5 Sell at a timely rate

```
import threading
from beem import Steem
from beem.market import Market
from beem.price import Price
from beem.amount import Amount

# Only for testing not a real working key
wif = "5KQwrPbwL6PhXujxW37FSSQZ1JiwsST4cqQzDeyXtP79zkvFD3"

def sell():
    """ Sell an asset for a price with amount (quote)
    """
    print(market.sell(
        Price(100.0, "SBD/STEEM"),
        Amount("0.01 STEEM")
    ))

    threading.Timer(60, sell).start()

if __name__ == "__main__":
    #
    # Instantiate Steem (pick network via API node)
    #
    steem = Steem(
        nobroadcast=True,      # <<---- set this to False when you want to fire!
        keys=[wif]            # <<---- use your real keys, when going live!
    )

    #
    # This defines the market we are looking at.
    # The first asset in the first argument is the *quote*
    # Sell and buy calls always refer to the *quote*
    #
    market = Market("STEEM:SBD",
                    steem_instance=steem
    )
```

(continues on next page)

(continued from previous page)

sell()

3.3.6 Batch api calls on AppBase

Batch api calls are possible with AppBase RPC nodes. If you call a Api-Call with add_to_queue=True it is not submitted but stored in rpc_queue. When a call with add_to_queue=False (default setting) is started, the complete queue is sended at once to the node. The result is a list with replies.

```
from beem import Steem
stm = Steem("https://api.steemit.com")
stm.rpc.get_config(add_to_queue=True)
stm.rpc.rpc_queue
```

```
[{'method': 'condenser_api.get_config', 'jsonrpc': '2.0', 'params': [], 'id': 6}]
```

```
result = stm.rpc.get_block({"block_num":1}, api="block", add_to_queue=False)
len(result)
```

```
2
```

3.3.7 Account history

Lets calculate the curation reward from the last 7 days:

```
from datetime import datetime, timedelta
from beem.account import Account
from beem.amount import Amount

acc = Account("gtg")
stop = datetime.utcnow() - timedelta(days=7)
reward_vests = Amount("0 VESTS")
for reward in acc.history_reverse(stop=stop, only_ops=["curation_reward"]):
    reward_vests += Amount(reward['reward'])
curation_rewards_SP = acc.steem.vests_to_sp(reward_vests.amount)
print("Rewards are %.3f SP" % curation_rewards_SP)
```

Lets display all Posts from an account:

```
from beem.account import Account
from beem.comment import Comment
from beem.exceptions import ContentDoesNotExistException
account = Account("holger80")
c_list = {}
for c in map(Comment, account.history(only_ops=["comment"])):
    if c_permalink in c_list:
        continue
    try:
        c.refresh()
    except ContentDoesNotExistException:
        continue
    c_list[c_permalink] = 1
```

(continues on next page)

(continued from previous page)

```
if not c.is_comment():
    print("%s" % c.title)
```

3.3.8 Transactionbuilder

Sign transactions with beem without using the wallet and build the transaction by hand. Example with one operation with and without the wallet:

```
from beem import Steem
from beem.transactionbuilder import TransactionBuilder
from beembase import operations
stm = Steem()
# Uncomment the following when using a wallet:
# stm.wallet.unlock("secret_password")
tx = TransactionBuilder(steem_instance=stm)
op = operations.Transfer(**{"from": 'user_a',
                           "to": 'user_b',
                           "amount": '1.000 SBD',
                           "memo": 'test 2'})
tx.appendOps(op)
# Comment appendWif out and uncomment appendSigner when using a stored key from the
# →wallet
tx.appendWif('5.....') # `user_a`
# tx.appendSigner('user_a', 'active')
tx.sign()
tx.broadcast()
```

Example with signing and broadcasting two operations:

```
from beem import Steem
from beem.transactionbuilder import TransactionBuilder
from beembase import operations
stm = Steem()
# Uncomment the following when using a wallet:
# stm.wallet.unlock("secret_password")
tx = TransactionBuilder(steem_instance=stm)
ops = []
op = operations.Transfer(**{"from": 'user_a',
                           "to": 'user_b',
                           "amount": '1.000 SBD',
                           "memo": 'test 2'})
ops.append(op)
op = operations.Vote(**{"voter": v,
                       "author": author,
                       "permlink": permlink,
                       "weight": int(percent * 100)})
ops.append(op)
tx.appendOps(ops)
# Comment appendWif out and uncomment appendSigner when using a stored key from the
# →wallet
tx.appendWif('5.....') # `user_a`
# tx.appendSigner('user_a', 'active')
tx.sign()
tx.broadcast()
```

3.4 beempy CLI

beempy is a convenient CLI utility that enables you to manage your wallet, transfer funds, check balances and more.

3.4.1 Using the Wallet

beempy lets you leverage your BIP38 encrypted wallet to perform various actions on your accounts.

The first time you use *beempy*, you will be prompted to enter a password. This password will be used to encrypt the *beempy* wallet, which contains your private keys.

You can change the password via *changewalletpassphrase* command.

```
beempy changewalletpassphrase
```

From this point on, every time an action requires your private keys, you will be prompted to enter this password (from CLI as well as while using *steem* library).

To bypass password entry, you can set an environment variable `UNLOCK`.

```
UNLOCK=mysecretpassword beempy transfer <recipient_name> 100 STEEM
```

3.4.2 Using a key json file

A `key_file.json` can be used to provide private keys to *beempy*:

```
{  
    "account_a": {"posting": "5xx", "active": "5xx"},  
    "account_b": {"posting": "5xx"},  
}
```

with

```
beempy --key key_file.json command
```

When set, the wallet cannot be used.

3.4.3 Common Commands

First, you may like to import your Steem account:

```
beempy importaccount
```

You can also import individual private keys:

```
beempy addkey <private_key>
```

Listing accounts:

```
beempy listaccounts
```

Show balances:

```
beempy balance account_name1 account_name2
```

Sending funds:

```
beempy transfer --account <account_name> <recipient_name> 100 STEEM memo
```

Upvoting a post:

```
beempy upvote --account <account_name> https://steemit.com/funny/@mynameisbrian/the-  
→content-stand-a-comic
```

3.4.4 Setting Defaults

For a more convenient use of beempy as well as the beem library, you can set some defaults. This is especially useful if you have a single Steem account.

```
beempy set default_account test
beempy set default_vote_weight 100

beempy config
+-----+-----+
| Key           | Value   |
+-----+-----+
| default_account | test    |
| default_vote_weight | 100    |
+-----+-----+
```

If you've set up your *default_account*, you can now send funds by omitting this field:

```
beempy transfer <recipient_name> 100 STEEM memo
```

3.4.5 Commands

beempy

```
beempy [OPTIONS] COMMAND1 [ARGS]... [COMMAND2 [ARGS]...]...
```

Options

- n, --node** <node>
URL for public Steem API (e.g. <https://api.steemit.com>)
- o, --offline**
Prevent connecting to network
- d, --no-broadcast**
Do not broadcast
- p, --no-wallet**
Do not load the wallet
- x, --unsigned**
Nothing will be signed

```
-l, --create-link  
    Creates steemconnect/hivesigner links from all broadcast operations  
  
-s, --steem  
    Connect to the Steem blockchain  
  
-h, --hive  
    Connect to the Hive blockchain  
  
-k, --keys <keys>  
    JSON file that contains account keys, when set, the wallet cannot be used.  
  
-u, --use-ledger  
    Uses the ledger device Nano S for signing.  
  
--path <path>  
    BIP32 path from which the keys are derived, when not set, default_path is used.  
  
-t, --token  
    Uses a hivesigner/steemconnect token to broadcast (only broadcast operation with posting permission)  
  
-e, --expires <expires>  
    Delay in seconds until transactions are supposed to expire(defaults to 60)  
  
-v, --verbose <verbose>  
    Verbosity  
  
--version  
    Show the version and exit.
```

about

About beempy

```
beempy about [OPTIONS]
```

addkey

Add key to wallet

When no [OPTION] is given, a password prompt for unlocking the wallet and a prompt for entering the private key are shown.

```
beempy addkey [OPTIONS]
```

Options

```
--unsafe-import-key <unsafe_import_key>  
    Private key to import to wallet (unsafe, unless shell history is deleted afterwards)
```

addtoken

Add key to wallet

When no [OPTION] is given, a password prompt for unlocking the wallet and a prompt for entering the private key are shown.

```
beempy addtoken [OPTIONS] NAME
```

Options

--unsafe-import-token <unsafe_import_token>

Private key to import to wallet (unsafe, unless shell history is deleted afterwards)

Arguments

NAME

Required argument

allow

Allow an account/key to interact with your account

foreign_account: The account or key that will be allowed to interact with account. When not given, password will be asked, from which a public key is derived. This derived key will then interact with your account.

```
beempy allow [OPTIONS] [FOREIGN_ACCOUNT]
```

Options

--permission <permission>

The permission to grant (defaults to “posting”)

-a, --account <account>

The account to allow action for

--weight <weight>

The weight to use instead of the (full) threshold. If the weight is smaller than the threshold, additional signatures are required

--threshold <threshold>

The permission’s threshold that needs to be reached by signatures to be able to interact

Arguments

FOREIGN_ACCOUNT

Optional argument

approvewitness

Approve a witnesses

```
beempy approvewitness [OPTIONS] WITNESS
```

Options

-a, --account <account>
Your account

Arguments

WITNESS
Required argument

balance

Shows balance

```
beempy balance [OPTIONS] [ACCOUNT]...
```

Arguments

ACCOUNT
Optional argument(s)

beneficiaries

Set beneficiaries

```
beempy beneficiaries [OPTIONS] AUTHORPERM [BENEFICIARIES]...
```

Arguments

AUTHORPERM
Required argument

BENEFICIARIES
Optional argument(s)

broadcast

broadcast a signed transaction

```
beempy broadcast [OPTIONS]
```

Options

--file <file>
Load transaction from file. If “-“, read from stdin (defaults to “-“)

buy

Buy STEEM/HIVE or SBD/HBD from the internal market

Limit buy price denoted in (SBD per STEEM or HBD per HIVE)

```
beempy buy [OPTIONS] AMOUNT ASSET [PRICE]
```

Options

-a, --account <account>
Buy with this account (defaults to “default_account”)

--orderid <orderid>
Set an orderid

Arguments

AMOUNT
Required argument

ASSET
Required argument

PRICE
Optional argument

cancel

Cancel order in the internal market

```
beempy cancel [OPTIONS] ORDERID
```

Options

-a, --account <account>
Sell with this account (defaults to “default_account”)

Arguments

ORDERID
Required argument

changekeys

Changes all keys for the specified account Keys are given in their public form. Asks for the owner key for broadcasting the op to the chain.

```
beempy changekeys [OPTIONS] ACCOUNT
```

Options

```
--owner <owner>
    Main owner public key - when not given, a passphrase is used to create keys.

--active <active>
    Active public key - when not given, a passphrase is used to create keys.

--posting <posting>
    posting public key - when not given, a passphrase is used to create keys.

--memo <memo>
    Memo public key - when not given, a passphrase is used to create keys.

-i, --import-pub <import_pub>
    Load public keys from file.
```

Arguments

ACCOUNT
Required argument

changerecovery

Changes the recovery account with the owner key (needs 30 days to be active)

```
beempy changerecovery [OPTIONS] NEW_RECOVERY_ACCOUNT
```

Options

```
-a, --account <account>
    Change the recovery account from this account
```

Arguments

NEW_RECOVERY_ACCOUNT
Required argument

changewalletpassphrase

Change wallet password

```
beempy changewalletpassphrase [OPTIONS]
```

claimaccount

Claim account for claimed account creation.

```
beempy claimaccount [OPTIONS] CREATOR
```

Options

--fee <fee>

When fee is 0 (default) a subsidized account is claimed and can be created later with create_claimed_account

-n, --number <number>

Number of subsidized accounts to be claimed (default = 1), when fee = 0 STEEM

Arguments

CREATOR

Required argument

claimreward

Claim reward balances

By default, this will claim all outstanding balances.

```
beempy claimreward [OPTIONS] [ACCOUNT]
```

Options

--reward_steam <reward_steam>

Amount of STEEM/HIVE you would like to claim

--reward_sbd <reward_sbd>

Amount of SBD/HBD you would like to claim

--reward_vests <reward_vests>

Amount of VESTS you would like to claim

--claim_all_steam

Claim all STEEM/HIVE, overwrites reward_steam

--claim_all_sbd

Claim all SBD/HBD, overwrites reward_sbd

--claim_all_vests

Claim all VESTS, overwrites reward_vests

Arguments

ACCOUNT

Optional argument

config

Shows local configuration

```
beempy config [OPTIONS]
```

convert

Convert SBD/HBD to Steem/Hive (takes a week to settle)

```
beempy convert [OPTIONS] AMOUNT
```

Options

-a, --account <account>
Powerup from this account

Arguments

AMOUNT

Required argument

createwallet

Create new wallet with a new password

```
beempy createwallet [OPTIONS]
```

Options

--wipe
Wipe old wallet without prompt.

curation

Lists curation rewards of all votes for authorperm

When authorperm is empty or “all”, the curation rewards for all account votes are shown.

authorperm can also be a number. e.g. 5 is equivalent to the fifth account vote in the given time duration (default is 7 days)

```
beempy curation [OPTIONS] [AUTHORPERM]
```

Options

-a, --account <account>
Show only curation for this account

-m, --limit <limit>
Show only the first minutes

-v, --min-vote <min_vote>
Show only votes higher than the given value

-w, --max-vote <max_vote>
Show only votes lower than the given value

```
-x, --min-performance <min_performance>
    Show only votes with performance higher than the given value in HBD/SBD

-y, --max-performance <max_performance>
    Show only votes with performance lower than the given value in HBD/SBD

--payout <payout>
    Show the curation for a potential payout in SBD as float

-e, --export <export>
    Export results to HTML-file

-s, --short
    Show only Curation without sum

-l, --length <length>
    Limits the permlink character length

-p, --permlink
    Show the permlink for each entry

-t, --title
    Show the title for each entry

-d, --days <days>
    Limit shown rewards by this amount of days (default: 7), max is 7 days.
```

Arguments

AUTHORPERM

Optional argument

currentnode

Sets the currently working node at the first place in the list

```
beempy currentnode [OPTIONS]
```

Options

```
--version
    Returns only the raw version value

--url
    Returns only the raw url value
```

customjson

Broadcasts a custom json

First parameter is the custom json id, the second field is a json file or a json key value combination e.g. beempy customjson -a holger80 dw-heist username holger80 amount 100

```
beempy customjson [OPTIONS] JSONID [JSON_DATA]...
```

Options

- a, --account <account>**
The account which broadcasts the custom_json
- t, --active**
When set, the active key is used for broadcasting

Arguments

JSONID
Required argument

JSON_DATA
Optional argument(s)

delegate

Delegate (start delegating VESTS to another account)

amount is in VESTS / Steem

```
beempy delegate [OPTIONS] AMOUNT TO_ACCOUNT
```

Options

- a, --account <account>**
Delegate from this account

Arguments

AMOUNT
Required argument

TO_ACCOUNT
Required argument

delete

delete a post/comment

POST is @author/permlink

```
beempy delete [OPTIONS] POST
```

Options

- a, --account <account>**
Voter account name

Arguments

POST

Required argument

delkey

Delete key from the wallet

PUB is the public key from the private key which will be deleted from the wallet

```
beempy delkey [OPTIONS] PUB
```

Options

--confirm

Please confirm!

Arguments

PUB

Required argument

delprofile

Delete a variable in an account's profile

```
beempy delprofile [OPTIONS] VARIABLE...
```

Options

-a, --account <account>

delprofile as this user

Arguments

VARIABLE

Required argument(s)

delproxy

Delete your witness/proposal system proxy

```
beempy delproxy [OPTIONS]
```

Options

-a, --account <account>
Your account

deltoken

Delete name from the wallet

name is the public name from the private token which will be deleted from the wallet

```
beempy deltoken [OPTIONS] NAME
```

Options

--confirm
Please confirm!

Arguments

NAME
Required argument

disallow

Remove allowance an account/key to interact with your account

```
beempy disallow [OPTIONS] [FOREIGN_ACCOUNT]
```

Options

--permission <permission>
The permission to grant (defaults to “posting”)
-a, --account <account>
The account to disallow action for
--threshold <threshold>
The permission’s threshold that needs to be reached by signatures to be able to interact

Arguments

FOREIGN_ACCOUNT
Optional argument

disapprovewitness

Disapprove a witnesses

```
beempy disapprovewitness [OPTIONS] WITNESS
```

Options

-a, --account <account>

Your account

Arguments

WITNESS

Required argument

download

Download body with yaml header

```
beempy download [OPTIONS] [PERMLINK] ...
```

Options

-a, --account <account>

Account are you posting from

-s, --save

Saves markdown in current directoy as date_permalink.md

-e, --export <export>

Export markdown to given a md-file name

Arguments

PERMLINK

Optional argument(s)

downvote

Downvote a post/comment

POST is @author/permalink

```
beempy downvote [OPTIONS] POST
```

Options

```
-a, --account <account>
Voter account name

-w, --weight <weight>
Downvote weight (from 0.1 to 100.0)
```

Arguments

POST

Required argument

featureflags

Get the account's feature flags.

The request has to be signed by the requested account or an admin account.

```
beempy featureflags [OPTIONS] [ACCOUNT]
```

Options

```
-s, --signing-account <signing_account>
Signing account, when empty account is used.
```

Arguments

ACCOUNT

Optional argument

follow

Follow another account

```
beempy follow [OPTIONS] FOLLOW
```

Options

```
-a, --account <account>
Follow from this account

--what <what>
Follow these objects (defaults to ["blog"])
```

Arguments

FOLLOW

Required argument

follower

Get information about followers

```
beempy follower [OPTIONS] [ACCOUNT] ...
```

Arguments

ACCOUNT

Optional argument(s)

following

Get information about following

```
beempy following [OPTIONS] [ACCOUNT] ...
```

Arguments

ACCOUNT

Optional argument(s)

importaccount

Import an account using a passphrase

```
beempy importaccount [OPTIONS] ACCOUNT
```

Options

--roles <roles>

Import specified keys (owner, active, posting, memo).

Arguments

ACCOUNT

Required argument

info

Show basic blockchain info

General information about the blockchain, a block, an account, a post/comment and a public key

```
beempy info [OPTIONS] [OBJECTS] ...
```

Arguments

OBJECTS

Optional argument(s)

interest

Get information about interest payment

```
beempy interest [OPTIONS] [ACCOUNT] ...
```

Arguments

ACCOUNT

Optional argument(s)

keygen

Creates a new random BIP39 key or password based key and prints its derived private key and public key. The generated key is not stored. Can also be used to create new keys for an account. Can also be used to derive account keys from a password or BIP39 wordlist

```
beempy keygen [OPTIONS]
```

Options

-l, --import-word-list

Imports a BIP39 wordlist and derives a private and public key

--strength <strength>

Defines word list length for BIP39 (default = 256).

-p, --passphrase

Sets a BIP39 passphrase

-m, --path <path>

Sets a path for BIP39 key creations. When path is set, network, role, account_keys, account and sequence is not used

-n, --network <network>

Network index, when using BIP39, 0 for steem and 13 for hive, (default is 13)

-r, --role <role>

Defines the key role for BIP39 when a single key is generated (default = owner).

-k, --account-keys

Derives four BIP39 keys for each role

-s, --sequence <sequence>

Sequence key number, when using BIP39 (default is 0)

-a, --account <account>

account name for password based key generation or sequence number for BIP39 key, default = 0

-i, --import-password
Imports a password and derives all four account keys

-c, --create-password
Creates a new password and derives four account keys from it

-w, --wif <wif>
Defines how many times the password is replaced by its WIF representation for password based keys (default = 0).

-u, --export-pub <export_pub>
Exports the public account keys to a json file for account creation or keychange

-e, --export <export>
The results are stored in a text file and will not be shown

listaccounts

Show stored accounts

Can be used with the ledger to obtain all accounts that uses pubkeys derived from this ledger

```
beempy listaccounts [OPTIONS]
```

Options

-r, --role <role>
When set, limits the shown keys for this role

-a, --max-account-index <max_account_index>
Set maximum account index to check pubkeys (only when using ledger)

-s, --max-sequence <max_sequence>
Set maximum key sequence to check pubkeys (only when using ledger)

listkeys

Show stored keys

Can be used to receive and approve the pubkey obtained from the ledger

```
beempy listkeys [OPTIONS]
```

Options

-p, --path <path>
Set path (when using ledger)

-a, --ledger-approval
When set, you can confirm the shown pubkey on your ledger.

listtoken

Show stored token

```
beempy listtoken [OPTIONS]
```

mute

Mute another account

```
beempy mute [OPTIONS] MUTE
```

Options

-a, --account <account>

Mute from this account

--what <what>

Mute these objects (defaults to [“ignore”])

Arguments

MUTE

Required argument

muter

Get information about muter

```
beempy muter [OPTIONS] [ACCOUNT] ...
```

Arguments

ACCOUNT

Optional argument(s)

muting

Get information about muting

```
beempy muting [OPTIONS] [ACCOUNT] ...
```

Arguments

ACCOUNT

Optional argument(s)

newaccount

Create a new account Default setting is that a fee is payed for account creation Use –create-claimed-account for free account creation

Please use keygen and set public keys

```
beempy newaccount [OPTIONS] ACCOUNTNAME
```

Options

-a, --account <account>

Account that pays the fee or uses account tickets

--owner <owner>

Main public owner key - when not given, a passphrase is used to create keys.

--active <active>

Active public key - when not given, a passphrase is used to create keys.

--memo <memo>

Memo public key - when not given, a passphrase is used to create keys.

--posting <posting>

posting public key - when not given, a passphrase is used to create keys.

-w, --wif <wif>

Defines how many times the password is replaced by its WIF representation for password based keys (default = 0).

-c, --create-claimed-account

Instead of paying the account creation fee a subsidized account is created.

-i, --import-pub <import_pub>

Load public keys from file.

Arguments

ACCOUNTNAME

Required argument

nextnode

Uses the next node in list

```
beempy nextnode [OPTIONS]
```

Options

--results

Shows result of changing the node.

notifications

Show notifications of an account

```
beempy notifications [OPTIONS] [ACCOUNT]
```

Options

- l, --limit <limit>**
Limits shown notifications
- a, --all**
Show all notifications (when not set, only unread are shown)
- m, --mark_as_read**
Broadcast a mark all as read custom json
- r, --replies**
Show only replies
- t, --mentions**
Show only mentions
- f, --follows**
Show only follows
- v, --votes**
Show only upvotes
- b, --reblogs**
Show only reblogs

Arguments

ACCOUNT

Optional argument

openorders

Show open orders

```
beempy openorders [OPTIONS] [ACCOUNT]
```

Arguments

ACCOUNT

Optional argument

orderbook

Obtain orderbook of the internal market

```
beempy orderbook [OPTIONS]
```

Options

--chart

Enable charting

-l, --limit <limit>

Limit number of returned open orders (default 25)

--show-date

Show dates

-w, --width <width>

Plot width (default 75)

-h, --height <height>

Plot height (default 15)

--ascii

Use only ascii symbols

parsewif

Parse a WIF private key without importing

```
beempy parsewif [OPTIONS]
```

Options

--unsafe-import-key <unsafe_import_key>

WIF key to parse (unsafe, unless shell history is deleted afterwards)

pending

Lists pending rewards

```
beempy pending [OPTIONS] [ACCOUNTS]...
```

Options

-s, --only-sum

Show only the sum

-p, --post

Show pending post payout

-c, --comment

Show pending comments payout

-v, --curation

Shows pending curation

```
-l, --length <length>
    Limits the permalink character length

-a, --author
    Show the author for each entry

-e, --permalink
    Show the permalink for each entry

-t, --title
    Show the title for each entry

-d, --days <days>
    Limit shown rewards by this amount of days (default: 7), max is 7 days.

-f, --from <_from>
    Start day from which on rewards are shown (default: 0), max is 7 days.
```

Arguments

ACCOUNTS

Optional argument(s)

permissions

Show permissions of an account

```
beempy permissions [OPTIONS] [ACCOUNT]
```

Arguments

ACCOUNT

Optional argument

pingnode

Returns the answer time in milliseconds

```
beempy pingnode [OPTIONS]
```

Options

```
--raw
    Returns only the raw value

--sort
    Sort all nodes by ping value

--remove
    Remove node with errors from list

--threading
    Use a thread for each node
```

post

broadcasts a post/comment. All image links which links to a file will be uploaded. The yaml header can contain:

```
— title: your title tags: tag1,tag2 community: hive-100000 beneficiaries: beempy:5%,holger80:5% —
```

```
beempy post [OPTIONS] MARKDOWN_FILE
```

Options

- a, --account <account>**
Account are you posting from
- t, --title <title>**
Title of the post
- p, --permlink <permlink>**
Manually set the permlink (optional)
- g, --tags <tags>**
A komma separated list of tags to go with the post.
- r, --reply_identifier <reply_identifier>**
Identifier of the parent post/comment, when set a comment is broadcasted
- c, --community <community>**
Name of the community (optional)
- b, --beneficiaries <beneficiaries>**
Post beneficiaries (komma separated, e.g. a:10%,b:20%)
- d, --percent-steem-dollars <percent_steem_dollars>**
50% SBD /50% SP is 10000 (default), 100% SP is 0
- m, --max-accepted-payout <max_accepted_payout>**
Default is 1000000.000 [SBD]
- n, --no-parse-body**
Disable parsing of links, tags and images
- e, --no-patch-on-edit**
Disable patch posting on edits (when the permlink already exists)

Arguments

MARKDOWN_FILE

Required argument

power

Shows vote power and bandwidth

```
beempy power [OPTIONS] [ACCOUNT]...
```

Arguments

ACCOUNT

Optional argument(s)

powerdown

Power down (start withdrawing VESTS from Steem POWER)

amount is in VESTS

```
beempy powerdown [OPTIONS] AMOUNT
```

Options

-a, --account <account>

Powerup from this account

Arguments

AMOUNT

Required argument

powerdownroute

Setup a powerdown route

```
beempy powerdownroute [OPTIONS] TO
```

Options

--percentage <percentage>

The percent of the withdraw to go to the “to” account

-a, --account <account>

Powerup from this account

--auto_vest

Set to true if the from account should receive the VESTS asVESTS, or false if it should receive them as STEEM/HIVE.

Arguments

TO

Required argument

powerup

Power up (vest STEEM/HIVE as STEEM/HIVE POWER)

```
beempy powerup [OPTIONS] AMOUNT
```

Options

-a, --account <account>
Powerup from this account

--to <to>
Powerup this account

Arguments

AMOUNT
Required argument

pricehistory

Show price history

```
beempy pricehistory [OPTIONS]
```

Options

-w, --width <width>
Plot width (default 75)
-h, --height <height>
Plot height (default 15)
--ascii
Use only ascii symbols

reblog

Reblog an existing post

```
beempy reblog [OPTIONS] IDENTIFIER
```

Options

-a, --account <account>
Reblog as this user

Arguments

IDENTIFIER

Required argument

reply

replies to a comment

```
beempy reply [OPTIONS] AUTHORPERM BODY
```

Options

-a, --account <account>

Account are you posting from

-t, --title <title>

Title of the post

Arguments

AUTHORPERM

Required argument

BODY

Required argument

rewards

Lists received rewards

```
beempy rewards [OPTIONS] [ACCOUNTS]...
```

Options

-s, --only-sum

Show only the sum

-p, --post

Show post payout

-c, --comment

Show comments payout

-v, --curation

Shows curation

-l, --length <length>

Limits the permalink character length

-a, --author

Show the author for each entry

-e, --permlink
 Show the permlink for each entry

-t, --title
 Show the title for each entry

-d, --days <days>
 Limit shown rewards by this amount of days (default: 7)

Arguments

ACCOUNTS
 Optional argument(s)

sell

Sell STEEM/HIVE or SBD/HBD from the internal market
 Limit sell price denoted in (SBD per STEEM) or (HBD per HIVE)

```
beempy sell [OPTIONS] AMOUNT ASSET [PRICE]
```

Options

-a, --account <account>
 Sell with this account (defaults to “default_account”)

--orderid <orderid>
 Set an orderid

Arguments

AMOUNT
 Required argument

ASSET
 Required argument

PRICE
 Optional argument

set

Set default_account, default_vote_weight or nodes

set [key] [value]

Examples:

Set the default vote weight to 50 %: set default_vote_weight 50

```
beempy set [OPTIONS] KEY VALUE
```

Arguments

KEY

Required argument

VALUE

Required argument

setprofile

Set a variable in an account's profile

```
beempy setprofile [OPTIONS] [VARIABLE] [VALUE]
```

Options

-a, --account <account>

setprofile as this user

-p, --pair <pair>

"Key=Value" pairs

Arguments

VARIABLE

Optional argument

VALUE

Optional argument

setproxy

Set your witness/proposal system proxy

```
beempy setproxy [OPTIONS] PROXY
```

Options

-a, --account <account>

Your account

Arguments

PROXY

Required argument

sign

Sign a provided transaction with available and required keys

```
beempy sign [OPTIONS]
```

Options

-i, --file <file>
Load transaction from file. If “-“, read from stdin (defaults to “-“)

-o, --outfile <outfile>
Load transaction from file. If “-“, read from stdin (defaults to “-“)

ticker

Show ticker

```
beempy ticker [OPTIONS]
```

Options

-i, --sbd-to-steem
Show ticker in SBD/STEEM

tradehistory

Show price history

```
beempy tradehistory [OPTIONS]
```

Options

-d, --days <days>
Limit the days of shown trade history (default 7)
--hours <hours>
Limit the intervall history intervall (default 2 hours)
-i, --sbd-to-steem
Show ticker in SBD/STEEM
-l, --limit <limit>
Limit number of trades which is fetched at each intervall point (default 100)
-w, --width <width>
Plot width (default 75)
-h, --height <height>
Plot height (default 15)
--ascii
Use only ascii symbols

transfer

Transfer SBD/HD STEEM/HIVE

```
beempy transfer [OPTIONS] TO AMOUNT ASSET [MEMO]
```

Options

-a, --account <account>
Transfer from this account

Arguments

TO
Required argument

AMOUNT
Required argument

ASSET
Required argument

MEMO
Optional argument

unfollow

Unfollow/Unmute another account

```
beempy unfollow [OPTIONS] UNFOLLOW
```

Options

-a, --account <account>
UnFollow/UnMute from this account

Arguments

UNFOLLOW
Required argument

updatememokey

Update an account's memo key

```
beempy updatememokey [OPTIONS]
```

Options

-a, --account <account>
 The account to updatememokey action for

--key <key>
 The new memo key

updatenodes

Update the nodelist from @fullnodeupdate

```
beempy updatenodes [OPTIONS]
```

Options

-s, --show
 Prints the updated nodes

-h, --hive
 Switch to HIVE blockchain, when set to true.

-e, --steem
 Switch to STEEM nodes, when set to true.

-t, --test
 Do change the node list, only print the newest nodes setup.

--only-https
 Use only https nodes.

--only-wss
 Use only websocket nodes.

uploadimage

```
beempy uploadimage [OPTIONS] IMAGE
```

Options

-a, --account <account>
 Account name

-n, --image-name <image_name>
 Image name

Arguments

IMAGE
 Required argument

upvote

Upvote a post/comment

POST is @author/permalink

```
beempy upvote [OPTIONS] POST
```

Options

-w, --weight <weight>
Vote weight (from 0.1 to 100.0)

-a, --account <account>
Voter account name

Arguments

POST

Required argument

userdata

Get the account's email address and phone number.

The request has to be signed by the requested account or an admin account.

```
beempy userdata [OPTIONS] [ACCOUNT]
```

Options

-s, --signing-account <signing_account>
Signing account, when empty account is used.

Arguments

ACCOUNT

Optional argument

verify

Returns the public signing keys for a block

```
beempy verify [OPTIONS] [BLOCKNUMBER]
```

Options

- t, --trx <trx>**
Show only one transaction number
- u, --use-api**
Uses the get_potential_signatures api call

Arguments

BLOCKNUMBER

Optional argument

votes

List outgoing/incoming account votes

```
beempy votes [OPTIONS] [ACCOUNT]
```

Options

- direction <direction>**
in or out
- o, --outgoing**
Show outgoing votes
- i, --incoming**
Show incoming votes
- d, --days <days>**
Limit shown vote history by this amount of days (default: 2)
- e, --export <export>**
Export results to TXT-file

Arguments

ACCOUNT

Optional argument

walletinfo

Show info about wallet

```
beempy walletinfo [OPTIONS]
```

Options

```
-u, --unlock  
    Unlock wallet  
  
-l, --lock  
    Lock wallet
```

witness

List witness information

```
beempy witness [OPTIONS] WITNESS
```

Arguments

WITNESS
Required argument

witnesscreate

Create a witness

```
beempy witnesscreate [OPTIONS] WITNESS PUB_SIGNING_KEY
```

Options

```
--maximum_block_size <maximum_block_size>  
    Max block size  
  
--account_creation_fee <account_creation_fee>  
    Account creation fee  
  
--sbd_interest_rate <sbd_interest_rate>  
    SBD interest rate in percent  
  
--url <url>  
    Witness URL
```

Arguments

WITNESS
Required argument

PUB_SIGNING_KEY
Required argument

witnessdisable

Disable a witness

```
beempy witnessdisable [OPTIONS] WITNESS
```

Arguments

WITNESS

Required argument

witnessenable

Enable a witness

```
beempy witnessenable [OPTIONS] WITNESS SIGNING_KEY
```

Arguments

WITNESS

Required argument

SIGNING_KEY

Required argument

witnesses

List witnesses

```
beempy witnesses [OPTIONS] [ACCOUNT]
```

Options

--limit <limit>

How many witnesses should be shown

Arguments

ACCOUNT

Optional argument

witnessfeed

Publish price feed for a witness

```
beempy witnessfeed [OPTIONS] WITNESS [WIF]
```

Options

-b, --base <base>
Set base manually, when not set the base is automatically calculated.

-q, --quote <quote>
Steem quote manually, when not set the base is automatically calculated.

--support-peg
Supports peg adjusting the quote, is overwritten by -set-quote!

Arguments

WITNESS
Required argument

WIF
Optional argument

witnessproperties

Update witness properties of witness WITNESS with the witness signing key WIF

```
beempy witnessproperties [OPTIONS] WITNESS WIF
```

Options

--account_creation_fee <account_creation_fee>
Account creation fee (float)

--account_subsidy_budget <account_subsidy_budget>
Account subsidy per block

--account_subsidy_decay <account_subsidy_decay>
Per block decay of the account subsidy pool

--maximum_block_size <maximum_block_size>
Max block size

--sbd_interest_rate <sbd_interest_rate>
SBD interest rate in percent

--new_signing_key <new_signing_key>
Set new signing key

--url <url>
Witness URL

Arguments

WITNESS
Required argument

WIF
Required argument

witnessupdate

Change witness properties

```
beempy witnessupdate [OPTIONS]
```

Options

```
--witness <witness>
    Witness name

--maximum_block_size <maximum_block_size>
    Max block size

--account_creation_fee <account_creation_fee>
    Account creation fee

--sbd_interest_rate <sbd_interest_rate>
    SBD interest rate in percent

--url <url>
    Witness URL

--signing_key <signing_key>
    Signing Key
```

3.4.6 beempy --help

You can see all available commands with beempy --help

```
~ % beempy --help
Usage: cli.py [OPTIONS] COMMAND1 [ARGS]... [COMMAND2 [ARGS]...]...

Options:
  -n, --node TEXT          URL for public Steem API (e.g.
                           https://api.steemit.com)
  -o, --offline            Prevent connecting to network
  -d, --no-broadcast       Do not broadcast
  -p, --no-wallet          Do not load the wallet
  -x, --unsigned           Nothing will be signed
  -e, --expires INTEGER   Delay in seconds until transactions are supposed to
                           expire (defaults to 60)
  -v, --verbose INTEGER   Verbosity
  --version                Show the version and exit.
  --help                   Show this message and exit.

Commands:
  addkey                  Add key to wallet When no [OPTION] is given, ...
  allow                   Allow an account/key to interact with your...
  approvewitness          Approve a witnesses
  balance                 Shows balance
  broadcast               Broadcast a signed transaction
  buy                     Buy STEEM or SBD from the internal market...
  cancel                  Cancel order in the internal market
  changewalletpassphrase Change wallet password
  claimreward              Claim reward balances By default, this will...
```

(continues on next page)

(continued from previous page)

config	Shows local configuration
convert	Convert STEEMDollars to Steem (takes a week...)
createwallet	Create new wallet with a new password
currentnode	Sets the currently working node at the first...
delkey	Delete key from the wallet PUB is the public...
delprofile	Delete a variable in an account's profile
disallow	Remove allowance an account/key to interact...
disapprovewitness	Disapprove a witnesses
downvote	Downvote a post/comment POST is...
follow	Follow another account
follower	Get information about followers
following	Get information about following
importaccount	Import an account using a passphrase
info	Show basic blockchain info General...
interest	Get information about interest payment
listaccounts	Show stored accounts
listkeys	Show stored keys
mute	Mute another account
muter	Get information about muter
muting	Get information about muting
newaccount	Create a new account
nextnode	Uses the next node in list
openorders	Show open orders
orderbook	Obtain orderbook of the internal market
parsewif	Parse a WIF private key without importing
permissions	Show permissions of an account
pingnode	Returns the answer time in milliseconds
power	Shows vote power and bandwidth
powerdown	Power down (start withdrawing VESTS from...)
powerdownroute	Setup a powerdown route
powerup	Power up (vest STEEM as STEEM POWER)
pricehistory	Show price history
resteem	Resteem an existing post
sell	Sell STEEM or SBD from the internal market...
set	Set default_account, default_vote_weight or...
setprofile	Set a variable in an account's profile
sign	Sign a provided transaction with available...
ticker	Show ticker
tradehistory	Show price history
transfer	Transfer SBD/STEEM
unfollow	Unfollow/Unmute another account
updatememokey	Update an account's memo key
upvote	Upvote a post/comment POST is...
votes	List outgoing/incoming account votes
walletinfo	Show info about wallet
witnesscreate	Create a witness
witnesses	List witnesses
witnessupdate	Change witness properties

3.5 Configuration

The pysteem library comes with its own local configuration database that stores information like

- API node URLs
- default account name

- the encrypted master password
- the default voting weight
- if keyring should be used for unlocking the wallet

and potentially more.

You can access those variables like a regular dictionary by using

```
from beem import Steem
steem = Steem()
print(steem.config.items())
```

Keys can be added and changed like they are for regular dictionaries.

If you don't want to load the `beem.steem.Steem` class, you can load the configuration directly by using:

```
from beem.storage import configStorage as config
```

It is also possible to access the configuration with the commandline tool `beempy`:

```
beempy config
```

3.5.1 API node URLs

The default node URLs which will be used when `node` is `None` in `beem.steem.Steem` class is stored in `config["nodes"]` as string. The list can be get and set by:

```
from beem import Steem
steem = Steem()
node_list = steem.get_default_nodes()
node_list = node_list[1:] + [node_list[0]]
steem.set_default_nodes(node_list)
```

`beempy` can also be used to set nodes:

```
beempy set nodes wss://steemd.privex.io
beempy set nodes "['wss://steemd.privex.io', 'wss://gtg.steem.house:8090']"
```

The default nodes can be reset to the default value. When the first node does not answer, steem should be set to the offline mode. This can be done by:

```
beempy -o set nodes ""
```

or

```
from beem import Steem
steem = Steem(offline=True)
steem.set_default_nodes("")
```

3.5.2 Default account

The default account name is used in some functions, when no account name is given. It is also used in `beempy` for all account related functions.

```
from beem import Steem
steem = Steem()
steem.set_default_account("test")
steem.config["default_account"] = "test"
```

or by beempy with

```
beempy set default_account test
```

3.5.3 Default voting weight

The default vote weight is used for voting, when no vote weight is given.

```
from beem import Steem
steem = Steem()
steem.config["default_vote_weight"] = 100
```

or by beempy with

```
beempy set default_vote_weight 100
```

3.5.4 Setting password_storage

The password_storage can be set to:

- environment, this is the default setting. The master password for the wallet can be provided in the environment variable *UNLOCK*.
- keyring (when set with beempy, it asks for the wallet password)

```
beempy set password_storage environment
beempy set password_storage keyring
```

Environment variable for storing the master password

When *password_storage* is set to *environment*, the master password can be stored in *UNLOCK* for unlocking automatically the wallet.

Keyring support for beempy and wallet

In order to use keyring for storing the wallet password, the following steps are necessary:

- Install keyring: *pip install keyring*
- Change *password_storage* to *keyring* with *beempy* and enter the wallet password.

It also possible to change the password in the keyring by

```
python -m keyring set beem wallet
```

The stored master password can be displayed in the terminal by

```
python -m keyring get beem wallet
```

When keyring is set as *password_storage* and the stored password in the keyring is identically to the set master password of the wallet, the wallet is automatically unlocked everytime it is used.

Testing if unlocking works

Testing if the master password is correctly provided by keyring or the *UNLOCK* variable:

```
from beem import Steem
steem = Steem()
print(steem.wallet.locked())
```

When the output is False, automatic unlocking with keyring or the *UNLOCK* variable works. It can also tested by beempy with

```
beempy walletinfo --test-unlock
```

When no password prompt is shown, unlocking with keyring or the *UNLOCK* variable works.

3.6 Api Definitions

3.6.1 condenser_api

broadcast_block

not implemented

broadcast_transaction

```
from beem.transactionbuilder import TransactionBuilder
t = TransactionBuilder()
t.broadcast()
```

broadcast_transaction_synchronous

```
from beem.transactionbuilder import TransactionBuilder
t = TransactionBuilder()
t.broadcast()
```

get_account_bandwidth

```
from beem.account import Account
account = Account("test")
account.get_account_bandwidth()
```

get_account_count

```
from beem.blockchain import Blockchain
b = Blockchain()
b.get_account_count()
```

get_account_history

```
from beem.account import Account
acc = Account("steemit")
for h in acc.get_account_history(1, 0):
    print(h)
```

get_account_reputations

```
from beem.blockchain import Blockchain
b = Blockchain()
for h in b.get_account_reputations():
    print(h)
```

get_account_votes

```
from beem.account import Account
acc = Account("gtg")
for h in acc.get_account_votes():
    print(h)
```

get_active_votes

```
from beem.vote import ActiveVotes
acc = Account("gtg")
post = acc.get_feed(0, 1)[0]
a = ActiveVotes(post["authorperm"])
a.printAsTable()
```

get_active_witnesses

```
from beem.witness import Witnesses
w = Witnesses()
w.printAsTable()
```

get_block

```
from beem.block import Block
print(Block(1))
```

get_block_header

```
from beem.block import BlockHeader
print(BlockHeader(1))
```

get_blog

```
from beem.account import Account
acc = Account("gtg")
for h in acc.get_blog():
    print(h)
```

get_blog_authors

```
from beem.account import Account
acc = Account("gtg")
for h in acc.get_blog_authors():
    print(h)
```

get_blog_entries

```
from beem.account import Account
acc = Account("gtg")
for h in acc.get_blog_entries():
    print(h)
```

get_chain_properties

```
from beem import Steem
stm = Steem()
print(stm.get_chain_properties())
```

get_comment_discussions_by_payout

```
from beem.discussions import Query, Comment_discussions_by_payout
q = Query(limit=10)
for h in Comment_discussions_by_payout(q):
    print(h)
```

get_config

```
from beem import Steem
stm = Steem()
print(stm.get_config())
```

get_content

```
from beem.account import Account
from beem.comment import Comment
acc = Account("gtg")
post = acc.get_feed(0,1)[0]
print(Comment(post["authorperm"]))
```

get_content_replies

```
from beem.account import Account
from beem.comment import Comment
acc = Account("gtg")
post = acc.get_feed(0,1)[0]
c = Comment(post["authorperm"])
for h in c.get_replies():
    print(h)
```

get_conversion_requests

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_conversion_requests())
```

get_current_median_history_price

```
from beem import Steem
stm = Steem()
print(stm.get_current_median_history())
```

get_discussions_by_active

```
from beem.discussions import Query, Discussions_by_active
q = Query(limit=10)
for h in Discussions_by_active(q):
    print(h)
```

get_discussions_by_author_before_date

```
from beem.discussions import Query, Discussions_by_author_before_date
for h in Discussions_by_author_before_date(limit=10, author="gtg"):
    print(h)
```

get_discussions_by_blog

```
from beem.discussions import Query, Discussions_by_blog
q = Query(limit=10)
for h in Discussions_by_blog(q):
    print(h)
```

get_discussions_by_cashout

```
from beem.discussions import Query, Discussions_by_cashout
q = Query(limit=10)
for h in Discussions_by_cashout(q):
    print(h)
```

get_discussions_by_children

```
from beem.discussions import Query, Discussions_by_children
q = Query(limit=10)
for h in Discussions_by_children(q):
    print(h)
```

get_discussions_by_comments

```
from beem.discussions import Query, Discussions_by_comments
q = Query(limit=10, start_author="steemit", start_permalink="firstpost")
for h in Discussions_by_comments(q):
    print(h)
```

get_discussions_by_created

```
from beem.discussions import Query, Discussions_by_created
q = Query(limit=10)
for h in Discussions_by_created(q):
    print(h)
```

get_discussions_by_feed

```
from beem.discussions import Query, Discussions_by_feed
q = Query(limit=10, tag="steem")
for h in Discussions_by_feed(q):
    print(h)
```

get_discussions_by_hot

```
from beem.discussions import Query, Discussions_by_hot
q = Query(limit=10, tag="steem")
for h in Discussions_by_hot(q):
    print(h)
```

get_discussions_by_promoted

```
from beem.discussions import Query, Discussions_by_promoted
q = Query(limit=10, tag="steem")
for h in Discussions_by_promoted(q):
    print(h)
```

get_discussions_by_trending

```
from beem.discussions import Query, Discussions_by_trending
q = Query(limit=10, tag="steem")
for h in Discussions_by_trending(q):
    print(h)
```

get_discussions_by_votes

```
from beem.discussions import Query, Discussions_by_votes
q = Query(limit=10)
for h in Discussions_by_votes(q):
    print(h)
```

get_dynamic_global_properties

```
from beem import Steem
stm = Steem()
print(stm.get_dynamic_global_properties())
```

get_escrow

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_escrow())
```

get_expiring_vesting_delegations

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_expiring_vesting_delegations())
```

get_feed

```
from beem.account import Account
acc = Account("gtg")
for f in acc.get_feed():
    print(f)
```

get_feed_entries

```
from beem.account import Account
acc = Account("gtg")
for f in acc.get_feed_entries():
    print(f)
```

get_feed_history

```
from beem import Steem
stm = Steem()
print(stm.get_feed_history())
```

get_follow_count

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_follow_count())
```

get_followers

```
from beem.account import Account
acc = Account("gtg")
for f in acc.get_followers():
    print(f)
```

get_following

```
from beem.account import Account
acc = Account("gtg")
for f in acc.get_following():
    print(f)
```

get_hardfork_version

```
from beem import Steem
stm = Steem()
print(stm.get_hardfork_properties()["hf_version"])
```

get_key_references

```
from beem.account import Account
from beem.wallet import Wallet
acc = Account("gtg")
w = Wallet()
print(w.getAccountFromPublicKey(acc["posting"]["key_auths"][0][0]))
```

get_market_history

```
from beem.market import Market
m = Market()
for t in m.market_history():
    print(t)
```

get_market_history_buckets

```
from beem.market import Market
m = Market()
for t in m.market_history_buckets():
    print(t)
```

get_next_scheduled_hardfork

```
from beem import Steem
stm = Steem()
print(stm.get_hardfork_properties())
```

get_open_orders

```
from beem.market import Market
m = Market()
print(m.accountopenorders(account="gtg"))
```

get_ops_in_block

```
from beem.block import Block
b = Block(2e6, only_ops=True)
print(b)
```

get_order_book

```
from beem.market import Market
m = Market()
print(m.orderbook())
```

get_owner_history

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_owner_history())
```

get_post_discussions_by_payout

```
from beem.discussions import Query, Post_discussions_by_payout
q = Query(limit=10)
for h in Post_discussions_by_payout(q):
    print(h)
```

get_potential_signatures

```
from beem.transactionbuilder import TransactionBuilder
from beem.blockchain import Blockchain
b = Blockchain()
block = b.get_current_block()
trx = block.json()["transactions"][0]
t = TransactionBuilder(trx)
print(t.get_potential_signatures())
```

get_reblogged_by

```
from beem.account import Account
from beem.comment import Comment
acc = Account("gtg")
post = acc.get_feed(0,1)[0]
c = Comment(post["authorperm"])
for h in c.get_reblogged_by():
    print(h)
```

get_recent_trades

```
from beem.market import Market
m = Market()
for t in m.recent_trades():
    print(t)
```

get_recovery_request

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_recovery_request())
```

get_replies_by_last_update

```
from beem.discussions import Query, Replies_by_last_update
q = Query(limit=10, start_author="steemit", start_permlink="firstpost")
for h in Replies_by_last_update(q):
    print(h)
```

get_required_signatures

```
from beem.transactionbuilder import TransactionBuilder
from beem.blockchain import Blockchain
b = Blockchain()
block = b.get_current_block()
trx = block.json()["transactions"][0]
t = TransactionBuilder(trx)
print(t.get_required_signatures())
```

get_reward_fund

```
from beem import Steem
stm = Steem()
print(stm.get_reward_funds())
```

get_savings_withdraw_from

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_savings_withdrawals(direction="from"))
```

get_savings_withdraw_to

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_savings_withdrawals(direction="to"))
```

get_state

```
from beem.comment import RecentByPath
for p in RecentByPath(path="promoted"):
    print(p)
```

get_tags_used_by_author

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_tags_used_by_author())
```

get_ticker

```
from beem.market import Market
m = Market()
print(m.ticker())
```

get_trade_history

```
from beem.market import Market
m = Market()
for t in m.trade_history():
    print(t)
```

get_transaction

```
from beem.blockchain import Blockchain
b = Blockchain()
print(b.get_transaction("6fde0190a97835ea6d9e651293e90c89911f933c"))
```

get_transaction_hex

```
from beem.blockchain import Blockchain
b = Blockchain()
block = b.get_current_block()
trx = block.json()["transactions"][0]
print(b.get_transaction_hex(trx))
```

get_trending_tags

```
from beem.discussions import Query, Trending_tags
q = Query(limit=10, start_tag="steemit")
for h in Trending_tags(q):
    print(h)
```

get_version

not implemented

get_vesting_delegations

```
from beem.account import Account
acc = Account("gtg")
for v in acc.get_vesting_delegations():
    print(v)
```

get_volume

```
from beem.market import Market
m = Market()
print(m.volume24h())
```

get_withdraw_routes

```
from beem.account import Account
acc = Account("gtg")
print(acc.get_withdraw_routes())
```

get_witness_by_account

```
from beem.witness import Witness
w = Witness("gtg")
print(w)
```

get_witness_count

```
from beem.witness import Witnesses
w = Witnesses()
print(w.witness_count)
```

get_witness_schedule

```
from beem import Steem
stm = Steem()
print(stm.get_witness_schedule())
```

get_witnesses

not implemented

get_witnesses_by_vote

```
from beem.witness import WitnessesRankedByVote
for w in WitnessesRankedByVote():
    print(w)
```

lookup_account_names

```
from beem.account import Account
acc = Account("gtg", full=False)
print(acc.json())
```

lookup_accounts

```
from beem.account import Account
acc = Account("gtg")
for a in acc.get_similar_account_names(limit=100):
    print(a)
```

lookup_witness_accounts

```
from beem.witness import ListWitnesses
for w in ListWitnesses():
    print(w)
```

verify_account_authority

disabled and not implemented

verify_authority

```
from beem.transactionbuilder import TransactionBuilder
from beem.blockchain import Blockchain
b = Blockchain()
block = b.get_current_block()
trx = block.json()["transactions"][0]
t = TransactionBuilder(trx)
t.verify_authority()
print("ok")
```

3.7 Modules

3.7.1 beem Modules

beem.account

class beem.account.Account(*account*, *full=True*, *lazy=False*, *blockchain_instance=None*,
***kwargs*)
Bases: *beem.blockchainobject.BlockchainObject*

This class allows to easily access Account data

Parameters

- **account_name** (*str*) – Name of the account
- **blockchain_instance** (*Steem/Hive*) – Hive or Steem instance
- **lazy** (*bool*) – Use lazy loading
- **full** (*bool*) – Obtain all account data including orders, positions, etc.
- **hive_instance** (*Hive*) – Hive instance
- **steem_instance** (*Steem*) – Steem instance

Returns Account data

Return type dictionary

Raises *beem.exceptions.AccountDoesNotExistException* – if account does not exist

Instances of this class are dictionaries that come with additional methods (see below) that allow dealing with an account and its corresponding functions.

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("gtg", blockchain_instance=stm)
>>> print(account)
<Account gtg>
>>> print(account.balances)
```

Note: This class comes with its own caching function to reduce the load on the API server. Instances of this class can be refreshed with `Account.refresh()`. The cache can be cleared with `Account.clear_cache()`

allow (*foreign*, *weight=None*, *permission='posting'*, *account=None*, *threshold=None*, ***kwargs*)
Give additional access to an account by some other public key or account.

Parameters

- **foreign** (*str*) – The foreign account that will obtain access
- **weight** (*int*) – (optional) The weight to use. If not define, the threshold will be used. If the weight is smaller than the threshold, additional signatures will be required. (defaults to threshold)
- **permission** (*str*) – (optional) The actual permission to modify (defaults to posting)
- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)
- **threshold** (*int*) – (optional) The threshold that needs to be reached by signatures to be able to interact

approvewitness (*witness*, *account=None*, *approve=True*, ***kwargs*)
Approve a witness

Parameters

- **witness** (*list*) – list of Witness name or id
- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)

available_balances

List balances of an account. This call returns instances of `beem.amount.Amount`.

balances

Returns all account balances as dictionary

blog_history (*limit=None*, *start=-1*, *reblogs=True*, *account=None*)
Stream the blog entries done by an account in reverse time order.

Note: RPC nodes keep a limited history of entries for the user blog. Older blog posts of an account may not be available via this call due to these node limitations.

Parameters

- **limit** (*int*) – (optional) stream the latest *limit* blog entries. If unset (default), all available blog entries are streamed.
- **start** (*int*) – (optional) start streaming the blog entries from this index. *start=-1* (default) starts with the latest available entry.
- **reblogs** (*bool*) – (optional) if set *True* (default) reblogs / resteems are included. If set *False*, reblogs/resteems are omitted.
- **account** (*str*) – (optional) the account to stream blog entries for (defaults to `default_account`)

`blog_history_reverse` example:

```
from beem.account import Account
from beem import Steem
from beem.nodelist import NodeList
nodelist = NodeList()
nodelist.update_nodes()
stm = Steem(node=nodelist.get_hive_nodes())
acc = Account("steemitblog", blockchain_instance=stm)
for post in acc.blog_history(limit=10):
    print(post)
```

cancel_transfer_from_savings (*request_id*, *account=None*, ***kwargs*)
Cancel a withdrawal from ‘savings’ account.

Parameters

- **request_id** (*str*) – Identifier for tracking or cancelling the withdrawal
- **account** (*str*) – (optional) the source account for the transfer if not `default_account`

change_recovery_account (*new_recovery_account*, *account=None*, ***kwargs*)
Request a change of the recovery account.

Note: It takes 30 days until the change applies. Another request within this time restarts the 30 day period. Setting the current recovery account again cancels any pending change request.

Parameters

- **new_recovery_account** (*str*) – account name of the new recovery account
- **account** (*str*) – (optional) the account to change the recovery account for (defaults to `default_account`)

claim_reward_balance (*reward_steam=0*, *reward_sbd=0*, *reward_vests=0*, *account=None*, ***kwargs*)

Claim reward balances. By default, this will claim all outstanding balances. To bypass this behaviour, set desired claim amount by setting any of *reward_steam*, *reward_sbd* or *reward_vests*.

Parameters

- **reward_steam** (*str*) – Amount of STEEM you would like to claim.
- **reward_sbd** (*str*) – Amount of SBD you would like to claim.
- **reward_vests** (*str*) – Amount of VESTS you would like to claim.
- **account** (*str*) – The source account for the claim if not `default_account` is used.

comment_history (*limit=None*, *start_permalink=None*, *account=None*)

Stream the comments done by an account in reverse time order.

Note: RPC nodes keep a limited history of user comments for the user feed. Older comments may not be available via this call due to these node limitations.

Parameters

- **limit** (*int*) – (optional) stream the latest *limit* comments. If unset (default), all available comments are streamed.
- **start_permalink** (*str*) – (optional) start streaming the comments from this permalink. *start_permalink=None* (default) starts with the latest available entry.
- **account** (*str*) – (optional) the account to stream comments for (defaults to `default_account`)

comment_history_reverse example:

```
from beem.account import Account
from beem import Steem
from beem.nodelist import NodeList
nodelist = NodeList()
nodelist.update_nodes()
stm = Steem(node=nodelist.get_hive_nodes())
acc = Account("ned", blockchain_instance=stm)
for comment in acc.comment_history(limit=10):
    print(comment)
```

convert (*amount*, *account=None*, *request_id=None*)

Convert SteemDollars to Steem (takes 3.5 days to settle)

Parameters

- **amount** (*float*) – amount of SBD to convert
- **account** (*str*) – (optional) the source account for the transfer if not `default_account`
- **request_id** (*str*) – (optional) identifier for tracking the conversion

curation_stats()

Returns the curation reward of the last 24h and 7d and the average of the last 7 days

Returns Account curation

Return type dictionary

Sample output:

```
{  
    '24hr': 0.0,  
    '7d': 0.0,  
    'avg': 0.0  
}
```

delegate_vesting_shares (*to_account*, *vesting_shares*, *account=None*, ***kwargs*)

Delegate SP to another account.

Parameters

- **to_account** (*str*) – Account we are delegating shares to (delegatee).
- **vesting_shares** (*str*) – Amount of VESTS to delegate eg. *10000 VESTS*.
- **account** (*str*) – The source account (delegator). If not specified, `default_account` is used.

disallow (*foreign, permission='posting', account=None, threshold=None, **kwargs*)

Remove additional access to an account by some other public key or account.

Parameters

- **foreign** (*str*) – The foreign account that will obtain access
- **permission** (*str*) – (optional) The actual permission to modify (defaults to `posting`)
- **account** (*str*) – (optional) the account to allow access to (defaults to `default_account`)
- **threshold** (*int*) – The threshold that needs to be reached by signatures to be able to interact

disapprovewitness (*witness, account=None, **kwargs*)

Disapprove a witness

Parameters

- **witness** (*list*) – list of Witness name or id
- **account** (*str*) – (optional) the account to allow access to (defaults to `default_account`)

ensure_full()

Ensure that all data are loaded

estimate_virtual_op_num (*blocktime, stop_diff=0, max_count=100*)

Returns an estimation of an virtual operation index for a given time or blockindex

Parameters

- **blocktime** (*int, datetime*) – start time or start block index from which account operation should be fetched
- **stop_diff** (*int*) – Sets the difference between last estimation and new estimation at which the estimation stops. Must not be zero. (default is 1)
- **max_count** (*int*) – sets the maximum number of iterations. -1 disables this (default 100)

```
utc = pytz.timezone('UTC')
start_time = utc.localize(datetime.utcnow()) - timedelta(days=7)
acc = Account("gtg")
start_op = acc.estimate_virtual_op_num(start_time)

b = Blockchain()
start_block_num = b.get_estimated_block_num(start_time)
start_op2 = acc.estimate_virtual_op_num(start_block_num)
```

```
acc = Account("gtg")
block_num = 21248120
start = t.time()
op_num = acc.estimate_virtual_op_num(block_num, stop_diff=1, max_count=10)
stop = t.time()
```

(continues on next page)

(continued from previous page)

```
print(stop - start)
for h in acc.get_account_history(op_num, 0):
    block_est = h["block"]
print(block_est - block_num)
```

feed_history (*limit=None*, *start_author=None*, *start_permlink=None*, *account=None*)

Stream the feed entries of an account in reverse time order.

Note: RPC nodes keep a limited history of entries for the user feed. Older entries may not be available via this call due to these node limitations.

Parameters

- **limit** (*int*) – (optional) stream the latest *limit* feed entries. If unset (default), all available entries are streamed.
- **start_author** (*str*) – (optional) start streaming the replies from this author. *start_permlink=None* (default) starts with the latest available entry. If set, *start_permlink* has to be set as well.
- **start_permlink** (*str*) – (optional) start streaming the replies from this permlink. *start_permlink=None* (default) starts with the latest available entry. If set, *start_author* has to be set as well.
- **account** (*str*) – (optional) the account to get replies to (defaults to *default_account*)

comment_history_reverse example:

```
from beem.account import Account
from beem import Steem
from beem.nodelist import NodeList
nodelist = NodeList()
nodelist.update_nodes()
stm = Steem(node=nodelist.get_hive_nodes())
acc = Account("ned", blockchain_instance=stm)
for reply in acc.feed_history(limit=10):
    print(reply)
```

follow (*other*, *what=['blog']*, *account=None*)

Follow/Unfollow/Mute/Unmute another account's blog

Parameters

- **other** (*str*) – Follow this account
- **what** (*list*) – List of states to follow. *['blog']* means to follow *other*, *[]* means to unfollow/unmute *other*, *['ignore']* means to ignore *other*, (defaults to *['blog']*)
- **account** (*str*) – (optional) the account to allow access to (defaults to *default_account*)

getSimilarAccountNames (*limit=5*)Deprecated, please use `get_similar_account_names`**get_account_bandwidth** (*bandwidth_type=1*, *account=None*)

get_account_history(*index*, *limit*, *order=-1*, *start=None*, *stop=None*, *use_block_num=True*,
only_ops=[], *exclude_ops=[]*, *raw_output=False*)

Returns a generator for individual account transactions. This call can be used in a `for` loop.

Parameters

- **index** (*int*) – first number of transactions to return
- **limit** (*int*) – limit number of transactions to return
- **start** (*int, datetime*) – start number/date of transactions to return (*optional*)
- **stop** (*int, datetime*) – stop number/date of transactions to return (*optional*)
- **use_block_num** (*bool*) – if true, start and stop are block numbers, otherwise virtual OP count numbers.
- **only_ops** (*array*) – Limit generator by these operations (*optional*)
- **exclude_ops** (*array*) – Exclude these operations from generator (*optional*)
- **batch_size** (*int*) – internal api call batch size (*optional*)
- **order** (*int*) – 1 for chronological, -1 for reverse order
- **raw_output** (*bool*) – if False, the output is a dict, which includes all values. Otherwise, the output is list.

Note: `only_ops` and `exclude_ops` takes an array of strings: The full list of operation ID's can be found in `beembase.operationids.ops`. Example: `['transfer', 'vote']`

get_account_posts(*sort='feed'*, *account=None*, *observer=None*, *raw_data=False*)

Returns account feed

get_account_votes(*account=None*, *start_author=""*, *start_permalink=""*)

Returns all votes that the account has done

Return type

list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_account_votes()
```

get_balance(*balances*, *symbol*)

Obtain the balance of a specific Asset. This call returns instances of `beem.amount.Amount`. Available balance types:

- “available”
- “saving”
- “reward”
- “total”

Parameters

- **balances** (*str*) – Defines the balance type

- **symbol** (*str, dict*) – Can be “SBD”, “STEEM” or “VESTS

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_balance("rewards", "HBD")
0.000 HBD
```

get_balances()

Returns all account balances as dictionary

Returns Account balances

Return type dictionary

Sample output:

```
{
    'available': [102.985 STEEM, 0.008 SBD, 146273.695970 VESTS],
    'savings': [0.000 STEEM, 0.000 SBD],
    'rewards': [0.000 STEEM, 0.000 SBD, 0.000000 VESTS],
    'total': [102.985 STEEM, 0.008 SBD, 146273.695970 VESTS]
}
```

get_bandwidth()

Returns used and allocated bandwidth

Return type dictionary

Sample output:

```
{
    'used': 0,
    'allocated': 2211037
}
```

get_blog(*start_entry_id=0, limit=100, raw_data=False, short_entries=False, account=None*)

Returns the list of blog entries for an account

Parameters

- **start_entry_id** (*int*) – default is 0
- **limit** (*int*) – default is 100
- **raw_data** (*bool*) – default is False
- **short_entries** (*bool*) – when set to True and raw_data is True, get_blog_entries is used instead of get_blog
- **account** (*str*) – When set, a different account name is used (Default is object account name)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
```

(continues on next page)

(continued from previous page)

```
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("steemit", blockchain_instance=stm)
>>> account.get_blog(0, 1)
[<Comment @steemit/firstpost>]
```

get_blog_authors (*account=None*)

Returns a list of authors that have had their content reblogged on a given blog account

Parameters **account** (*str*) – When set, a different account name is used (Default is object account name)**Return type** list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("gtg", blockchain_instance=stm)
>>> account.get_blog_authors()
```

get_blog_entries (*start_entry_id=0, limit=100, raw_data=True, account=None*)

Returns the list of blog entries for an account

Parameters

- **start_entry_id** (*int*) – default is 0
- **limit** (*int*) – default is 100
- **raw_data** (*bool*) – default is False
- **account** (*str*) – When set, a different account name is used (Default is object account name)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("steemit", blockchain_instance=stm)
>>> entry = account.get_blog_entries(0, 1, raw_data=True)[0]
>>> print("%s - %s - %s" % (entry["author"], entry["permlink"], entry["blog"]))
steemit - firstpost - steemit
```

get_conversion_requests (*account=None*)

Returns a list of SBD conversion request

Parameters **account** (*str*) – When set, a different account is used for the request (Default is object account name)**Return type** list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_conversion_requests()
[]
```

get_creator()

Returns the account creator or *None* if the account was mined

get_curation_reward(*days*=7)

Returns the curation reward of the last *days* days

Parameters **days** (*int*) – limit number of days to be included int the return value

get_downvote_manabar()

Return downvote manabar

get_downvoting_power(*with_regeneration=True*)

Returns the account downvoting power in the range of 0-100%

get_effective_vesting_shares()

Returns the effective vesting shares

get_escrow(*escrow_id*=0, *account*=*None*)

Returns the escrow for a certain account by id

Parameters

- **escrow_id** (*int*) – Id (only pre appbase)
- **account** (*str*) – When set, a different account is used for the request (Default is object account name)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_escrow(1234)
[]
```

get_expiring_vesting_delegations(*after*=*None*, *limit*=1000, *account*=*None*)

Returns the expirations for vesting delegations.

Parameters

- **after** (*datetime*) – expiration after (only for pre appbase nodes)
- **limit** (*int*) – limits number of shown entries (only for pre appbase nodes)
- **account** (*str*) – When set, a different account is used for the request (Default is object account name)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_expiring_vesting_delegations()
[]
```

get_feed(*start_entry_id*=0, *limit*=100, *raw_data*=False, *short_entries*=False, *account*=None)
Returns a list of items in an account's feed

Parameters

- **start_entry_id** (*int*) – default is 0
- **limit** (*int*) – default is 100
- **raw_data** (*bool*) – default is False
- **short_entries** (*bool*) – when set to True and raw_data is True, get_feed_entries is used instead of get_feed
- **account** (*str*) – When set, a different account name is used (Default is object account name)

Return type

list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("steemit", blockchain_instance=stm)
>>> account.get_feed(0, 1, raw_data=True)
[]
```

get_feed_entries(*start_entry_id*=0, *limit*=100, *raw_data*=True, *account*=None)
Returns a list of entries in an account's feed

Parameters

- **start_entry_id** (*int*) – default is 0
- **limit** (*int*) – default is 100
- **raw_data** (*bool*) – default is False
- **short_entries** (*bool*) – when set to True and raw_data is True, get_feed_entries is used instead of get_feed
- **account** (*str*) – When set, a different account name is used (Default is object account name)

Return type

list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
```

(continues on next page)

(continued from previous page)

```
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("steemit", blockchain_instance=stm)
>>> account.get_feed_entries(0, 1)
[]
```

get_follow_count (*account=None*)

get_followers (*raw_name_list=True, limit=100*)
Returns the account followers as list

get_following (*raw_name_list=True, limit=100*)
Returns who the account is following as list

get_manabar ()
Return manabar

get_manabar_recharge_time (*manabar, recharge_pct_goal=100*)
Returns the account mana recharge time in minutes

Parameters

- **manabar** (*dict*) – manabar dict from get_manabar() or get_rc_manabar()
- **recharge_pct_goal** (*float*) – mana recovery goal in percentage (default is 100)

get_manabar_recharge_time_str (*manabar, recharge_pct_goal=100*)
Returns the account manabar recharge time as string

Parameters

- **manabar** (*dict*) – manabar dict from get_manabar() or get_rc_manabar()
- **recharge_pct_goal** (*float*) – mana recovery goal in percentage (default is 100)

get_manabar_recharge_timedelta (*manabar, recharge_pct_goal=100*)
Returns the account mana recharge time as timedelta object

Parameters

- **manabar** (*dict*) – manabar dict from get_manabar() or get_rc_manabar()
- **recharge_pct_goal** (*float*) – mana recovery goal in percentage (default is 100)

get_muters (*raw_name_list=True, limit=100*)
Returns the account muters as list

get_mutings (*raw_name_list=True, limit=100*)
Returns who the account is muting as list

get_notifications (*only_unread=True, limit=100, raw_data=False, account=None*)
Returns account notifications

Parameters

- **only_unread** (*bool*) – When True, only unread notifications are shown
- **limit** (*int*) – When set, the number of shown notifications is limited (max limit = 100)
- **raw_data** (*bool*) – When True, the raw data from the api call is returned.
- **account** (*str*) – (optional) the account for which the notification should be received to (defaults to default_account)

get_owner_history(*account=None*)

Returns the owner history of an account.

Parameters **account** (*str*) – When set, a different account is used for the request (Default is object account name)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_owner_history()
[]
```

get_rc()

Return RC of account

get_rc_manabar()

Returns current_mana and max_mana for RC

get_recharge_time(*voting_power_goal=100, starting_voting_power=None*)

Returns the account voting power recharge time in minutes

Parameters

- **voting_power_goal** (*float*) – voting power goal in percentage (default is 100)
- **starting_voting_power** (*float*) – returns recharge time if current voting power is the provided value.

get_recharge_time_str(*voting_power_goal=100, starting_voting_power=None*)

Returns the account recharge time as string

Parameters

- **voting_power_goal** (*float*) – voting power goal in percentage (default is 100)
- **starting_voting_power** (*float*) – returns recharge time if current voting power is the provided value.

get_recharge_timedelta(*voting_power_goal=100, starting_voting_power=None*)

Returns the account voting power recharge time as timedelta object

Parameters

- **voting_power_goal** (*float*) – voting power goal in percentage (default is 100)
- **starting_voting_power** (*float*) – returns recharge time if current voting power is the provided value.

get_recovery_request(*account=None*)

Returns the recovery request for an account

Parameters **account** (*str*) – When set, a different account is used for the request (Default is object account name)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_recovery_request()
[]
```

get_reputation()

Returns the account reputation in the (steemit) normalized form

get_savings_withdrawals(*direction='from'*, *account=None*)

Returns the list of savings withdrawls for an account.

Parameters

- **account (str)** – When set, a different account is used for the request (Default is object account name)
- **direction (str)** – Can be either from or to (only non appbase nodes)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_savings_withdrawals()
[]
```

get_similar_account_names(*limit=5*)

Returns limit account names similar to the current account name as a list

Parameters **limit (int)** – limits the number of accounts, which will be returned**Returns** Similar account names as list**Return type** list

This is a wrapper around `beem.blockchain.Blockchain.get_similar_account_names()` using the current account name as reference.

get_steam_power(*onlyOwnSP=False*)

Returns the account steem power

get_tags_used_by_author(*account=None*)

Returns a list of tags used by an author.

Parameters **account (str)** – When set, a different account is used for the request (Default is object account name)**Return type** list**get_token_power(*only_own_vests=False*)**

Returns the account Hive/Steem power (amount of staked token + delegations)

get_vesting_delegations(*start_account=*", *limit=100*, *account=None*)

Returns the vesting delegations by an account.

Parameters

- **account** (*str*) – When set, a different account is used for the request (Default is object account name)
- **start_account** (*str*) – delegatee to start with, leave empty to start from the first by name
- **limit** (*int*) – maximum number of results to return

Return type

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_vesting_delegations()
[]
```

`get_vests` (*only_own_vests=False*)

Returns the account vests

`get_vote` (*comment*)

Returns a vote if the account has already voted for comment.

Parameters `comment` (*str, Comment*) – can be a Comment object or a authorpermlink

`get_vote_pct_for_SBD` (*sbd, post_rshares=0, voting_power=None, steem_power=None, not_broadcasted_vote=True*)

Returns the voting percentage needed to have a vote worth a given number of SBD.

If the returned number is bigger than 10000 or smaller than -10000, the given SBD value is too high for that account

Parameters `sbd` (*str, int, amount.Amount*) – The amount of SBD in vote value

`get_vote_pct_for_vote_value` (*token_units, post_rshares=0, voting_power=None, token_power=None, not_broadcasted_vote=True*)

Returns the voting percentage needed to have a vote worth a given number of Hive/Steem token units

If the returned number is bigger than 10000 or smaller than -10000, the given SBD value is too high for that account

Parameters `token_units` (*str, int, amount.Amount*) – The amount of HBD/SBD in vote value

`get_voting_power` (*with_regeneration=True*)

Returns the account voting power in the range of 0-100%

`get_voting_value` (*post_rshares=0, voting_weight=100, voting_power=None, token_power=None, not_broadcasted_vote=True*)

Returns the account voting value in Hive/Steem token units

`get_voting_value_SBD` (*post_rshares=0, voting_weight=100, voting_power=None, steem_power=None, not_broadcasted_vote=True*)

Returns the account voting value in SBD

`get_withdraw_routes` (*account=None*)

Returns the withdraw routes for an account.

Parameters `account` (`str`) – When set, a different account is used for the request (Default is object account name)

Return type list

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("beem.app", blockchain_instance=stm)
>>> account.get_withdraw_routes()
[]
```

has_voted (`comment`)

Returns if the account has already voted for comment

Parameters `comment` (`str, Comment`) – can be a Comment object or a authorpermlink

history (`start=None`, `stop=None`, `use_block_num=True`, `only_ops=[]`, `exclude_ops=[]`, `batch_size=1000`, `raw_output=False`)

Returns a generator for individual account transactions. The earliest operation will be first. This call can be used in a `for` loop.

Parameters

- `start` (`int, datetime`) – start number/date of transactions to return (*optional*)
- `stop` (`int, datetime`) – stop number/date of transactions to return (*optional*)
- `use_block_num` (`bool`) – if true, start and stop are block numbers, otherwise virtual OP count numbers.
- `only_ops` (`array`) – Limit generator by these operations (*optional*)
- `exclude_ops` (`array`) – Exclude these operations from generator (*optional*)
- `batch_size` (`int`) – internal api call batch size (*optional*)
- `raw_output` (`bool`) – if False, the output is a dict, which includes all values. Otherwise, the output is list.

Note: `only_ops` and `exclude_ops` takes an array of strings: The full list of operation ID's can be found in `beembase.operationids.ops`. Example: `['transfer', 'vote']`

```
acc = Account("gtg")
max_op_count = acc.virtual_op_count()
# Returns the 100 latest operations
acc_op = []
for h in acc.history(start=max_op_count - 99, stop=max_op_count, use_block_
    ↪num=False):
    acc_op.append(h)
len(acc_op)
```

```
100
```

```
acc = Account("test")
max_block = 21990141
```

(continues on next page)

(continued from previous page)

```
# Returns the account operation inside the last 100 block. This can be empty.
acc_op = []
for h in acc.history(start=max_block - 99, stop=max_block, use_block_
    ↪num=True):
    acc_op.append(h)
len(acc_op)
```

0

```
acc = Account("test")
start_time = datetime(2018, 3, 1, 0, 0, 0)
stop_time = datetime(2018, 3, 2, 0, 0, 0)
# Returns the account operation from 1.4.2018 back to 1.3.2018
acc_op = []
for h in acc.history(start=start_time, stop=stop_time):
    acc_op.append(h)
len(acc_op)
```

0

history_reverse (*start=None*, *stop=None*, *use_block_num=True*, *only_ops=[]*, *exclude_ops=[]*, *batch_size=1000*, *raw_output=False*)

Returns a generator for individual account transactions. The latest operation will be first. This call can be used in a `for` loop.

Parameters

- **start** (*int, datetime*) – start number/date of transactions to return. If negative the virtual_op_count is added. (*optional*)
- **stop** (*int, datetime*) – stop number/date of transactions to return. If negative the virtual_op_count is added. (*optional*)
- **use_block_num** (*bool*) – if true, start and stop are block numbers, otherwise virtual OP count numbers.
- **only_ops** (*array*) – Limit generator by these operations (*optional*)
- **exclude_ops** (*array*) – Exclude these operations from generator (*optional*)
- **batch_size** (*int*) – internal api call batch size (*optional*)
- **raw_output** (*bool*) – if False, the output is a dict, which includes all values. Otherwise, the output is list.

Note: only_ops and exclude_ops takes an array of strings: The full list of operation ID's can be found in `beembase.operationids.ops`. Example: ['transfer', 'vote']

```
acc = Account("gtg")
max_op_count = acc.virtual_op_count()
# Returns the 100 latest operations
acc_op = []
for h in acc.history_reverse(start=max_op_count, stop=max_op_count - 99, use_
    ↪block_num=False):
    acc_op.append(h)
len(acc_op)
```

```
100
```

```
max_block = 21990141
acc = Account("test")
# Returns the account operation inside the last 100 block. This can be empty.
acc_op = []
for h in acc.history_reverse(start=max_block, stop=max_block-100, use_block_
    ↴num=True):
    acc_op.append(h)
len(acc_op)
```

```
0
```

```
acc = Account("test")
start_time = datetime(2018, 4, 1, 0, 0, 0)
stop_time = datetime(2018, 3, 1, 0, 0, 0)
# Returns the account operation from 1.4.2018 back to 1.3.2018
acc_op = []
for h in acc.history_reverse(start=start_time, stop=stop_time):
    acc_op.append(h)
len(acc_op)
```

```
0
```

interest()

Calculate interest for an account

Parameters **account** (*str*) – Account name to get interest for

Return type dictionary

Sample output:

```
{  
    'interest': 0.0,  
    'last_payment': datetime.datetime(2018, 1, 26, 5, 50, 27, tzinfo=<UTC>),  
    'next_payment': datetime.datetime(2018, 2, 25, 5, 50, 27, tzinfo=<UTC>),  
    'next_payment_duration': datetime.timedelta(-65, 52132, 684026),  
    'interest_rate': 0.0  
}
```

is_fully_loaded

Is this instance fully loaded / e.g. all data available?

Return type bool

json()

json_metadata

list_all_subscriptions (*account=None*)

Returns all subscriptions

mark_notifications_as_read (*last_read=None, account=None*)

Broadcast a mark all notification as read custom_json

Parameters

- **last_read** (*str*) – When set, this datestring is used to set the mark as read date

- **account** (*str*) – (optional) the account to broadcast the custom_json to (defaults to default_account)

mute (*mute*, *account=None*)

Mute another account

Parameters

- **mute** (*str*) – Mute this account
- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)

name

Returns the account name

posting_json_metadata

print_info (*force_refresh=False*, *return_str=False*, *use_table=False*, ***kwargs*)

Prints import information about the account

profile

Returns the account profile

refresh()

Refresh/Obtain an account's data from the API server

rep

Returns the account reputation

reply_history (*limit=None*, *start_author=None*, *start_permalink=None*, *account=None*)

Stream the replies to an account in reverse time order.

Note: RPC nodes keep a limited history of entries for the replies to an author. Older replies to an account may not be available via this call due to these node limitations.

Parameters

- **limit** (*int*) – (optional) stream the latest *limit* replies. If unset (default), all available replies are streamed.
- **start_author** (*str*) – (optional) start streaming the replies from this author. *start_permalink=None* (default) starts with the latest available entry. If set, *start_permalink* has to be set as well.
- **start_permalink** (*str*) – (optional) start streaming the replies from this permalink. *start_permalink=None* (default) starts with the latest available entry. If set, *start_author* has to be set as well.
- **account** (*str*) – (optional) the account to get replies to (defaults to default_account)

comment_history_reverse example:

```
from beem.account import Account
acc = Account("ned")
for reply in acc.reply_history(limit=10):
    print(reply)
```

reward_balances

saving_balances**set_withdraw_vesting_route**(*to*, *percentage*=100, *account*=None, *auto_vest*=False, ***kwargs*)

Set up a vesting withdraw route. When vesting shares are withdrawn, they will be routed to these accounts based on the specified weights.

Parameters

- **to** (*str*) – Recipient of the vesting withdrawal
- **percentage** (*float*) – The percent of the withdraw to go to the ‘to’ account.
- **account** (*str*) – (optional) the vesting account
- **auto_vest** (*bool*) – Set to true if the ‘to’ account should receive the VESTS as VESTS, or false if it should receive them as STEEM. (defaults to False)

setproxy(*proxy*=”, *account*=None)

Set the witness and proposal system proxy of an account

Parameters

- **proxy** (*str or Account*) – The account to set the proxy to (Leave empty for removing the proxy)
- **account** (*str or Account*) – The account the proxy should be set for

sp

Returns the accounts Steem Power

total_balances**tp**

Returns the accounts Hive/Steem Power

transfer(*to*, *amount*, *asset*, *memo*=”, *account*=None, ***kwargs*)

Transfer an asset to another account.

Parameters

- **to** (*str*) – Recipient
- **amount** (*float*) – Amount to transfer
- **asset** (*str*) – Asset to transfer
- **memo** (*str*) – (optional) Memo, may begin with # for encrypted messaging
- **account** (*str*) – (optional) the source account for the transfer if not default_account

Transfer example:

```
from beem.account import Account
from beem import Steem
active_wif = "5xxxx"
stm = Steem(keys=[active_wif])
acc = Account("test", blockchain_instance=stm)
acc.transfer("test1", 1, "STEEM", "test")
```

transfer_from_savings(*amount*, *asset*, *memo*, *request_id*=None, *to*=None, *account*=None, ***kwargs*)

Withdraw SBD or STEEM from ‘savings’ account.

Parameters

- **amount** (*float*) – STEEM or SBD amount
- **asset** (*float*) – ‘STEEM’ or ‘SBD’
- **memo** (*str*) – (optional) Memo
- **request_id** (*str*) – (optional) identifier for tracking or cancelling the withdrawal
- **to** (*str*) – (optional) the source account for the transfer if not `default_account`
- **account** (*str*) – (optional) the source account for the transfer if not `default_account`

transfer_to_savings (*amount, asset, memo, to=None, account=None, **kwargs*)

Transfer SBD or STEEM into a ‘savings’ account.

Parameters

- **amount** (*float*) – STEEM or SBD amount
- **asset** (*float*) – ‘STEEM’ or ‘SBD’
- **memo** (*str*) – (optional) Memo
- **to** (*str*) – (optional) the source account for the transfer if not `default_account`
- **account** (*str*) – (optional) the source account for the transfer if not `default_account`

transfer_to_vesting (*amount, to=None, account=None, **kwargs*)

Vest STEEM

Parameters

- **amount** (*float*) – Amount to transfer
- **to** (*str*) – Recipient (optional) if not set equal to account
- **account** (*str*) – (optional) the source account for the transfer if not `default_account`

type_id = 2

unfollow (*unfollow, account=None*)

Unfollow/Unmute another account’s blog

Parameters

- **unfollow** (*str*) – Unfollow/Unmute this account
- **account** (*str*) – (optional) the account to allow access to (defaults to `default_account`)

update_account_jsonmetadata (*metadata, account=None, **kwargs*)

Update an account’s profile in `json_metadata` using the posting key

Parameters

- **metadata** (*dict*) – The new metadata to use
- **account** (*str*) – (optional) the account to allow access to (defaults to `default_account`)

update_account_keys (*new_password, account=None, **kwargs*)

Updates all account keys

This method does **not** add any private keys to your wallet but merely changes the public keys.

Parameters

- **new_password** (*str*) – is used to derive the owner, active, posting and memo key
- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)

update_account_metadata (*metadata, account=None, **kwargs*)

Update an account's profile in json_metadata

Parameters

- **metadata** (*dict*) – The new metadata to use
- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)

update_account_profile (*profile, account=None, **kwargs*)

Update an account's profile in json_metadata

Parameters

- **profile** (*dict*) – The new profile to use
- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)

Sample profile structure:

```
{  
    'name': 'Holger',  
    'about': 'beem Developer',  
    'location': 'Germany',  
    'profile_image': 'https://c1.staticflickr.com/5/4715/38733717165_  
    ↪7070227c89_n.jpg',  
    'cover_image': 'https://farm1.staticflickr.com/894/26382750057_69f5c8e568.  
    ↪jpg',  
    'website': 'https://github.com/holgern/beem'  
}
```

```
from beem.account import Account  
account = Account("test")  
profile = account.profile  
profile["about"] = "test account"  
account.update_account_profile(profile)
```

update_memo_key (*key, account=None, **kwargs*)

Update an account's memo public key

This method does **not** add any private keys to your wallet but merely changes the memo public key.

Parameters

- **key** (*str*) – New memo public key
- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)

verify_account_authority (*keys, account=None*)

Returns true if the signers have enough authority to authorize an account.

Parameters

- **keys** (*list*) – public key

- **account** (*str*) – When set, a different account is used for the request (Default is object account name)

Return type dictionary

```
>>> from beem.account import Account
>>> from beem import Hive
>>> from beem.nodelist import NodeList
>>> nodelist = NodeList()
>>> nodelist.update_nodes()
>>> stm = Hive(node=nodelist.get_hive_nodes())
>>> account = Account("steemit", blockchain_instance=stm)
>>> print(account.verify_account_authority([
    "STM7Q2rLBqzPzFeteQZewv9Lu3NLE69fZoLeL6YK59t7UmssCBNTU"])) ["valid"])
False
```

virtual_op_count (*until=None*)

Returns the number of individual account transactions

Return type list

vp

Returns the account voting power in the range of 0-100%

withdraw_vesting (*amount, account=None, **kwargs*)

Withdraw VESTS from the vesting account.

Parameters

- **amount** (*float*) – number of VESTS to withdraw over a period of 13 weeks
- **account** (*str*) – (optional) the source account for the transfer if not default_account

```
class beem.account.Accounts(name_list,      batch_limit=100,      lazy=False,      full=True,
                             blockchain_instance=None, **kwargs)
```

Bases: *beem.account.AccountsObject*

Obtain a list of accounts

Parameters

- **name_list** (*list*) – list of accounts to fetch
- **batch_limit** (*int*) – (optional) maximum number of accounts to fetch per call, defaults to 100
- **blockchain_instance** (*Steem/Hive*) – Steem() or Hive() instance to use when accessing a RPCcreator = Account(creator, blockchain_instance=self)

```
class beem.account.AccountsObject
```

Bases: list

printAsTable()

print_summarize_table (*tag_type='Follower', return_str=False, **kwargs*)

beem.aes

```
class beem.aes.AESCipher(key)
```

Bases: object

A classical AES Cipher. Can use any size of data and any size of password thanks to padding. Also ensure the coherence and the type of the data with a unicode to byte converter.

```
decrypt (enc)
encrypt (raw)
static str_to_bytes (data)
```

beem.amount

```
class beem.amount.Amount (amount,           asset=None,           fixed_point_arithmetic=False,
                           new_appbase_format=True, blockchain_instance=None, **kwargs)
Bases: dict
```

This class deals with Amounts of any asset to simplify dealing with the tuple:

```
(amount, asset)
```

Parameters

- **args** (*list*) – Allows to deal with different representations of an amount
- **amount** (*float*) – Let's create an instance with a specific amount
- **asset** (*str*) – Let's you create an instance with a specific asset (symbol)
- **fixed_point_arithmetic** (*boolean*) – when set to True, all operation are fixed point operations and the amount is always be rounded down to the precision
- **steem_instance** (*Steem*) – Steem instance

Returns All data required to represent an Amount/Asset

Return type dict

Raises **ValueError** – if the data provided is not recognized

Way to obtain a proper instance:

- args can be a string, e.g.: “1 SBD”
- args can be a dictionary containing amount and asset_id
- args can be a dictionary containing amount and asset
- args can be a list of a float and str (symbol)
- args can be a list of a float and a *beem.asset.Asset*
- amount and asset are defined manually

An instance is a dictionary and comes with the following keys:

- amount (float)
- symbol (str)
- asset (instance of *beem.asset.Asset*)

Instances of this class can be used in regular mathematical expressions (+-*/%) such as:

```
from beem.amount import Amount
from beem.asset import Asset
a = Amount("1 STEEM")
b = Amount(1, "STEEM")
c = Amount("20", Asset("STEEM"))
a + b
a * 2
a += b
a /= 2.0
```

```
2.000 STEEM
2.000 STEEM
```

amount

Returns the amount as float

amount_decimal

Returns the amount as decimal

asset

Returns the asset as instance of steem.asset.Asset

copy()

Copy the instance and make sure not to use a reference

json()**symbol**

Returns the symbol of the asset

tuple()

beem.amount.**check_asset**(other, self, stm)

beem.amount.**quantize**(amount, precision)

beem.asciichart

class beem.asciichart.**AsciiChart**(height=None, width=None, offset=3, placeholder='{:8.2f}', charset='utf8')

Bases: object

Can be used to plot price and trade history

Parameters

- **height** (*int*) – Height of the plot
- **width** (*int*) – Width of the plot
- **offset** (*int*) – Offset between tick strings and y-axis (default is 3)
- **placeholder** (*str*) – Defines how the numbers on the y-axes are formatted (default is '{:8.2f}')
- **charset** (*str*) – sets the charset for plotting, utf8 or ascii (default: utf8)

adapt_on_series(series)

Calculates the minimum, maximum and length from the given list

Parameters **series** (*list*) – time series to plot

```
from beem.asciichart import AsciiChart
chart = AsciiChart()
series = [1, 2, 3, 7, 2, -4, -2]
chart.adapt_on_series(series)
chart.new_chart()
chart.add_axis()
chart.add_curve(series)
print(str(chart))
```

add_axis()

Adds a y-axis to the canvas

```
from beem.asciichart import AsciiChart
chart = AsciiChart()
series = [1, 2, 3, 7, 2, -4, -2]
chart.adapt_on_series(series)
chart.new_chart()
chart.add_axis()
chart.add_curve(series)
print(str(chart))
```

add_curve(series)

Add a curve to the canvas

Parameters `series` (`list`) – List width float data points

```
from beem.asciichart import AsciiChart
chart = AsciiChart()
series = [1, 2, 3, 7, 2, -4, -2]
chart.adapt_on_series(series)
chart.new_chart()
chart.add_axis()
chart.add_curve(series)
print(str(chart))
```

clear_data()

Clears all data

new_chart(minimum=None, maximum=None, n=None)

Clears the canvas

```
from beem.asciichart import AsciiChart
chart = AsciiChart()
series = [1, 2, 3, 7, 2, -4, -2]
chart.adapt_on_series(series)
chart.new_chart()
chart.add_axis()
chart.add_curve(series)
print(str(chart))
```

plot(series, return_str=False)

All in one function for plotting

```
from beem.asciichart import AsciiChart
chart = AsciiChart()
series = [1, 2, 3, 7, 2, -4, -2]
chart.plot(series)
```

set_parameter (*height=None*, *offset=None*, *placeholder=None*)
Can be used to change parameter

beem.asset

class beem.asset.**Asset** (*asset*, *lazy=False*, *full=False*, *blockchain_instance=None*, ***kwargs*)
Bases: *beem.blockchainobject.BlockchainObject*

Deals with Assets of the network.

Parameters

- **Asset** (*str*) – Symbol name or object id of an asset
- **lazy** (*bool*) – Lazy loading
- **full** (*bool*) – Also obtain bitasset-data and dynamic asset dat
- **steem_instance** (*Steem*) – Steem instance

Returns All data of an asset

Note: This class comes with its own caching function to reduce the load on the API server. Instances of this class can be refreshed with `Asset.refresh()`.

```
asset
precision
refresh()
    Refresh the data from the API server
symbol
type_id = 3
```

beem.block

class beem.block.**Block** (*block*, *only_ops=False*, *only_virtual_ops=False*, *full=True*, *lazy=False*, *blockchain_instance=None*, ***kwargs*)
Bases: *beem.blockchainobject.BlockchainObject*

Read a single block from the chain

Parameters

- **block** (*int*) – block number
- **steem_instance** (*Steem*) – Steem instance
- **lazy** (*bool*) – Use lazy loading
- **only_ops** (*bool*) – Includes only operations, when set to True (default: False)
- **only_virtual_ops** (*bool*) – Includes only virtual operations (default: False)

Instances of this class are dictionaries that come with additional methods (see below) that allow dealing with a block and its corresponding functions.

When `only_virtual_ops` is set to True, `only_ops` is always set to True.

In addition to the block data, the block number is stored as `self["id"]` or `self.identifier`.

```
>>> from beem.block import Block
>>> block = Block(1)
>>> print(block)
<Block 1>
```

Note: This class comes with its own caching function to reduce the load on the API server. Instances of this class can be refreshed with `Account.refresh()`.

block_num

Returns the block number

json()**json_operations**

Returns all block operations as list, all dates are strings.

json_transactions

Returns all transactions as list, all dates are strings.

operations

Returns all block operations as list

ops_statistics (add_to_ops_stat=None)

Returns a statistic with the occurrence of the different operation types

refresh()

Even though blocks never change, you freshly obtain its contents from an API with this method

time()

Return a datetime instance for the timestamp of this block

transactions

Returns all transactions as list

class beem.block.**BlockHeader**(block, full=True, lazy=False, blockchain_instance=None, **kwargs)

Bases: `beem.blockchainobject.BlockchainObject`

Read a single block header from the chain

Parameters

- **block** (*int*) – block number
- **steem_instance** ([Steem](#)) – Steem instance
- **lazy** (*bool*) – Use lazy loading

In addition to the block data, the block number is stored as `self["id"]` or `self.identifier`.

```
>>> from beem.block import BlockHeader
>>> block = BlockHeader(1)
>>> print(block)
<BlockHeader 1>
```

block_num

Returns the block number

json()

refresh()

Even though blocks never change, you freshly obtain its contents from an API with this method

time()

Return a datetime instance for the timestamp of this block

beem.blockchain

```
class beem.blockchain.Blockchain(blockchain_instance=None, mode='irreversible',
                                 max_block_wait_repetition=None,
                                 data_refresh_time_seconds=900, **kwargs)
```

Bases: object

This class allows to access the blockchain and read data from it

Parameters

- **blockchain_instance** ([Steem](#)) – Steem instance
- **mode** (*str*) – (default) Irreversible block (`irreversible`) or actual head block (`head`)
- **max_block_wait_repetition** (*int*) – maximum wait repetition for next block where each repetition is block_interval long (default is 3)

This class let's you deal with blockchain related data and methods. Read blockchain related data:

Read current block and blockchain info

```
print(chain.get_current_block())
print(chain.blockchain.info())
```

Monitor for new blocks. When `stop` is not set, monitoring will never stop.

```
blocks = []
current_num = chain.get_current_block_num()
for block in chain.blocks(start=current_num - 99, stop=current_num):
    blocks.append(block)
len(blocks)
```

```
100
```

or each operation individually:

```
ops = []
current_num = chain.get_current_block_num()
for operation in chain.ops(start=current_num - 99, stop=current_num):
    ops.append(operation)
```

awaitTxConfirmation(*transaction*, *limit=10*)

Returns the transaction as seen by the blockchain after being included into a block

Parameters

- **transaction** (*dict*) – transaction to wait for
- **limit** (*int*) – (optional) number of blocks to wait for the transaction (default: 10)

Note: If you want instant confirmation, you need to instantiate class:`beem.blockchain.Blockchain` with `mode="head"`, otherwise, the call will wait until confirmed in an irreversible block.

Note: This method returns once the blockchain has included a transaction with the **same signature**. Even though the signature is not usually used to identify a transaction, it still cannot be forfeited and is derived from the transaction contented and thus identifies a transaction uniquely.

block_time(*block_num*)

Returns a datetime of the block with the given block number.

Parameters **block_num**(*int*) – Block number

block_timestamp(*block_num*)

Returns the timestamp of the block with the given block number as integer.

Parameters **block_num**(*int*) – Block number

blocks(*start=None*, *stop=None*, *max_batch_size=None*, *threading=False*, *thread_num=8*, *only_ops=False*, *only_virtual_ops=False*)

Yields blocks starting from *start*.

Parameters

- **start** (*int*) – Starting block
- **stop** (*int*) – Stop at this block
- **max_batch_size** (*int*) – only for appbase nodes. When not None, batch calls of are used. Cannot be combined with threading
- **threading** (*bool*) – Enables threading. Cannot be combined with batch calls
- **thread_num** (*int*) – Defines the number of threads, when *threading* is set.
- **only_ops** (*bool*) – Only yield operations (default: False). Cannot be combined with *only_virtual_ops=True*.
- **only_virtual_ops** (*bool*) – Only yield virtual operations (default: False)

Note: If you want instant confirmation, you need to instantiate class:*beem.blockchain.Blockchain* with mode="head", otherwise, the call will wait until confirmed in an irreversible block.

find_change_recovery_account_requests(*accounts*)

Find pending *change_recovery_account* requests for one or more specific accounts.

Parameters **accounts** (*str/list*) – account name or list of account names to find *change_recovery_account* requests for.

Returns list of *change_recovery_account* requests for the given account(s).

Return type list

```
>>> from beem.blockchain import Blockchain
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> blockchain = Blockchain(blockchain_instance=stm)
>>> ret = blockchain.find_change_recovery_account_requests('bott')
```

find_rc_accounts(*name*)

Returns the RC parameters of one or more accounts.

Parameters **name** (*str*) – account name to search rc params for (can also be a list of accounts)

Returns RC params

Return type list

```
>>> from beem.blockchain import Blockchain
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> blockchain = Blockchain(blockchain_instance=stm)
>>> ret = blockchain.find_rc_accounts(["test"])
>>> len(ret) == 1
True
```

get_account_count()

Returns the number of accounts

get_account_reputations(*start*=”, *stop*=”, *steps*=1000.0, *limit*=-1, *kwargs*)**

Yields account reputation between start and stop.

Parameters

- **start** (*str*) – Start at this account name
- **stop** (*str*) – Stop at this account name
- **steps** (*int*) – Obtain steps ret with a single call from RPC

get_all_accounts(*start*=”, *stop*=”, *steps*=1000.0, *limit*=-1, *kwargs*)**

Yields account names between start and stop.

Parameters

- **start** (*str*) – Start at this account name
- **stop** (*str*) – Stop at this account name
- **steps** (*int*) – Obtain steps ret with a single call from RPC

get_current_block(*only_ops*=False, *only_virtual_ops*=False)

This call returns the current block

Parameters

- **only_ops** (*bool*) – Returns block with operations only, when set to True (default: False)
- **only_virtual_ops** (*bool*) – Includes only virtual operations (default: False)

Note: The block number returned depends on the mode used when instantiating from this class.

get_current_block_num()

This call returns the current block number

Note: The block number returned depends on the mode used when instantiating from this class.

get_estimated_block_num(*date*, *estimateForwards*=False, *accurate*=True)

This call estimates the block number based on a given date

Parameters **date** (*datetime*) – block time for which a block number is estimated

Note: The block number returned depends on the mode used when instantiating from this class.

```
>>> from beem.blockchain import Blockchain
>>> from datetime import datetime
>>> blockchain = Blockchain()
>>> block_num = blockchain.get_estimated_block_num(datetime(2019, 6, 18, 5, 8,
    ↪ 27))
>>> block_num == 33898184
True
```

get_similar_account_names (name, limit=5)

Returns limit similar accounts with name as list

Parameters

- **name** (*str*) – account name to search similars for
- **limit** (*int*) – limits the number of accounts, which will be returned

Returns Similar account names as list

Return type list

```
>>> from beem.blockchain import Blockchain
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> blockchain = Blockchain(blockchain_instance=stm)
>>> ret = blockchain.get_similar_account_names("test", limit=5)
>>> len(ret) == 5
True
```

get_transaction (transaction_id)

Returns a transaction from the blockchain

Parameters **transaction_id** (*str*) – transaction_id

get_transaction_hex (transaction)

Returns a hexdump of the serialized binary form of a transaction.

Parameters **transaction** (*dict*) – transaction

static hash_op (event)

This method generates a hash of blockchain operation.

is_irreversible_mode ()**list_change_recovery_account_requests (start='', limit=1000, order='by_account')**

List pending *change_recovery_account* requests.

Parameters

- **start** (*str/list*) – Start the listing from this entry. Leave empty to start from the beginning. If *order* is set to *by_account*, *start* has to be an account name. If *order* is set to *by_effective_date*, *start* has to be a list of [effective_on, account_to_recover], e.g. *start*=['2018-12-18T01:46:24', 'bott'].
- **limit** (*int*) – maximum number of results to return (default and maximum: 1000).
- **order** (*str*) – valid values are “*by_account*” (default) or “*by_effective_date*”.

Returns list of *change_recovery_account* requests.

Return type list

```
>>> from beem.blockchain import Blockchain
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> blockchain = Blockchain(blockchain_instance=stm)
>>> ret = blockchain.list_change_recovery_account_requests(limit=1)
```

ops(*start=None, stop=None, only_virtual_ops=False, **kwargs*)

`Blockchain.ops()` is deprecated. Please use `Blockchain.stream()` instead.

ops_statistics(*start, stop=None, add_to_ops_stat=None, with_virtual_ops=True, verbose=False*)

Generates statistics for all operations (including virtual operations) starting from `start`.

Parameters

- **start** (*int*) – Starting block
- **stop** (*int*) – Stop at this block, if set to None, the `current_block_num` is taken
- **add_to_ops_stat** (*dict*) – if set, the result is added to `add_to_ops_stat`
- **verbose** (*bool*) – if True, the current block number and timestamp is printed

This call returns a dict with all possible operations and their occurrence.

stream(*opNames=[], raw_ops=False, *args, **kwargs*)

Yield specific operations (e.g. comments) only

Parameters

- **opNames** (*array*) – List of operations to filter for
- **raw_ops** (*bool*) – When set to True, it returns the unmodified operations (default: False)
- **start** (*int*) – Start at this block
- **stop** (*int*) – Stop at this block
- **max_batch_size** (*int*) – only for appbase nodes. When not None, batch calls of are used. Cannot be combined with threading
- **threading** (*bool*) – Enables threading. Cannot be combined with batch calls
- **thread_num** (*int*) – Defines the number of threads, when `threading` is set.
- **only_ops** (*bool*) – Only yield operations (default: False) Cannot be combined with `only_virtual_ops=True`
- **only_virtual_ops** (*bool*) – Only yield virtual operations (default: False)

The dict output is formated such that `type` carries the operation type. `Timestamp` and `block_num` are taken from the block the operation was stored in and the other keys depend on the actual operation.

Note: If you want instant confirmation, you need to instantiate class:`beem.blockchain.Blockchain` with mode="head", otherwise, the call will wait until confirmed in an irreversible block.

output when `raw_ops=False` is set:

```
{
    'type': 'transfer',
    'from': 'johngreenfield',
    'to': 'thundercurator',
```

(continues on next page)

(continued from previous page)

```
'amount': '0.080 SBD',
'memo': 'https://steemit.com/lofi/@johngreenfield/lofi-joji-yeah-right',
'_id': '6d4c5f2d4d8ef1918acaee4a8dce34f9da384786',
'timestamp': datetime.datetime(2018, 5, 9, 11, 23, 6, tzinfo=<UTC>),
'block_num': 22277588, 'trx_num': 35, 'trx_id':
→'cf11b2ac8493c71063ec121b2e8517ab1e0e6bea'
}
```

output when `raw_ops=True` is set:

```
{
    'block_num': 22277588,
    'op':
        [
            {
                'transfer',
                {
                    'from': 'johngreenfield', 'to': 'thundercurator',
                    'amount': '0.080 SBD',
                    'memo': 'https://steemit.com/lofi/@johngreenfield/lofi-
→joji-yeah-right'
                }
            ],
            'timestamp': datetime.datetime(2018, 5, 9, 11, 23, 6, tzinfo=<UTC>)
}
```

`wait_for_and_get_block`(`block_number`, `blocks_waiting_for=None`, `only_ops=False`,
 `only_virtual_ops=False`, `block_number_check_cnt=-1`,
 `last_current_block_num=None`)

Get the desired block from the chain, if the current head block is smaller (for both head and irreversible) then we wait, but a maximum of `blocks_waiting_for` * `max_block_wait_repetition` time before failure.

Parameters

- **`block_number`** (`int`) – desired block number
- **`blocks_waiting_for`** (`int`) – difference between `block_number` and current head and defines how many blocks we are willing to wait, positive int (default: `None`)
- **`only_ops`** (`bool`) – Returns blocks with operations only, when set to `True` (default: `False`)
- **`only_virtual_ops`** (`bool`) – Includes only virtual operations (default: `False`)
- **`block_number_check_cnt`** (`int`) – limit the number of retries when greater than -1
- **`last_current_block_num`** (`int`) – can be used to reduce the number of `get_current_block_num()` api calls

`class beem.blockchain.Pool`(`thread_count`, `batch_mode=True`, `exception_handler=<function de-`
`fault_handler>`)

Bases: `object`

Pool of threads consuming tasks from a queue

`abort`(`block=False`)

Tell each worker that its done working

`alive()`

Returns `True` if any threads are currently running

```
done()
    Returns True if not tasks are left to be completed

enqueue(func, *args, **kargs)
    Add a task to the queue

idle()
    Returns True if all threads are waiting for work

join()
    Wait for completion of all the tasks in the queue

results(sleep_time=0)
    Get the set of results that have been processed, repeatedly call until done

run(block=False)
    Start the threads, or restart them if you've aborted

class beem.blockchain.Worker(name, queue, results, abort, idle, exception_handler)
Bases: threading.Thread

    Thread executing tasks from a given tasks queue

run()
    Thread work loop calling the function with the params

beem.blockchain.default_handler(name, exception, *args, **kwargs)
```

beem.blockchainobject

```
class beem.blockchainobject.BlockchainObject(data,      klass=None,      space_id=1,
                                              object_id=None,      lazy=False,
                                              use_cache=True,      id_item=None,
                                              blockchain_instance=None,      *args,
                                              **kwargs)
Bases: dict

cache()
static clear_cache()
clear_cache_from_expired_items()
get_cache_auto_clean()
get_cache_expiration()
getcache(id)
iscached(id)

items() → a set-like object providing a view on D's items

json()

set_cache_auto_clean(auto_clean)
set_cache_expiration(expiration)
space_id = 1
test_valid_objectid(i)
testid(id)
```

```
type_id = None
type_ids = []

class beem.blockchainobject.ObjectCache(initial_data={},           default_expiration=10,
                                         auto_clean=True)
Bases: dict

clear_expired_items()
get(key, default)
    Return the value for key if key is in the dictionary, else default.
```

beem.blockchaininstance

```
class beem.blockchaininstance.BlockChainInstance(node='',      rpcuser=None,      rpc-
                                                 password=None,      debug=False,
                                                 data_refresh_time_seconds=900,
                                                 **kwargs)
```

Bases: object

Connect to a Graphene network.

Parameters

- **node** (*str*) – Node to connect to (*optional*)
- **rpcuser** (*str*) – RPC user (*optional*)
- **rpcpassword** (*str*) – RPC password (*optional*)
- **nobroadcast** (*bool*) – Do **not** broadcast a transaction! (*optional*)
- **unsigned** (*bool*) – Do **not** sign a transaction! (*optional*)
- **debug** (*bool*) – Enable Debugging (*optional*)
- **keys** (*array, dict, string*) – Predefine the wif keys to shortcut the wallet database (*optional*)
- **wif** (*array, dict, string*) – Predefine the wif keys to shortcut the wallet database (*optional*)
- **offline** (*bool*) – Boolean to prevent connecting to network (defaults to `False`) (*optional*)
- **expiration** (*int*) – Delay in seconds until transactions are supposed to expire (*optional*) (default is 30)
- **blocking** (*str*) – Wait for broadcasted transactions to be included in a block and return full transaction (can be “head” or “irreversible”)
- **bundle** (*bool*) – Do not broadcast transactions right away, but allow to bundle operations. It is not possible to send out more than one vote operation and more than one comment operation in a single broadcast (*optional*)
- **appbase** (*bool*) – Use the new appbase rpc protocol on nodes with version 0.19.4 or higher. The settings has no effect on nodes with version 0.19.3 or lower.
- **num_retries** (*int*) – Set the maximum number of reconnects to the nodes before NumRetriesReached is raised. Disabled for -1. (default is -1)
- **num_retries_call** (*int*) – Repeat num_retries_call times a rpc call on node error (default is 5)

- **timeout** (*int*) – Timeout setting for https nodes (default is 60)
- **use_sc2** (*bool*) – When True, a steemconnect object is created. Can be used for broadcast posting op or creating hot_links (default is False)
- **steemconnect** (*SteemConnect*) – A SteemConnect object can be set manually, set use_sc2 to True
- **custom_chains** (*dict*) – custom chain which should be added to the known chains

Three wallet operation modes are possible:

- **Wallet Database:** Here, the steemlibs load the keys from the locally stored wallet SQLite database (see `storage.py`). To use this mode, simply call `Steem()` without the `keys` parameter
- **Providing Keys:** Here, you can provide the keys for your accounts manually. All you need to do is add the wif keys for the accounts you want to use as a simple array using the `keys` parameter to `Steem()`.
- **Force keys:** This mode is for advanced users and requires that you know what you are doing. Here, the `keys` parameter is a dictionary that overwrite the `active`, `owner`, `posting` or `memo` keys for any account. This mode is only used for *foreign* signatures!

If no node is provided, it will connect to default nodes of <http://geo.steem.pl>. Default settings can be changed with:

```
steem = Steem(<host>)
```

where `<host>` starts with `https://`, `ws://` or `wss://`.

The purpose of this class is to simplify interaction with Steem.

The idea is to have a class that allows to do this:

```
>>> from beem import Steem
>>> steem = Steem()
>>> print(steem.get_blockchain_version())
```

This class also deals with edits, votes and reading content.

Example for adding a custom chain:

```
from beem import Steem
stm = Steem(node=["https://mytstnet.com"], custom_chains={"MYTESTNET": {
    'chain_assets': [{ 'asset': 'SBD', 'id': 0, 'precision': 3, 'symbol': 'SBD' },
                     { 'asset': 'STEEM', 'id': 1, 'precision': 3, 'symbol': 'STEEM' },
                     { 'asset': 'VESTS', 'id': 2, 'precision': 6, 'symbol': 'VESTS' }],
    'chain_id': '79276aea5d4877d9a25892eaa01b0adf019d3e5cb12a97478df3298ccdd01674',
    'min_version': '0.0.0',
    'prefix': 'MTN'
  }
})
```

backed_token_symbol

get the current chains symbol for SBD (e.g. “TBD” on testnet)

broadcast (*tx=None*)

Broadcast a transaction to the Steem network

Parameters `tx` (*tx*) – Signed transaction to broadcast

chain_params**claim_account** (*creator*, *fee=None*, ***kwargs*)

Claim account for claimed account creation.

When fee is 0 STEEM/HIVE a subsidized account is claimed and can be created later with `create_claimed_account`. The number of subsidized account is limited.**Parameters**

- **creator** (*str*) – which account should pay the registration fee (RC or STEEM/HIVE) (defaults to `default_account`)
- **fee** (*str*) – when set to 0 STEEM (default), claim account is paid by RC

clear()**clear_data()**

Clears all stored blockchain parameters

comment_options (*options*, *identifier*, *beneficiaries=[]*, *account=None*, ***kwargs*)

Set the comment options

Parameters

- **options** (*dict*) – The options to define.
- **identifier** (*str*) – Post identifier
- **beneficiaries** (*list*) – (optional) list of beneficiaries
- **account** (*str*) – (optional) the account to allow access to (defaults to `default_account`)

For the options, you have these defaults::

```
{  
    "author": "",  
    "permlink": "",  
    "max_accepted_payout": "1000000.000 SBD",  
    "percent_steem_dollars": 10000,  
    "allow_votes": True,  
    "allow_curation_rewards": True,  
}
```

connect (*node=*", *rpcuser=*", *rpcpassword=*", ***kwargs*)

Connect to Steem network (internal use only)

create_account (*account_name*, *creator=None*, *owner_key=None*, *active_key=None*, *memo_key=None*, *posting_key=None*, *password=None*, *additional_owner_keys=[]*, *additional_active_keys=[]*, *additional_posting_keys=[]*, *additional_owner_accounts=[]*, *additional_active_accounts=[]*, *additional_posting_accounts=[]*, *storekeys=True*, *store_owner_key=False*, *json_meta=None*, ***kwargs*)

Create new account on Steem

The brainkey/password can be used to recover all generated keys (see `beemgraphenebase.account` for more details).By default, this call will use `default_account` to register a new name `account_name` with all keys being derived from a new brain key that will be returned. The corresponding keys will automatically be installed in the wallet.

Warning: Don't call this method unless you know what you are doing! Be sure to understand what this method does and where to find the private keys for your account.

Note: Please note that this imports private keys (if password is present) into the wallet by default when nobroadcast is set to False. However, it **does not import the owner key** for security reasons by default. If you set store_owner_key to True, the owner key is stored. Do NOT expect to be able to recover it from the wallet if you lose your password!

Note: Account creations cost a fee that is defined by the network. If you create an account, you will need to pay for that fee!

Parameters

- **account_name** (*str*) – **(required)** new account name
- **json_meta** (*str*) – Optional meta data for the account
- **owner_key** (*str*) – Main owner key
- **active_key** (*str*) – Main active key
- **posting_key** (*str*) – Main posting key
- **memo_key** (*str*) – Main memo_key
- **password** (*str*) – Alternatively to providing keys, one can provide a password from which the keys will be derived
- **additional_owner_keys** (*array*) – Additional owner public keys
- **additional_active_keys** (*array*) – Additional active public keys
- **additional_posting_keys** (*array*) – Additional posting public keys
- **additional_owner_accounts** (*array*) – Additional owner account names
- **additional_active_accounts** (*array*) – Additional active account names
- **storekeys** (*bool*) – Store new keys in the wallet (default: True)
- **creator** (*str*) – which account should pay the registration fee (defaults to default_account)

Raises `AccountExistsException` – if the account already exists on the blockchain

```
create_claimed_account(account_name, creator=None, owner_key=None, active_key=None,
                      memo_key=None, posting_key=None, password=None, additional_owner_keys=[],
                      additional_active_keys=[], additional_posting_keys=[],
                      additional_owner_accounts=[], additional_active_accounts=[],
                      storekeys=True, store_owner_key=False, json_meta=None, combine_with_claim_account=False, fee=None, **kwargs)
```

Create new claimed account on Steem

The brainkey/password can be used to recover all generated keys (see `beemgraphenebase.account` for more details).

By default, this call will use `default_account` to register a new name `account_name` with all keys being derived from a new brain key that will be returned. The corresponding keys will automatically be installed in the wallet.

Warning: Don't call this method unless you know what you are doing! Be sure to understand what this method does and where to find the private keys for your account.

Note: Please note that this imports private keys (if password is present) into the wallet by default when nobroadcast is set to False. However, it **does not import the owner key** for security reasons by default. If you set `store_owner_key` to True, the owner key is stored. Do NOT expect to be able to recover it from the wallet if you lose your password!

Note: Account creations cost a fee that is defined by the network. If you create an account, you will need to pay for that fee!

Parameters

- `account_name` (`str`) – **(required)** new account name
- `json_meta` (`str`) – Optional meta data for the account
- `owner_key` (`str`) – Main owner key
- `active_key` (`str`) – Main active key
- `posting_key` (`str`) – Main posting key
- `memo_key` (`str`) – Main memo_key
- `password` (`str`) – Alternatively to providing keys, one can provide a password from which the keys will be derived
- `additional_owner_keys` (`array`) – Additional owner public keys
- `additional_active_keys` (`array`) – Additional active public keys
- `additional_posting_keys` (`array`) – Additional posting public keys
- `additional_owner_accounts` (`array`) – Additional owner account names
- `additional_active_accounts` (`array`) – Additional active account names
- `storekeys` (`bool`) – Store new keys in the wallet (default: `True`)
- `combine_with_claim_account` (`bool`) – When set to `True`, a `claim_account` operation is additionally broadcasted
- `fee` (`str`) – When `combine_with_claim_account` is set to `True`, this parameter is used for the `claim_account` operation
- `creator` (`str`) – which account should pay the registration fee (defaults to `default_account`)

Raises `AccountExistsException` – if the account already exists on the blockchain

`custom_json` (`id, json_data, required_auths=[], required_posting_auths=[], **kwargs`)
Create a custom json operation

Parameters

- **id** (*str*) – identifier for the custom json (max length 32 bytes)
- **json_data** (*json*) – the json data to put into the custom_json operation
- **required_auths** (*list*) – (optional) required auths
- **required_posting_auths** (*list*) – (optional) posting auths

Note: While required auths and required_posting_auths are both optional, one of the two are needed in order to send the custom json.

```
steem.custom_json("id", "json_data",
required_posting_auths=['account'])
```

finalizeOp (*ops, account, permission, **kwargs*)

This method obtains the required private keys if present in the wallet, finalizes the transaction, signs it and broadcasts it

Parameters

- **ops** (*list, GrapheneObject*) – The operation (or list of operations) to broadcast
- **account** (*Account*) – The account that authorizes the operation
- **permission** (*string*) – The required permission for signing (active, owner, posting)
- **append_to** (*TransactionBuilder*) – This allows to provide an instance of TransactionBuilder (see `Steem.new_tx()`) to specify where to put a specific operation.

Note: `append_to` is exposed to every method used in the Steem class

Note: If `ops` is a list of operation, they all need to be signable by the same key! Thus, you cannot combine ops that require active permission with ops that require posting permission. Neither can you use different accounts for different operations!

Note: This uses `Steem.txbuffer()` as instance of `beem.transactionbuilder.TransactionBuilder`. You may want to use your own txbuffer

get_api_methods()

Returns all supported api methods

get_apis()

Returns all enabled apis

get_block_interval (*use_stored_data=True*)

Returns the block interval in seconds

get_blockchain_name (*use_stored_data=True*)

Returns the blockchain version

get_blockchain_version (*use_stored_data=True*)

Returns the blockchain version

get_chain_properties (*use_stored_data=True*)

Return witness elected chain properties

Properties::

```
{  
    'account_creation_fee': '30.000 STEEM',  
    'maximum_block_size': 65536,  
    'sbd_interest_rate': 250  
}
```

get_config (*use_stored_data=True*)

Returns internal chain configuration.

Parameters **use_stored_data** (*bool*) – If True, the cached value is returned

get_current_median_history (*use_stored_data=True*)

Returns the current median price

Parameters **use_stored_data** (*bool*) – if True, stored data will be returned. If stored data are empty or old, refresh_data() is used.

get_default_nodes ()

Returns the default nodes

get_dust_threshold (*use_stored_data=True*)

Returns the vote dust threshold

get_dynamic_global_properties (*use_stored_data=True*)

This call returns the *dynamic global properties*

Parameters **use_stored_data** (*bool*) – if True, stored data will be returned. If stored data are empty or old, refresh_data() is used.

get_feed_history (*use_stored_data=True*)

Returns the feed_history

Parameters **use_stored_data** (*bool*) – if True, stored data will be returned. If stored data are empty or old, refresh_data() is used.

get_hardfork_properties (*use_stored_data=True*)

Returns Hardfork and live_time of the hardfork

Parameters **use_stored_data** (*bool*) – if True, stored data will be returned. If stored data are empty or old, refresh_data() is used.

get_median_price (*use_stored_data=True*)

Returns the current median history price as Price

get_network (*use_stored_data=True, config=None*)

Identify the network

Parameters **use_stored_data** (*bool*) – if True, stored data will be returned. If stored data are empty or old, refresh_data() is used.

Returns Network parameters

Return type dictionary

get_rc_cost (*resource_count*)

Returns the RC costs based on the resource_count

get_reserve_ratio ()

This call returns the *reserve ratio*

```
get_resource_params()
    Returns the resource parameter

get_resource_pool()
    Returns the resource pool

get_reward_funds (use_stored_data=True)
    Get details for a reward fund.

    Parameters use_stored_data (bool) – if True, stored data will be returned. If stored data
    are empty or old, refresh_data() is used.

get_witness_schedule (use_stored_data=True)
    Return witness elected chain properties

hardfork

info (use_stored_data=True)
    Returns the global properties

is_connected()
    Returns if rpc is connected

is_hive

is_steem

move_current_node_to_front()
    Returns the default node list, until the first entry is equal to the current working node url

newWallet (pwd)
    Create a new wallet. This method is basically only calls beem.wallet.Wallet.create().

    Parameters pwd (str) – Password to use for the new wallet
    Raises WalletExists – if there is already a wallet created

new_tx (*args, **kwargs)
    Let's obtain a new txbuffer

    Returns id of the new txbuffer

    Return type int

post (title, body, author=None, permalink=None, reply_identifier=None, json_metadata=None,
      comment_options=None, community=None, app=None, tags=None, beneficiaries=None,
      self_vote=False, parse_body=False, **kwargs)
    Create a new post. If this post is intended as a reply/comment, reply_identifier needs to be set with the
    identifier of the parent post/comment (eg. @author/permalink). Optionally you can also set json_metadata,
    comment_options and upvote the newly created post as an author. Setting category, tags or community
    will override the values provided in json_metadata and/or comment_options where appropriate.

    Parameters
        • title (str) – Title of the post
        • body (str) – Body of the post/comment
        • author (str) – Account are you posting from
        • permalink (str) – Manually set the permalink (defaults to None). If left empty, it will be
          derived from title automatically.
        • reply_identifier (str) – Identifier of the parent post/comment (only if this post is
          a reply/comment).
```

- **json_metadata** (*str, dict*) – JSON meta object that can be attached to the post.
- **comment_options** (*dict*) – JSON options object that can be attached to the post.

Example:

```
comment_options = {  
    'max_accepted_payout': '1000000.000 SBD',  
    'percent_steem_dollars': 10000,  
    'allow_votes': True,  
    'allow_curation_rewards': True,  
    'extensions': [[0, {  
        'beneficiaries': [  
            {'account': 'account1', 'weight': 5000},  
            {'account': 'account2', 'weight': 5000},  
        ]  
    }]  
}]
```

Parameters

- **community** (*str*) – (Optional) Name of the community we are posting into. This will also override the community specified in *json_metadata* and the category
- **app** (*str*) – (Optional) Name of the app which are used for posting when not set, beem/<version> is used
- **tags** (*str, list*) – (Optional) A list of tags to go with the post. This will also override the tags specified in *json_metadata*. The first tag will be used as a ‘category’ when community is not specified. If provided as a string, it should be space separated.
- **beneficiaries** (*list*) – (Optional) A list of beneficiaries for posting reward distribution. This argument overrides beneficiaries as specified in *comment_options*.

For example, if we would like to split rewards between account1 and account2:

```
beneficiaries = [  
    {'account': 'account1', 'weight': 5000},  
    {'account': 'account2', 'weight': 5000}  
]
```

Parameters

- **self_vote** (*bool*) – (Optional) Upvote the post as author, right after posting.
- **parse_body** (*bool*) – (Optional) When set to True, all mentioned users, used links and images are put into users, links and images array inside *json_metadata*. This will override provided links, images and users inside *json_metadata*. Hashtags will added to tags until its length is below five entries.

prefix

refresh_data (*chain_property, force_refresh=False, data_refresh_time_seconds=None*)

Read and stores steem blockchain parameters If the last data refresh is older than *data_refresh_time_seconds*, data will be refreshed

Parameters

- **force_refresh** (*bool*) – if True, a refresh of the data is enforced

- **data_refresh_time_seconds** (*float*) – set a new minimal refresh time in seconds

set_default_account (*account*)

Set the default account to be used

set_default_nodes (*nodes*)

Set the default nodes to be used

set_default_vote_weight (*vote_weight*)

Set the default vote weight to be used

set_password_storage (*password_storage*)

Set the password storage mode.

When set to “no”, the password has to be provided each time. When set to “environment” the password is taken from the UNLOCK variable

When set to “keyring” the password is taken from the python keyring module. A wallet password can be stored with python -m keyring set beem wallet password

Parameters **password_storage** (*str*) – can be “no”, “keyring” or “environment”

sign (*tx=None, wifs=[], reconstruct_tx=True*)

Sign a provided transaction with the provided key(s)

Parameters

- **tx** (*dict*) – The transaction to be signed and returned
- **wifs** (*string*) – One or many wif keys to use for signing a transaction. If not present, the keys will be loaded from the wallet as defined in “missing_signatures” key of the transactions.
- **reconstruct_tx** (*bool*) – when set to False and tx is already contructed, it will not reconstructed and already added signatures remain

switch_blockchain (*blockchain, update_nodes=False*)

Switches the connected blockchain. Can be either hive or steem.

Parameters

- **blockchain** (*str*) – can be “hive” or “steem”
- **update_nodes** (*bool*) – When true, the nodes are updated, using NodeList.update_nodes()

token_symbol

get the current chains symbol for STEEM (e.g. “TESTS” on testnet)

tx()

Returns the default transaction buffer

txbuffer

Returns the currently active tx buffer

unlock (**args*, ***kwargs*)

Unlock the internal wallet

update_account (*account, owner_key=None, active_key=None, memo_key=None, posting_key=None, password=None, additional_owner_keys=[], additional_active_keys=[], additional_posting_keys=[], additional_active_accounts=[], additional_posting_accounts=None, storekeys=True, store_owner_key=False, json_meta=None, **kwargs*)

Update account

The brainkey/password can be used to recover all generated keys (see `beemgraphenebase.account` for more details).

The corresponding keys will automatically be installed in the wallet.

Warning: Don't call this method unless you know what you are doing! Be sure to understand what this method does and where to find the private keys for your account.

Note: Please note that this imports private keys (if password is present) into the wallet by default when nobroadcast is set to False. However, it **does not import the owner key** for security reasons by default. If you set store_owner_key to True, the owner key is stored. Do NOT expect to be able to recover it from the wallet if you lose your password!

Parameters

- **account_name** (`str`) – (required) account name
- **json_meta** (`str`) – Optional updated meta data for the account
- **owner_key** (`str`) – Main owner (public) key
- **active_key** (`str`) – Main active (public) key
- **posting_key** (`str`) – Main posting (public) key
- **memo_key** (`str`) – Main memo (public) key
- **password** (`str`) – Alternatively to providing keys, one can provide a password from which the keys will be derived
- **additional_owner_keys** (`array`) – Additional owner public keys
- **additional_active_keys** (`array`) – Additional active public keys
- **additional_posting_keys** (`array`) – Additional posting public keys
- **additional_owner_accounts** (`array`) – Additional owner account names
- **additional_active_accounts** (`array`) – Additional active account names
- **storekeys** (`bool`) – Store new keys in the wallet (default: `True`)

Raises `AccountExistsException` – if the account already exists on the blockchain

update_proposal_votes (`proposal_ids, approve, account=None, **kwargs`)
Update proposal votes

Parameters

- **proposal_ids** (`list`) – list of proposal ids
- **approve** (`bool`) – True/False
- **account** (`str`) – (optional) witness account name

vest_token_symbol
get the current chains symbol for VESTS

vests_to_rshares (*vests*, *voting_power*=10000, *vote_pct*=10000, *subtract_dust_threshold*=True, *use_stored_data*=True)

Obtain the r-shares from vests

Parameters

- **vests** (*number*) – vesting shares
- **voting_power** (*int*) – voting power (100% = 10000)
- **vote_pct** (*int*) – voting percentage (100% = 10000)

vote (*weight*, *identifier*, *account*=None, ***kwargs*)

Vote for a post

Parameters

- **weight** (*float*) – Voting weight. Range: -100.0 - +100.0.
- **identifier** (*str*) – Identifier for the post to vote. Takes the form @author/permlink.
- **account** (*str*) – (optional) Account to use for voting. If account is not defined, the default_account will be used or a ValueError will be raised

witness_set_properties (*wif*, *owner*, *props*, *use_condenser_api*=True)

Set witness properties

Parameters

- **wif** (*str*) – Private signing key
- **props** (*dict*) – Properties
- **owner** (*str*) – witness account name

Properties::

```
{
    "account_creation_fee": x,
    "account_subsidy_budget": x,
    "account_subsidy_decay": x,
    "maximum_block_size": x,
    "url": x,
    "sbd_exchange_rate": x,
    "sbd_interest_rate": x,
    "new_signing_key": x
}
```

witness_update (*signing_key*, *url*, *props*, *account*=None, ***kwargs*)

Creates/updates a witness

Parameters

- **signing_key** (*str*) – Public signing key
- **url** (*str*) – URL
- **props** (*dict*) – Properties
- **account** (*str*) – (optional) witness account name

Properties::

```
{  
    "account_creation_fee": "3.000 STEEM",  
    "maximum_block_size": 65536,  
    "sbd_interest_rate": 0,  
}
```

beem.comment

```
class beem.comment.Comment (authorperm,      use_tags_api=True,      full=True,      lazy=False,  
                           blockchain_instance=None, **kwargs)  
Bases: beem.blockchainobject.BlockchainObject
```

Read data about a Comment/Post in the chain

Parameters

- **authorperm** (*str*) – identifier to post/comment in the form of @author/permlink
- **use_tags_api** (*boolean*) – when set to False, list_comments from the database_api is used
- **blockchain_instance** (*Steem*) – *beem.steem.Steem* instance to use when accessing a RPC

```
>>> from beem.comment import Comment  
>>> from beem.account import Account  
>>> from beem import Steem  
>>> stm = Steem()  
>>> acc = Account("gtg", blockchain_instance=stm)  
>>> authorperm = acc.get_blog(limit=1)[0]["authorperm"]  
>>> c = Comment(authorperm)  
>>> postdate = c["created"]  
>>> postdate_str = c.json()["created"]
```

author

authorperm

body

category

curation_penalty_compensation_SBD()

Returns The required post payout amount after 15 minutes which will compensate the curation penalty, if voting earlier than 15 minutes

delete (*account=None, identifier=None*)

Delete an existing post/comment

Parameters

- **account** (*str*) – (optional) Account to use for deletion. If account is not defined, the default_account will be taken or a ValueError will be raised.
- **identifier** (*str*) – (optional) Identifier for the post to delete. Takes the form @author/permlink. By default the current post will be used.

Note: A post/comment can only be deleted as long as it has no replies and no positive rshares on it.

depth**downvote** (*weight=100, voter=None*)

Downvote the post

Parameters

- **weight** (*float*) – (optional) Weight for posting (-100.0 - +100.0) defaults to -100.0
- **voter** (*str*) – (optional) Voting account

edit (*body, meta=None, replace=False*)

Edit an existing post

Parameters

- **body** (*str*) – Body of the reply
- **meta** (*json*) – JSON meta object that can be attached to the post. (optional)
- **replace** (*bool*) – Instead of calculating a *diff*, replace the post entirely (defaults to False)

estimate_curation_SBD (*vote_value_SBD, estimated_value_SBD=None*)

Estimates curation reward

Parameters

- **vote_value_SBD** (*float*) – The vote value in SBD for which the curation should be calculated
- **estimated_value_SBD** (*float*) – When set, this value is used for calculate the curation. When not set, the current post value is used.

get_all_replies (*parent=None*)

Returns all content replies

get_author_rewards ()

Returns the author rewards.

Example:

```
{
    'pending_rewards': True,
    'payout_SP': 0.912 STEEM,
    'payout_SBD': 3.583 SBD,
    'total_payout_SBD': 7.166 SBD
}
```

get_beneficiaries_pct ()

Returns the sum of all post beneficiaries in percentage

get_curation_penalty (*vote_time=None*)

If post is less than 5 minutes old, it will incur a curation reward penalty.

Parameters **vote_time** (*datetime*) – A vote time can be given and the curation penalty is calculated regarding the given time (default is None) When set to None, the current date is used.

Returns Float number between 0 and 1 (0.0 -> no penalty, 1.0 -> 100 % curation penalty)

Return type float

get_curation_rewards (*pending_payout_SBD=False*, *pending_payout_value=None*)

Returns the curation rewards. The split between creator/curator is currently 50%/50%.

Parameters

- **pending_payout_SBD** (*bool*) – If True, the rewards are returned in SBD and not in STEEM (default is False)
- **pending_payout_value** (*float, str*) – When not None this value instead of the current value is used for calculating the rewards

pending_rewards is True when the post is younger than 7 days. *unclaimed_rewards* is the amount of curation_rewards that goes to the author (self-vote or votes within the first 30 minutes). *active_votes* contains all voter with their curation reward.

Example:

```
{  
    'pending_rewards': True, 'unclaimed_rewards': 0.245 STEEM,  
    'active_votes': {  
        'leprechaun': 0.006 STEEM, 'timcliff': 0.186 STEEM,  
        'st3llar': 0.000 STEEM, 'crokkon': 0.015 STEEM, 'feedyourminnows': 0.  
        ↵003 STEEM,  
        'isnochys': 0.003 STEEM, 'loshcat': 0.001 STEEM, 'greenorange': 0.000  
        ↵STEEM,  
        'qustodian': 0.123 STEEM, 'jpphotography': 0.002 STEEM, 'thinkingmind  
        ↵': 0.001 STEEM,  
        'oups': 0.006 STEEM, 'mattockfs': 0.001 STEEM, 'holger80': 0.003  
        ↵STEEM, 'michaelizer': 0.004 STEEM,  
        'flugschwein': 0.010 STEEM, 'ulisesababeque': 0.000 STEEM, 'hakancelik  
        ↵': 0.002 STEEM, 'sbi2': 0.008 STEEM,  
        'zcool': 0.000 STEEM, 'steemhq': 0.002 STEEM, 'rowdiya': 0.000 STEEM,  
        ↵'qurator-tier-1-2': 0.012 STEEM  
    }  
}
```

get_parent (*children=None*)

Returns the parent post with depth == 0

get_reblogged_by (*identifier=None*)

Shows in which blogs this post appears

get_replies (*raw_data=False*, *identifier=None*)

Returns content replies

Parameters raw_data (*bool*) – When set to False, the replies will be returned as Comment class objects

get_rewards ()

Returns the total_payout, author_payout and the curator payout in SBD. When the payout is still pending, the estimated payout is given out.

Note: Potential beneficiary rewards were already deducted from the *author_payout* and the *total_payout*

Example::

```
{
    'total_payout': 9.956 SBD,
    'author_payout': 7.166 SBD,
    'curator_payout': 2.790 SBD
}
```

get_vote_with_curation(voter=None, raw_data=False, pending_payout_value=None)

Returns vote for voter. Returns None, if the voter cannot be found in *active_votes*.

Parameters

- **voter** (*str*) – Voter for which the vote should be returned
- **raw_data** (*bool*) – If True, the raw data are returned
- **pending_payout_SBD** (*float, str*) – When not None this value instead of the current value is used for calculating the rewards

get_votes(raw_data=False)

Returns all votes as ActiveVotes object

id**is_comment()**

Returns True if post is a comment

is_main_post()

Returns True if main post, and False if this is a comment (reply).

is_pending()

Returns if the payout is pending (the post/comment is younger than 7 days)

json()**json_metadata****parent_author****parent_permalink****permalink****refresh()****reply(body, title='', author='', meta=None)**

Reply to an existing post

Parameters

- **body** (*str*) – Body of the reply
- **title** (*str*) – Title of the reply post
- **author** (*str*) – Author of reply (optional) if not provided `default_user` will be used, if present, else a `ValueError` will be raised.
- **meta** (*json*) – JSON meta object that can be attached to the post. (optional)

resteem(identifier=None, account=None)

Resteem a post

Parameters

- **identifier** (*str*) – post identifier (@<account>/<permlink>)

- **account** (*str*) – (optional) the account to allow access to (defaults to default_account)

reward

Return the estimated total SBD reward.

time_elapsed()

Returns a timedelta on how old the post is.

title

type_id = 8

upvote (weight=100, voter=None)

Upvote the post

Parameters

- **weight** (*float*) – (optional) Weight for posting (-100.0 - +100.0) defaults to +100.0
- **voter** (*str*) – (optional) Voting account

vote (weight, account=None, identifier=None, **kwargs)

Vote for a post

Parameters

- **weight** (*float*) – Voting weight. Range: -100.0 - +100.0.
- **account** (*str*) – (optional) Account to use for voting. If account is not defined, the default_account will be used or a ValueError will be raised
- **identifier** (*str*) – Identifier for the post to vote. Takes the form @author/permlink.

class beem.comment.RankedPosts (sort='trending', tag='', observer='', lazy=False, full=True, blockchain_instance=None, **kwargs)

Bases: list

Obtain a list of ranked posts

Parameters

- **account** (*str*) – Account name
- **blockchain_instance** ([Steem](#)) – Steem() instance to use when accesing a RPC

class beem.comment.RecentByPath (path='trending', category=None, lazy=False, full=True, blockchain_instance=None, **kwargs)

Bases: list

Obtain a list of posts recent by path

Parameters

- **account** (*str*) – Account name
- **blockchain_instance** ([Steem](#)) – Steem() instance to use when accesing a RPC

class beem.comment.RecentReplies (author, skip_own=True, lazy=False, full=True, blockchain_instance=None, **kwargs)

Bases: list

Obtain a list of recent replies

Parameters

- **author** (*str*) – author

- **skip_own** (*bool*) – (optional) Skip replies of the author to him/herself. Default: True
- **blockchain_instance** (*Steem*) – Steem() instance to use when accesing a RPC

beem.conveyor

```
class beem.conveyor.Conveyor(url='https://conveyor.steemit.com', blockchain_instance=None,  
                           **kwargs)
```

Bases: object

Class to access Steemit Conveyor instances: <https://github.com/steemit/conveyor>

Description from the official documentation:

- Feature flags: “Feature flags allows our apps (condenser mainly) to hide certain features behind flags.”
- User data: “Conveyor is the central point for storing sensitive user data (email, phone, etc). No other services should store this data and should instead query for it here every time.”
- User tags: “Tagging mechanism for other services, allows defining and assigning tags to accounts (or other identifiers) and querying for them.”

Not contained in the documentation, but implemented and working:

- Draft handling: saving, listing and removing post drafts consisting of a post title and a body.

The underlying RPC authentication and request signing procedure is described here: <https://github.com/steemit/rpc-auth>

get_feature_flag (*account*, *flag*, *signing_account=None*)

Test if a specific feature flag is set for an account. The request has to be signed by the requested account or an admin account.

Parameters

- **account** (*str*) – requested account
- **flag** (*str*) – flag to be tested
- **signing_account** (*str*) – (optional) account to sign the request. If unset, *account* is used.

Example:

```
from beem import Steem
from beem.conveyor import Conveyor
s = Steem(keys=["5JPOSTINGKEY"])
c = Conveyor(blockchain_instance=s)
print(c.get_feature_flag('accountname', 'accepted_tos'))
```

get_feature_flags (*account*, *signing_account=None*)

Get the account's feature flags. The request has to be signed by the requested account or an admin account.

Parameters

- **account** (*str*) – requested account
- **signing_account** (*str*) – (optional) account to sign the request. If unset, *account* is used.

Example:

```
from beem import Steem
from beem.conveyor import Conveyor
s = Steem(keys=["5JPOSTINGKEY"])
c = Conveyor(blockchain_instance=s)
print(c.get_feature_flags('accountname'))
```

get_user_data(*account*, *signing_account*=None)

Get the account's email address and phone number. The request has to be signed by the requested account or an admin account.

Parameters

- **account** (*str*) – requested account
- **signing_account** (*str*) – (optional) account to sign the request. If unset, *account* is used.

Example:

```
from beem import Steem
from beem.conveyor import Conveyor
s = Steem(keys=["5JPOSTINGKEY"])
c = Conveyor(blockchain_instance=s)
print(c.get_user_data('accountname'))
```

healthcheck()

Get the Conveyor status

Sample output:

```
{  
    'ok': True, 'version': '1.1.1-4d28e36-1528725174',  
    'date': '2018-07-21T12:12:25.502Z'  
}
```

list_drafts(*account*)

List all saved drafts from *account*

Parameters **account** (*str*) – requested account

Sample output:

```
{  
    'jsonrpc': '2.0', 'id': 2, 'result': [  
        {'title': 'draft-title', 'body': 'draft-body',  
         'uuid': '06497ele-ac30-48cb-a069-27e1672924c9'}  
    ]  
}
```

prehash_message(*timestamp*, *account*, *method*, *params*, *nonce*)

Prepare a hash for the Conveyor API request with SHA256 according to <https://github.com/steemit/rpc-auth> Hashing of *second* is then done inside *ecdsasig.sign_message()*.

Parameters

- **timestamp** (*str*) – valid iso8601 datetime ending in “Z”
- **account** (*str*) – valid steem blockchain account name
- **method** (*str*) – Conveyor method name to be called
- **param** (*bytes*) – base64 encoded request parameters

- **nonce** (*bytes*) – random 8 bytes

remove_draft (*account, uuid*)

Remove a draft from the Conveyor database

Parameters

- **account** (*str*) – requested account
- **uuid** (*str*) – draft identifier as returned from *list_drafts*

save_draft (*account, title, body*)

Save a draft in the Conveyor database

Parameters

- **account** (*str*) – requested account
- **title** (*str*) – draft post title
- **body** (*str*) – draft post body

set_user_data (*account, params, signing_account=None*)

Set the account's email address and phone number. The request has to be signed by an admin account.

Parameters

- **account** (*str*) – requested account
- **param** (*dict*) – user data to be set
- **signing_account** (*str*) – (optional) account to sign the request. If unset, *account* is used.

Example:

```
from beem import Steem
from beem.conveyor import Conveyor
s = Steem(keys=["5JADMINPOSTINGKEY"])
c = Conveyor(blockchain_instance=s)
userdata = {'email': 'foo@bar.com', 'phone': '+123456789'}
c.set_user_data('accountname', userdata, 'adminaccountname')
```

beem.discussions

```
class beem.discussions.Comment_discussions_by_payout(discussion_query, lazy=False,
                                                       use_appbase=False,
                                                       raw_data=False,
                                                       blockchain_instance=None,
                                                       **kwargs)
```

Bases: list

Get comment_discussions_by_payout

Parameters

- **discussion_query** (*Query*) – Defines the parameter for searching posts
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** (*Steem*) – Steem instance

```
from beem.discussions import Query, Comment_discussions_by_payout
q = Query(limit=10)
for h in Comment_discussions_by_payout(q):
    print(h)
```

class beem.discussions.Discussions(*lazy=False*,
 use_appbase=False,
 blockchain_instance=None, ***kwargs*)

Bases: object

Get Discussions

Parameters **blockchain_instance** ([Steem](#)) – Steem instance

get_discussions (*discussion_type*, *discussion_query*, *limit=1000*, *raw_data=False*)

Get Discussions

Parameters

- **discussion_type** (*str*) – Defines the used discussion query
- **discussion_query** ([Query](#)) – Defines the parameter for searching posts
- **raw_data** (*bool*) – returns list of comments when False, default is False

```
from beem.discussions import Query, Discussions
query = Query(limit=51, tag="steemit")
discussions = Discussions()
count = 0
for d in discussions.get_discussions("tags", query, limit=200):
    print("%d. " % (count + 1)) + str(d)
    count += 1
```

class beem.discussions.Discussions_by_active(*discussion_query*,
 lazy=False,
 use_appbase=False, *raw_data=False*,
 blockchain_instance=None, ***kwargs*)

Bases: list

get_discussions_by_active

Parameters

- **discussion_query** ([Query](#)) – Defines the parameter searching posts
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** ([Steem](#)) – Steem() instance to use when accesing a RPC

```
from beem.discussions import Query, Discussions_by_active
q = Query(limit=10)
for h in Discussions_by_active(q):
    print(h)
```

```
class beem.discussions.Discussions_by_author_before_date(author="",
                                                       start_permalink="",
                                                       before_date='1970-01-01T00:00:00',
                                                       limit=100, lazy=False,
                                                       use_appbase=False,
                                                       raw_data=False,
                                                       blockchain_instance=None,
                                                       **kwargs)
```

Bases: list

Get Discussions by author before date

Note: To retrieve discussions before date, the time of creation of the discussion @author/start_permalink must be older than the specified before_date parameter.

Parameters

- **author** (*str*) – Defines the author (*required*)
- **start_permalink** (*str*) – Defines the permalink of a starting discussion
- **before_date** (*str*) – Defines the before date for query
- **limit** (*int*) – Defines the limit of discussions
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** (*Steem*) – Steem instance

```
from beem.discussions import Query, Discussions_by_author_before_date
for h in Discussions_by_author_before_date(limit=10, author="gtg") :
    print(h)
```

```
class beem.discussions.Discussions_by_blog(discussion_query,           lazy=False,
                                             use_appbase=False,          raw_data=False,
                                             blockchain_instance=None, **kwargs)
```

Bases: list

Get discussions by blog

Parameters

- **discussion_query** (*Query*) – Defines the parameter searching posts, tag musst be set to a username
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** (*Steem*) – Steem instance

```
from beem.discussions import Query, Discussions_by_blog
q = Query(limit=10)
for h in Discussions_by_blog(q) :
    print(h)
```

```
class beem.discussions.Discussions_by_cashout(discussion_query,           lazy=False,
                                              use_appbase=False,    raw_data=False,
                                              blockchain_instance=None, **kwargs)
```

Bases: list

Get discussions_by_cashout. This query seems to be broken at the moment. The output is always empty.

Parameters

- **discussion_query** ([Query](#)) – Defines the parameter searching posts
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** ([Steem](#)) – Steem instance

```
from beem.discussions import Query, Discussions_by_cashout
q = Query(limit=10)
for h in Discussions_by_cashout(q):
    print(h)
```

```
class beem.discussions.Discussions_by_children(discussion_query,           lazy=False,
                                                use_appbase=False,   raw_data=False,
                                                blockchain_instance=None, **kwargs)
```

Bases: list

Get discussions by children

Parameters

- **discussion_query** ([Query](#)) – Defines the parameter searching posts
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** ([Steem](#)) – Steem instance

```
from beem.discussions import Query, Discussions_by_children
q = Query(limit=10)
for h in Discussions_by_children(q):
    print(h)
```

```
class beem.discussions.Discussions_by_comments(discussion_query,           lazy=False,
                                                use_appbase=False,   raw_data=False,
                                                blockchain_instance=None, **kwargs)
```

Bases: list

Get discussions by comments

Parameters

- **discussion_query** ([Query](#)) – Defines the parameter searching posts, start_author and start_permlink must be set.
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** ([Steem](#)) – Steem instance

```
from beem.discussions import Query, Discussions_by_comments
q = Query(limit=10, start_author="steemit", start_permalink="firstpost")
for h in Discussions_by_comments(q):
    print(h)
```

class beem.discussions.Discussions_by_created(discussion_query, lazy=False, use_appbase=False, raw_data=False, blockchain_instance=None, **kwargs)

Bases: list

Get discussions_by_created

Parameters

- **discussion_query** (`Query`) – Defines the parameter for searching posts
- **use_appbase** (`bool`) – use condenser call when set to False, default is False
- **raw_data** (`bool`) – returns list of comments when False, default is False
- **blockchain_instance** (`Steem`) – Steem instance

```
from beem.discussions import Query, Discussions_by_created
q = Query(limit=10)
for h in Discussions_by_created(q):
    print(h)
```

class beem.discussions.Discussions_by_feed(discussion_query, lazy=False, use_appbase=False, raw_data=False, blockchain_instance=None, **kwargs)

Bases: list

Get discussions by feed

Parameters

- **discussion_query** (`Query`) – Defines the parameter searching posts, tag must be set to a username
- **use_appbase** (`bool`) – use condenser call when set to False, default is False
- **raw_data** (`bool`) – returns list of comments when False, default is False
- **blockchain_instance** (`Steem`) – Steem instance

```
from beem.discussions import Query, Discussions_by_feed
q = Query(limit=10, tag="steem")
for h in Discussions_by_feed(q):
    print(h)
```

class beem.discussions.Discussions_by_hot(discussion_query, lazy=False, use_appbase=False, raw_data=False, blockchain_instance=None, **kwargs)

Bases: list

Get discussions by hot

Parameters

- **discussion_query** (`Query`) – Defines the parameter searching posts
- **use_appbase** (`bool`) – use condenser call when set to False, default is False
- **raw_data** (`bool`) – returns list of comments when False, default is False

- **blockchain_instance** ([Steem](#)) – Steem instance

```
from beem.discussions import Query, Discussions_by_hot
q = Query(limit=10, tag="steem")
for h in Discussions_by_hot(q):
    print(h)
```

```
class beem.discussions.Discussions_by_promoted(discussion_query,           lazy=False,
                                                use_appbase=False,   raw_data=False,
                                                blockchain_instance=None, **kwargs)
```

Bases: list

Get discussions by promoted

Parameters

- **discussion_query** ([Query](#)) – Defines the parameter searching posts
- **use_appbase** ([bool](#)) – use condenser call when set to False, default is False
- **raw_data** ([bool](#)) – returns list of comments when False, default is False
- **blockchain_instance** ([Steem](#)) – Steem instance

```
from beem.discussions import Query, Discussions_by_promoted
q = Query(limit=10, tag="steem")
for h in Discussions_by_promoted(q):
    print(h)
```

```
class beem.discussions.Discussions_by_trending(discussion_query,           lazy=False,
                                                use_appbase=False,   raw_data=False,
                                                blockchain_instance=None, **kwargs)
```

Bases: list

Get Discussions by trending

Parameters

- **discussion_query** ([Query](#)) – Defines the parameter for searching posts
- **blockchain_instance** ([Steem](#)) – Steem instance
- **raw_data** ([bool](#)) – returns list of comments when False, default is False

```
from beem.discussions import Query, Discussions_by_trending
q = Query(limit=10, tag="steem")
for h in Discussions_by_trending(q):
    print(h)
```

```
class beem.discussions.Discussions_by_votes(discussion_query,           lazy=False,
                                              use_appbase=False,   raw_data=False,
                                              blockchain_instance=None, **kwargs)
```

Bases: list

Get discussions_by_votes

Parameters

- **discussion_query** ([Query](#)) – Defines the parameter searching posts
- **use_appbase** ([bool](#)) – use condenser call when set to False, default is False
- **raw_data** ([bool](#)) – returns list of comments when False, default is False
- **blockchain_instance** ([Steem](#)) – Steem instance

```
from beem.discussions import Query, Discussions_by_votes
q = Query(limit=10)
for h in Discussions_by_votes(q):
    print(h)
```

```
class beem.discussions.Post_discussions_by_payout(discussion_query,      lazy=False,
                                                    use_appbase=False,
                                                    raw_data=False,
                                                    blockchain_instance=None,
                                                    **kwargs)
```

Bases: list

Get post_discussions_by_payout

Parameters

- **discussion_query** (`Query`) – Defines the parameter for searching posts
- **use_appbase** (`bool`) – use condenser call when set to False, default is False
- **raw_data** (`bool`) – returns list of comments when False, default is False
- **blockchain_instance** (`Steem`) – Steem instance

```
from beem.discussions import Query, Post_discussions_by_payout
q = Query(limit=10)
for h in Post_discussions_by_payout(q):
    print(h)
```

```
class beem.discussions.Query(limit=0,    tag="",    truncate_body=0,    filter_tags=[],    se-
                                lect_authors=[],    select_tags=[],    start_author=None,
                                start_permalink=None,    start_tag=None,    parent_author=None,
                                parent_permalink=None,    start_parent_author=None,    be-
                                fore_date=None,    author=None)
```

Bases: dict

Query to be used for all discussion queries

Parameters

- **limit** (`int`) – limits the number of posts
- **tag** (`str`) – tag query
- **truncate_body** (`int`) –
- **filter_tags** (`array`) –
- **select_authors** (`array`) –
- **select_tags** (`array`) –
- **start_author** (`str`) –
- **start_permalink** (`str`) –
- **start_tag** (`str`) –
- **parent_author** (`str`) –
- **parent_permalink** (`str`) –
- **start_parent_author** (`str`) –
- **before_date** (`str`) –

- **author** (*str*) – Author (see Discussions_by_author_before_date)

```
from beem.discussions import Query
query = Query(limit=10, tag="steemit")
```

```
class beem.discussions.Replies_by_last_update(discussion_query, lazy=False,
                                                use_appbase=False, raw_data=False,
                                                blockchain_instance=None, **kwargs)
```

Bases: list

Returns a list of replies by last update

Parameters

- **discussion_query** (*Query*) – Defines the parameter searching posts start_parent_author and start_permalink must be set.
- **use_appbase** (*bool*) – use condenser call when set to False, default is False
- **raw_data** (*bool*) – returns list of comments when False, default is False
- **blockchain_instance** (*Steem*) – Steem instance

```
from beem.discussions import Query, Replies_by_last_update
q = Query(limit=10, start_parent_author="steemit", start_permalink="firstpost")
for h in Replies_by_last_update(q):
    print(h)
```

```
class beem.discussions.Trending_tags(discussion_query, lazy=False, use_appbase=False,
                                       blockchain_instance=None, **kwargs)
```

Bases: list

Returns the list of trending tags.

Parameters

- **discussion_query** (*Query*) – Defines the parameter searching posts, start_tag can be set. :param bool use_appbase: use condenser call when set to False, default is False
- **blockchain_instance** (*Steem*) – Steem instance

```
from beem.discussions import Query, Trending_tags
q = Query(limit=10, start_tag="")
for h in Trending_tags(q):
    print(h)
```

beem.exceptions

```
exception beem.exceptions.AccountDoesNotExistException
```

Bases: Exception

The account does not exist

```
exception beem.exceptions.AccountExistsException
```

Bases: Exception

The requested account already exists

```
exception beem.exceptions.AssetDoesNotExistException
```

Bases: Exception

The asset does not exist

```
exception beem.exceptions.BatchedCallsNotSupportedException
Bases: Exception
Batch calls do not work

exception beem.exceptions.BlockDoesNotExistException
Bases: Exception
The block does not exist

exception beem.exceptions.BlockWaitTimeExceeded
Bases: Exception
Wait time for new block exceeded

exception beem.exceptions.ContentDoesNotExistException
Bases: Exception
The content does not exist

exception beem.exceptions.InsufficientAuthorityError
Bases: Exception
The transaction requires signature of a higher authority

exception beem.exceptions.InvalidAssetException
Bases: Exception
An invalid asset has been provided

exception beem.exceptions.InvalidMemoKeyException
Bases: Exception
Memo key in message is invalid

exception beem.exceptions.InvalidMessageSignature
Bases: Exception
The message signature does not fit the message

exception beem.exceptions.InvalidWifError
Bases: Exception
The provided private Key has an invalid format

exception beem.exceptions.MissingKeyError
Bases: Exception
A required key couldn't be found in the wallet

exception beem.exceptions.NoWalletException
Bases: Exception
No Wallet could be found, please use beem.wallet.Wallet.create() to create a new wallet

exception beem.exceptions.NoWriteAccess
Bases: Exception
Cannot store to sqlite3 database due to missing write access

exception beem.exceptions.OfflineHasNoRPCEException
Bases: Exception
When in offline mode, we don't have RPC
```

```
exception beem.exceptions.RPCConnectionRequired
Bases: Exception

An RPC connection is required

exception beem.exceptions.VestingBalanceDoesNotExistsException
Bases: Exception

Vesting Balance does not exist

exception beem.exceptions.VoteDoesNotExistsException
Bases: Exception

The vote does not exist

exception beem.exceptions.VotingInvalidOnArchivedPost
Bases: Exception

The transaction requires signature of a higher authority

exception beem.exceptions.WalletExists
Bases: Exception

A wallet has already been created and requires a password to be unlocked by means of beem.wallet.Wallet.unlock().

exception beem.exceptions.WalletLocked
Bases: Exception

Wallet is locked

exception beem.exceptions.WitnessDoesNotExistsException
Bases: Exception

The witness does not exist

exception beem.exceptions.WrongMasterPasswordException
Bases: Exception

The password provided could not properly unlock the wallet

exception beem.exceptions.WrongMemoKey
Bases: Exception

The memo provided is not equal the one on the blockchain
```

beem.hive

```
class beem.hive.Hive(node='',      rpcuser=None,      rpcpassword=None,      debug=False,
                     data_refresh_time_seconds=900, **kwargs)
Bases: beem.blockchaininstance.BlockChainInstance

Connect to the Hive network.
```

Parameters

- **node** (*str*) – Node to connect to (*optional*)
- **rpcuser** (*str*) – RPC user (*optional*)
- **rpcpassword** (*str*) – RPC password (*optional*)
- **nobroadcast** (*bool*) – Do **not** broadcast a transaction! (*optional*)
- **unsigned** (*bool*) – Do **not** sign a transaction! (*optional*)

- **debug** (*bool*) – Enable Debugging (*optional*)
- **keys** (*array, dict, string*) – Predefine the wif keys to shortcut the wallet database (*optional*)
- **wif** (*array, dict, string*) – Predefine the wif keys to shortcut the wallet database (*optional*)
- **offline** (*bool*) – Boolean to prevent connecting to network (defaults to `False`) (*optional*) (default is 30)
- **blocking** (*str*) – Wait for broadcasted transactions to be included in a block and return full transaction (can be “head” or “irreversible”)
- **bundle** (*bool*) – Do not broadcast transactions right away, but allow to bundle operations. It is not possible to send out more than one vote operation and more than one comment operation in a single broadcast (*optional*)
- **appbase** (*bool*) – Use the new appbase rpc protocol on nodes with version 0.19.4 or higher. The settings has no effect on nodes with version of 0.19.3 or lower.
- **num_retries** (*int*) – Set the maximum number of reconnects to the nodes before NumRetriesReached is raised. Disabled for -1. (default is -1)
- **num_retries_call** (*int*) – Repeat num_retries_call times a rpc call on node error (default is 5)
- **timeout** (*int*) – Timeout setting for https nodes (default is 60)
- **use_hs** (*bool*) – When True, a hivesigner object is created. Can be used for broadcast posting op or creating hot_links (default is `False`)
- **hivesigner** (*HiveSigner*) – A HiveSigner object can be set manually, set use_hs to True
- **custom_chains** (*dict*) – custom chain which should be added to the known chains

Three wallet operation modes are possible:

- **Wallet Database:** Here, the beemlibs load the keys from the locally stored wallet SQLite database (see `storage.py`). To use this mode, simply call `Hive()` without the `keys` parameter
- **Providing Keys:** Here, you can provide the keys for your accounts manually. All you need to do is add the wif keys for the accounts you want to use as a simple array using the `keys` parameter to `Steem()`.
- **Force keys:** This mode is for advanced users and requires that you know what you are doing. Here, the `keys` parameter is a dictionary that overwrite the `active`, `owner`, `posting` or `memo` keys for any account. This mode is only used for *foreign* signatures!

If no node is provided, it will connect to default nodes from `beem.NodeList`. Default settings can be changed with:

```
hive = Hive(<host>)
```

where `<host>` starts with `https://`, `ws://` or `wss://`.

The purpose of this class is to simplify interaction with Steem.

The idea is to have a class that allows to do this:

```
>>> from beem import Hive
>>> hive = Hive()
>>> print(hive.get_blockchain_version())
```

This class also deals with edits, votes and reading content.

Example for adding a custom chain:

```
from beem import Hive
stm = Hive(node=["https://mytstnet.com"], custom_chains={"MYTESTNET":
    {'chain_assets': [{asset: 'HBD', id: 0, precision: 3, symbol: 'HBD'},
                      {asset: 'STEEM', id: 1, precision: 3, symbol: 'STEEM'},
                      {'asset': 'VESTS', id: 2, precision: 6, symbol: 'VESTS'}],
     'chain_id': '79276aea5d4877d9a25892eaa01b0adf019d3e5cb12a97478df3298ccdd01674',
     'min_version': '0.0.0',
     'prefix': 'MTN'}
   }
)
```

chain_params

get_hbd_per_rshares (*not_broadcasted_vote_rshares=0, use_stored_data=True*)

Returns the current rshares to HBD ratio

get_hive_per_mvest (*time_stamp=None, use_stored_data=True*)

Returns the MVEST to HIVE ratio

Parameters **time_stamp** (*int*) – (optional) if set, return an estimated HIVE per MVEST ratio for the given time stamp. If unset the current ratio is returned (default). (can also be a datetime object)

get_network (*use_stored_data=True, config=None*)

Identify the network

Parameters **use_stored_data** (*bool*) – if True, stored data will be returned. If stored data are empty or old, refresh_data() is used.

Returns Network parameters

Return type dictionary

hardfork

hbd_symbol

get the current chains symbol for HBD (e.g. “TBD” on testnet)

hbd_to_rshares (*hbd, not_broadcasted_vote=False, use_stored_data=True*)

Obtain the r-shares from HBD

Parameters

- **hbd** (*str, int, amount.Amount*) – HBD
- **not_broadcasted_vote** (*bool*) – not_broadcasted or already broadcasted vote (True = not_broadcasted vote). Only impactful for very high amounts of HBD. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

hbd_to_vote_pct (*hbd*, *post_rshares*=0, *hive_power*=None, *vests*=None, *voting_power*=10000, *not_broadcasted_vote*=True, *use_stored_data*=True)

Obtain the voting percentage for a desired HBD value for a given Hive Power or vesting shares and voting power Give either Hive Power or vests, not both. When the output is greater than 10000 or smaller than -10000, the HBD value is too high.

Returns the required voting percentage (100% = 10000)

Parameters

- **hbd** (*str*, *int*, *amount.Amount*) – desired HBD value
- **hive_power** (*number*) – Hive Power
- **vests** (*number*) – vesting shares
- **not_broadcasted_vote** (*bool*) – not_broadcasted or already broadcasted vote (True = not_broadcasted vote). Only impactful for very high amounts of HBD. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

hive_symbol

get the current chains symbol for HIVE (e.g. “TESTS” on testnet)

hp_to_hbd (*hp*, *post_rshares*=0, *voting_power*=10000, *vote_pct*=10000, *not_broadcasted_vote*=True, *use_stored_data*=True)

Obtain the resulting HBD vote value from Hive power

Parameters

- **hive_power** (*number*) – Hive Power
- **post_rshares** (*int*) – rshares of post which is voted
- **voting_power** (*int*) – voting power (100% = 10000)
- **vote_pct** (*int*) – voting percentage (100% = 10000)
- **not_broadcasted_vote** (*bool*) – not_broadcasted or already broadcasted vote (True = not_broadcasted vote).

Only impactful for very big votes. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

hp_to_rshares (*hive_power*, *post_rshares*=0, *voting_power*=10000, *vote_pct*=10000, *use_stored_data*=True)

Obtain the r-shares from Hive power

Parameters

- **hive_power** (*number*) – Hive Power
- **post_rshares** (*int*) – rshares of post which is voted
- **voting_power** (*int*) – voting power (100% = 10000)
- **vote_pct** (*int*) – voting percentage (100% = 10000)

hp_to_vests (*hp*, *timestamp*=None, *use_stored_data*=True)

Converts HP to vests

Parameters

- **hp** (*float*) – Hive power to convert
- **timestamp** (*datetime*) – (Optional) Can be used to calculate the conversion rate from the past

is_hive**rshares_to_hbd**(rshares, not_broadcasted_vote=False, use_stored_data=True)

Calculates the current HBD value of a vote

rshares_to_vote_pct(rshares, post_rshares=0, hive_power=None, vests=None, voting_power=10000, use_stored_data=True)

Obtain the voting percentage for a desired rshares value for a given Hive Power or vesting shares and voting_power Give either hive_power or vests, not both. When the output is greater than 10000 or less than -10000, the given absolute rshares are too high

Returns the required voting percentage (100% = 10000)

Parameters

- **rshares** (*number*) – desired rshares value
- **hive_power** (*number*) – Hive Power
- **vests** (*number*) – vesting shares
- **voting_power** (*int*) – voting power (100% = 10000)

vests_symbol

get the current chains symbol for VESTS

vests_to_hbd(vests, post_rshares=0, voting_power=10000, vote_pct=10000, not_broadcasted_vote=True, use_stored_data=True)

Obtain the resulting HBD vote value from vests

Parameters

- **vests** (*number*) – vesting shares
- **post_rshares** (*int*) – rshares of post which is voted
- **voting_power** (*int*) – voting power (100% = 10000)
- **vote_pct** (*int*) – voting percentage (100% = 10000)
- **not_broadcasted_vote** (*bool*) – not_broadcasted or already broadcasted vote (True = not_broadcasted vote).

Only impactful for very big votes. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

vests_to_hp(vests, timestamp=None, use_stored_data=True)

Converts vests to HP

Parameters

- **vests/float vests** (*amount.Amount*) – Vests to convert
- **timestamp** (*int*) – (Optional) Can be used to calculate the conversion rate from the past

vests_to_rshares(vests, post_rshares=0, voting_power=10000, vote_pct=10000, subtract_dust_threshold=True, use_stored_data=True)

Obtain the r-shares from vests

Parameters

- **vests** (*number*) – vesting shares
- **post_rshares** (*int*) – rshares of post which is voted
- **voting_power** (*int*) – voting power (100% = 10000)

- **vote_pct** (*int*) – voting percentage (100% = 10000)

beem.hivesigner

```
class beem.hivesigner.HiveSigner(blockchain_instance=None, *args, **kwargs)
Bases: object
```

Parameters scope (*str*) – comma separated string with scopes login,offline,vote,comment,delete_comment,comment_options,custom_json,claim_reward_balance

```
# Run the login_app in examples and login with a account
from beem import Steem
from beem.HiveSigner import HiveSigner
from beem.comment import Comment
hs = HiveSigner(client_id="beem.app")
steem = Steem(HiveSigner=hs)
steem.wallet.unlock("supersecret-passphrase")
post = Comment("author/permlink", blockchain_instance=steem)
post.upvote(voter="test") # replace "test" with your account
```

Examples for creating HiveSigner urls for broadcasting in browser:

```
from beem import Steem
from beem.account import Account
from beem.HiveSigner import HiveSigner
from pprint import pprint
steem = Steem(nobroadcast=True, unsigned=True)
hs = HiveSigner(blockchain_instance=steem)
acc = Account("test", blockchain_instance=steem)
pprint(hs.url_from_tx(acc.transfer("test1", 1, "HIVE", "test")))
```

```
'https://hivesigner.com/sign/transfer?from=test&to=test1&amount=1.000+HIVE&memo=test'
```

```
from beem import Steem
from beem.transactionbuilder import TransactionBuilder
from beembase import operations
from beem.HiveSigner import HiveSigner
from pprint import pprint
stm = Steem(nobroadcast=True, unsigned=True)
hs = HiveSigner(blockchain_instance=stm)
tx = TransactionBuilder(blockchain_instance=stm)
op = operations.Transfer(**{"from": 'test',
                           "to": 'test1',
                           "amount": '1.000 HIVE',
                           "memo": 'test'})
tx.appendOps(op)
pprint(hs.url_from_tx(tx.json()))
```

```
'https://hivesigner.com/sign/transfer?from=test&to=test1&amount=1.000+HIVE&memo=test'
```

broadcast (*operations, username=None*)

Broadcast an operation

Sample operations:

```
[  
    [  
        'vote', {  
            'voter': 'gandalf',  
            'author': 'gtg',  
            'permlink': 'steem-pressure-4-need-for-speed',  
            'weight': 10000  
        }  
    ]  
]
```

create_hot_sign_url(*operation, params, redirect_uri=None*)

Creates a link for broadcasting an operation

Parameters

- **operation** (*str*) – operation name (e.g.: vote)
- **params** (*dict*) – operation dict params
- **redirect_uri** (*str*) – Redirects to this uri, when set

get_access_token(*code*)**get_login_url**(*redirect_uri, **kwargs*)

Returns a login url for receiving token from HiveSigner

headers**me**(*username=None*)

Calls the me function from HiveSigner

```
from beem.HiveSigner import HiveSigner  
hs = HiveSigner()  
hs.steem.wallet.unlock("supersecret-passphrase")  
hs.me(username="test")
```

refresh_access_token(*code, scope*)**revoke_token**(*access_token*)**set_access_token**(*access_token*)

Is needed for *broadcast()* and *me()*

set_username(*username, permission='posting'*)

Set a username for the next *broadcast()* or *me()* operation. The necessary token is fetched from the wallet

update_user_metadata(*metadata*)**url_from_tx**(*tx, redirect_uri=None*)

Creates a link for broadcasting an operation

Parameters

- **tx** (*dict*) – includes the operation, which should be broadcast
- **redirect_uri** (*str*) – Redirects to this uri, when set

beem.imageuploader

```
class beem.imageuploader.ImageUploader(base_url='https://steemitimages.com',
                                         challenge='ImageSigningChallenge',
                                         blockchain_instance=None, **kwargs)
```

Bases: object

```
upload(image, account, image_name=None)
    Uploads an image
```

Parameters

- **image** (*str, bytes*) – path to the image or image in bytes representation which should be uploaded
- **account** (*str*) – Account which is used to upload. A posting key must be provided.
- **image_name** (*str*) – optional

```
from beem import Steem
from beem.imageuploader import ImageUploader
stm = Steem(keys=["5xxx"]) # private posting key
iu = ImageUploader(blockchain_instance=stm)
iu.upload("path/to/image.png", "account_name") # "private posting key belongs_
    ↪ to account_name"
```

beem.instance

```
class beem.instance.SharedInstance
```

Bases: object

Singelton for the Steem Instance

```
config = {}
```

```
instance = None
```

```
beem.instance.clear_cache()
```

Clear Caches

```
beem.instance.set_shared_blockchain_instance(blockchain_instance)
```

This method allows us to override default steem instance for all users of SharedInstance.instance.

Parameters **blockchain_instance** (*Steem*) – Steem instance

```
beem.instance.set_shared_config(config)
```

This allows to set a config that will be used when calling shared_steam_instance and allows to define the configuration without requiring to actually create an instance

```
beem.instance.set_shared_hive_instance(hive_instance)
```

This method allows us to override default steem instance for all users of SharedInstance.instance.

Parameters **hive_instance** (*Hive*) – Hive instance

```
beem.instance.set_shared_steam_instance(steam_instance)
```

This method allows us to override default steem instance for all users of SharedInstance.instance.

Parameters **steam_instance** (*Steem*) – Steem instance

```
beem.instance.shared_blockchain_instance()
```

This method will initialize SharedInstance.instance and return it. The purpose of this method is to have offer single default steem instance that can be reused by multiple classes.

```
from beem.account import Account
from beem.instance import shared_steam_instance

account = Account("test")
# is equivalent with
account = Account("test", blockchain_instance=shared_steam_instance())
```

beem.instance.shared_hive_instance()

This method will initialize SharedInstance.instance and return it. The purpose of this method is to have offer single default steem instance that can be reused by multiple classes.

```
from beem.account import Account
from beem.instance import shared_hive_instance

account = Account("test")
# is equivalent with
account = Account("test", blockchain_instance=shared_hive_instance())
```

beem.instance.shared_steam_instance()

This method will initialize SharedInstance.instance and return it. The purpose of this method is to have offer single default steem instance that can be reused by multiple classes.

```
from beem.account import Account
from beem.instance import shared_steam_instance

account = Account("test")
# is equivalent with
account = Account("test", blockchain_instance=shared_steam_instance())
```

beem.market

class beem.market.Market(*base=None, quote=None, blockchain_instance=None, **kwargs*)

Bases: dict

This class allows to easily access Markets on the blockchain for trading, etc.

Parameters

- **blockchain_instance** (`Steem`) – Steem instance
- **base** (`Asset`) – Base asset
- **quote** (`Asset`) – Quote asset

Returns Blockchain Market**Return type** dictionary with overloaded methods

Instances of this class are dictionaries that come with additional methods (see below) that allow dealing with a market and its corresponding functions.

This class tries to identify **two** assets as provided in the parameters in one of the following forms:

- base and quote are valid assets (according to `beem.asset.Asset`)
- base:quote separated with :
- base/quote separated with /
- base-quote separated with -

Note: Throughout this library, the quote symbol will be presented first (e.g. STEEM:SBD with STEEM being the quote), while the base only refers to a secondary asset for a trade. This means, if you call `beem.market.Market.sell()` or `beem.market.Market.buy()`, you will sell/buy **only quote** and obtain/pay **only base**.

accountopenorders (*account=None, raw_data=False*)

Returns open Orders

Parameters

- **account** (`Account`) – Account name or instance of Account to show orders for in this market
- **raw_data** (`bool`) – (optional) returns raw data if set True, or a list of Order() instances if False (defaults to False)

static btc_usd_ticker (*verbose=False*)

Returns the BTC/USD price from bitfinex, gdax, kraken, okcoin and bitstamp. The mean price is weighted by the exchange volume.

buy (*price, amount, expiration=None, killfill=False, account=None, orderid=None, returnOrderId=False*)

Places a buy order in a given market

Parameters

- **price** (`float`) – price denoted in base/quote
- **amount** (`number`) – Amount of quote to buy
- **expiration** (`number`) – (optional) expiration time of the order in seconds (defaults to 7 days)
- **killfill** (`bool`) – flag that indicates if the order shall be killed if it is not filled (defaults to False)
- **account** (`string`) – Account name that executes that order
- **returnOrderId** (`string`) – If set to “head” or “irreversible” the call will wait for the tx to appear in the head/irreversible block and add the key “orderid” to the tx output

Prices/Rates are denoted in ‘base’, i.e. the SBD_STEEM market is priced in STEEM per SBD.

Example: in the SBD_STEEM market, a price of 300 means a SBD is worth 300 STEEM

Note: All prices returned are in the **reversed** orientation as the market. I.e. in the STEEM/SBD market, prices are SBD per STEEM. That way you can multiply prices with *1.05* to get a +5%.

Warning: Since buy orders are placed as limit-sell orders for the base asset, you may end up obtaining more of the buy asset than you placed the order for. Example:

- You place an order to buy 10 SBD for 100 STEEM/SBD
- This means that you actually place a sell order for 1000 STEEM in order to obtain **at least** 10 SBD
- If an order on the market exists that sells SBD for cheaper, you will end up with more than 10 SBD

cancel(*orderNumbers*, *account=None*, ***kwargs*)

Cancels an order you have placed in a given market. Requires only the “orderNumbers”.

Parameters **orderNumbers**(*int*, *list*) – A single order number or a list of order numbers**get_string**(*separator=':'*)

Return a formated string that identifies the market, e.g. STEEM:SBD

Parameters **separator**(*str*) – The separator of the assets (defaults to :) **static hive_btc_ticker()**

Returns the HIVE/BTC price from bittrex and upbit. The mean price is weighted by the exchange volume.

hive_usd_implied()

Returns the current HIVE/USD market price

market_history(*bucket_seconds=300*, *start_age=3600*, *end_age=0*, *raw_data=False*)

Return the market history (filled orders).

Parameters

- **bucket_seconds**(*int*) – Bucket size in seconds (see *returnMarketHistoryBuckets()*)
- **start_age**(*int*) – Age (in seconds) of the start of the window (default: 1h/3600)
- **end_age**(*int*) – Age (in seconds) of the end of the window (default: now/0)
- **raw_data**(*bool*) – (optional) returns raw data if set True

Example:

```
{  
    'close_sbd': 2493387,  
    'close_steam': 7743431,  
    'high_sbd': 1943872,  
    'high_steam': 5999610,  
    'id': '7.1.5252',  
    'low_sbd': 534928,  
    'low_steam': 1661266,  
    'open': '2016-07-08T11:25:00',  
    'open_sbd': 534928,  
    'open_steam': 1661266,  
    'sbd_volume': 9714435,  
    'seconds': 300,  
    'steam_volume': 30088443  
}
```

market_history_buckets()**orderbook**(*limit=25*, *raw_data=False*)

Returns the order book for SBD/STEEM market.

Parameters **limit**(*int*) – Limit the amount of orders (default: 25)

Sample output (raw_data=False):

```
{  
    'asks': [  
        380.510 STEEM 460.291 SBD @ 1.209669 SBD/STEEM,  
        53.785 STEEM 65.063 SBD @ 1.209687 SBD/STEEM  
    ],  
    'bids': [  
        100.000 STEEM 110.000 SBD @ 1.209669 SBD/STEEM,  
        100.000 STEEM 110.000 SBD @ 1.209687 SBD/STEEM  
    ]  
}
```

(continues on next page)

(continued from previous page)

```

        0.292 STEEM 0.353 SBD @ 1.208904 SBD/STEEM,
        8.498 STEEM 10.262 SBD @ 1.207578 SBD/STEEM
    ],
    'asks_date': [
        datetime.datetime(2018, 4, 30, 21, 7, 24, tzinfo=<UTC>),
        datetime.datetime(2018, 4, 30, 18, 12, 18, tzinfo=<UTC>)
    ],
    'bids_date': [
        datetime.datetime(2018, 4, 30, 21, 1, 21, tzinfo=<UTC>),
        datetime.datetime(2018, 4, 30, 20, 38, 21, tzinfo=<UTC>)
    ]
}

```

Sample output (raw_data=True):

```

{
    'asks': [
        {
            'order_price': {'base': '8.000 STEEM', 'quote': '9.618 SBD
←'},
            'real_price': '1.2022500000000004',
            'steem': 4565,
            'sbd': 5488,
            'created': '2018-04-30T21:12:45'
        }
    ],
    'bids': [
        {
            'order_price': {'base': '10.000 SBD', 'quote': '8.333 STEEM
←'},
            'real_price': '1.20004800192007677',
            'steem': 8333,
            'sbd': 10000,
            'created': '2018-04-30T20:29:33'
        }
    ]
}

```

Note: Each bid is an instance of class:*beem.price.Order* and thus carries the keys `base`, `quote` and `price`. From those you can obtain the actual amounts for sale

recent_trades (*limit=25, raw_data=False*)

Returns the order book for a given market. You may also specify “all” to get the orderbooks of all markets.

Parameters

- **limit** (*int*) – Limit the amount of orders (default: 25)
- **raw_data** (*bool*) – when False, FilledOrder objects will be returned

Sample output (raw_data=False):

```

[
    (2018-04-30 21:00:54+00:00) 0.267 STEEM 0.323 SBD @ 1.209738 SBD/
    ←STEEM,
    (2018-04-30 20:59:30+00:00) 0.131 STEEM 0.159 SBD @ 1.213740 SBD/
    ←STEEM,

```

(continues on next page)

(continued from previous page)

```
(2018-04-30 20:55:45+00:00) 0.093 STEEM 0.113 SBD @ 1.215054 SBD/
↳STEEM,
(2018-04-30 20:55:30+00:00) 26.501 STEEM 32.058 SBD @ 1.209690 SBD/
↳STEEM,
(2018-04-30 20:55:18+00:00) 2.108 STEEM 2.550 SBD @ 1.209677 SBD/
↳STEEM,
]
```

Sample output (raw_data=True):

```
[{'date': '2018-04-30T21:02:45', 'current_pays': '0.235 SBD', 'open_pays': '0.194 STEEM'},
 {'date': '2018-04-30T21:02:03', 'current_pays': '24.494 SBD',
  ↳'open_pays': '20.248 STEEM'},
 {'date': '2018-04-30T20:48:30', 'current_pays': '175.464 STEEM',
  ↳'open_pays': '211.955 SBD'},
 {'date': '2018-04-30T20:48:30', 'current_pays': '0.999 STEEM',
  ↳'open_pays': '1.207 SBD'},
 {'date': '2018-04-30T20:47:54', 'current_pays': '0.273 SBD', 'open_pays': '0.225 STEEM'},
]
```

Note: Each bid is an instance of `beem.price.Order` and thus carries the keys `base`, `quote` and `price`. From those you can obtain the actual amounts for sale

sell (`price`, `amount`, `expiration=None`, `killfill=False`, `account=None`, `orderid=None`, `returnOrderId=False`)
Places a sell order in a given market

Parameters

- **price** (`float`) – price denoted in `base/quote`
- **amount** (`number`) – Amount of `quote` to sell
- **expiration** (`number`) – (optional) expiration time of the order in seconds (defaults to 7 days)
- **killfill** (`bool`) – flag that indicates if the order shall be killed if it is not filled (defaults to False)
- **account** (`string`) – Account name that executes that order
- **returnOrderId** (`string`) – If set to “head” or “irreversible” the call will wait for the tx to appear in the head/irreversible block and add the key “`orderid`” to the tx output

Prices/Rates are denoted in ‘`base`’, i.e. the `SBD_STEEM` market is priced in `STEEM` per `SBD`.

Example: in the `SBD_STEEM` market, a price of 300 means a `SBD` is worth 300 `STEEM`

Note: All prices returned are in the **reversed** orientation as the market. I.e. in the `STEEM/SBD` market, prices are `SBD` per `STEEM`. That way you can multiply prices with `1.05` to get a +5%.

static steem_btc_ticker()

Returns the `STEEM/BTC` price from bittrex, binance, huobi and upbit. The mean price is weighted by the exchange volume.

steem_usd_implied()

Returns the current STEEM/USD market price

ticker (raw_data=False)

Returns the ticker for all markets.

Output Parameters:

- **latest**: Price of the order last filled
- **lowest_ask**: Price of the lowest ask
- **highest_bid**: Price of the highest bid
- **sbd_volume**: Volume of SBD
- **steem_volume**: Volume of STEEM
- **percent_change**: 24h change percentage (in %)

Note: Market is STEEM:SBD and prices are SBD per STEEM!

Sample Output:

```
{
    'highest_bid': 0.30100226633322913,
    'latest': 0.0,
    'lowest_ask': 0.3249636958897082,
    'percent_change': 0.0,
    'sbd_volume': 108329611.0,
    'steem_volume': 355094043.0
}
```

trade_history (start=None, stop=None, intervall=None, limit=25, raw_data=False)

Returns the trade history for the internal market

This function allows to fetch a fixed number of trades at fixed intervall times to reduce the call duration time. E.g. it is possible to receive the trades from the last 7 days, by fetching 100 trades each 6 hours.

When intervall is set to None, all trades are received between start and stop. This can take a while.

Parameters

- **start** (*datetime*) – Start date
- **stop** (*datetime*) – Stop date
- **intervall** (*timedelta*) – Defines the intervall
- **limit** (*int*) – Defines how many trades are fetched at each intervall point
- **raw_data** (*bool*) – when True, the raw data are returned

trades (limit=100, start=None, stop=None, raw_data=False)

Returns your trade history for a given market.

Parameters

- **limit** (*int*) – Limit the amount of orders (default: 100)
- **start** (*datetime*) – start time
- **stop** (*datetime*) – stop time

volume24h (raw_data=False)

Returns the 24-hour volume for all markets, plus totals for primary currencies.

Sample output:

```
{  
    "STEEM": 361666.63617,  
    "SBD": 1087.0  
}
```

beem.memo

```
class beem.memo.Memo (from_account=None, to_account=None, blockchain_instance=None,  
                      **kwargs)
```

Bases: object

Deals with Memos that are attached to a transfer

Parameters

- **from_account** ([Account](#)) – Account that has sent the memo
- **to_account** ([Account](#)) – Account that has received the memo
- **blockchain_instance** ([Steem](#)) – Steem instance

A memo is encrypted with a shared secret derived from a private key of the sender and a public key of the receiver. Due to the underlying mathematics, the same shared secret can be derived by the private key of the receiver and the public key of the sender. The encrypted message is perturbed by a nonce that is part of the transmitted message.

```
from beem.memo import Memo  
m = Memo("steemeu", "wallet.xeroc")  
m.steem.wallet.unlock("secret")  
enc = (m.encrypt("foobar"))  
print(enc)  
>> {'nonce': '17329630356955254641', 'message': '8563e2bb2976e0217806d642901a2855  
˓→'}  
print(m.decrypt(enc))  
>> foobar
```

To decrypt a memo, simply use

```
from beem.memo import Memo  
m = Memo()  
m.steem.wallet.unlock("secret")  
print(m.decrypt(op_data["memo"]))
```

if op_data being the payload of a transfer operation.

Memo Keys

In Steem, memos are AES-256 encrypted with a shared secret between sender and receiver. It is derived from the memo private key of the sender and the memo public key of the receiver.

In order for the receiver to decode the memo, the shared secret has to be derived from the receiver's private key and the senders public key.

The memo public key is part of the account and can be retrieved with the `get_account` call:

```
get_account <accountname>
{
    [...]
    "options": {
        "memo_key": "GPH5TPTziKkLexhVKsQKtSpo4bAv5RnB8oXcG4sMHEwCcTf3r7dqE",
        [...]
    },
    [...]
}
```

while the memo private key can be dumped with `dump_private_keys`

Memo Message

The take the following form:

```
{
    "from": "GPH5mgup8evDqMnT86L7scVebRYDC2fwAWmygPEUL43LjstQegYCC",
    "to": "GPH5Ar4j53kFWuEZQ9XhbAja4YXMPJ2EnUg5QcrdeMFYUNMMNJbe",
    "nonce": "13043867485137706821",
    "message": "d55524c37320920844ca83bb20c8d008"
}
```

The fields `from` and `to` contain the memo public key of sender and receiver. The `nonce` is a random integer that is used for the seed of the AES encryption of the message.

Encrypting a memo

The high level memo class makes use of the beem wallet to obtain keys for the corresponding accounts.

```
from beem.memo import Memo
from beem.account import Account

memoObj = Memo(
    from_account=Account(from_account),
    to_account=Account(to_account)
)
encrypted_memo = memoObj.encrypt(memo)
```

Decoding of a received memo

```
from getpass import getpass
from beem.block import Block
from beem.memo import Memo

# Obtain a transfer from the blockchain
block = Block(23755086)                                # block
transaction = block["transactions"][3]                  # transactions
op = transaction["operations"][0]                        # operation
op_id = op[0]                                           # operation type
op_data = op[1]                                         # operation payload

# Instantiate Memo for decoding
memo = Memo()

# Unlock wallet
memo.unlock_wallet(getpass())

# Decode memo
```

(continues on next page)

(continued from previous page)

```
# Raises exception if required keys not available in the wallet
print(memo.decrypt(op_data["transfer"]))
```

decrypt(*memo*)

Decrypt a memo

Parameters **memo** (*str*) – encrypted memo message**Returns** encrypted memo**Return type** str**encrypt**(*memo*, *bts_encrypt=False*)

Encrypt a memo

Parameters **memo** (*str*) – clear text memo message**Returns** encrypted memo**Return type** str**unlock_wallet**(*args, **kwargs)

Unlock the library internal wallet

beem.message**class** beem.message.**Message**(*message*, *blockchain_instance=None*, ***kwargs*)

Bases: object

sign(*account=None*, ***kwargs*)

Sign a message with an account's memo key

Parameters **account** (*str*) – (optional) the account that owns the bet (defaults to default_account)**Returns** the signed message encapsulated in a known format**verify**(***kwargs*)

Verify a message with an account's memo key

Parameters **account** (*str*) – (optional) the account that owns the bet (defaults to default_account)**Returns** True if the message is verified successfully**Raises** *InvalidMessageSignature* – if the signature is not ok**beem.nodelist****class** beem.nodelist.**NodeList**

Bases: list

Returns HIVE/STEEM nodes as list

```
from beem.nodelist import NodeList
n = NodeList()
nodes_urls = n.get_nodes()
```

get_hive_nodes(*testnet=False*, *not_working=False*, *wss=True*, *https=True*)

Returns hive only nodes as list

Parameters

- **testnet** (*bool*) – when True, testnet nodes are included
- **not_working** (*bool*) – When True, all nodes including not working ones will be returned

get_nodes (*hive=False*, *exclude_limited=False*, *dev=False*, *testnet=False*, *testnetdev=False*, *wss=True*, *https=True*, *not_working=False*, *normal=True*, *appbase=True*)

Returns nodes as list

Parameters

- **hive** (*bool*) – When True, only HIVE nodes will be returned
- **exclude_limited** (*bool*) – When True, limited nodes are excluded
- **dev** (*bool*) – when True, dev nodes with version 0.19.11 are included
- **testnet** (*bool*) – when True, testnet nodes are included
- **testnetdev** (*bool*) – When True, testnet-dev nodes are included
- **not_working** (*bool*) – When True, all nodes including not working ones will be returned
- **normal** (*bool*) – deprecated
- **appbase** (*bool*) – deprecated

get_steam_nodes (*testnet=False*, *not_working=False*, *wss=True*, *https=True*)

Returns steam only nodes as list

Parameters

- **testnet** (*bool*) – when True, testnet nodes are included
- **not_working** (*bool*) – When True, all nodes including not working ones will be returned

get_testnet (*testnet=True*, *testnetdev=False*)

Returns testnet nodes

update_nodes (*weights=None*, *blockchain_instance=None*, ***kwargs*)

Reads metadata from fullnodeupdate and recalculates the nodes score

Parameters weight (*list*, *dict*) – can be used to weight the different benchmarks

```
from beem.nodelist import NodeList
nl = NodeList()
weights = [0, 0.1, 0.2, 1]
nl.update_nodes(weights)
weights = {'block': 0.1, 'history': 0.1, 'apicall': 1, 'config': 1}
nl.update_nodes(weights)
```

beem.notify

class beem.notify.**Notify** (*on_block=None*, *only_block_id=False*, *blockchain_instance=None*, *keep_alive=25*, ***kwargs*)

Bases: events.events.Events

Notifications on Blockchain events.

This module allows you to be notified of events taking place on the blockchain.

Parameters

- **on_block** (*fn*) – Callback that will be called for each block received
- **blockchain_instance** ([Steem](#)) – Steem instance

Example

```
from pprint import pprint
from beem.notify import Notify

notify = Notify(
    on_block=print,
)
notify.listen()
```

`close()`

Cleanly close the Notify instance

`listen()`

This call initiates the listening/notification process. It behaves similar to `run_forever()`.

`process_block(message)`

`reset_subscriptions(accounts=[])`

Change the subscriptions of a running Notify instance

[beem.price](#)

class `beem.price.FilledOrder(order, blockchain_instance=None, **kwargs)`
Bases: `beem.price.Price`

This class inherits `beem.price.Price` but has the `base` and `quote` Amounts not only be used to represent the price (as a ratio of base and quote) but instead has those amounts represent the amounts of an actually filled order!

Parameters `blockchain_instance` ([Steem](#)) – Steem instance

Note: Instances of this class come with an additional `date` key that shows when the order has been filled!

`json()`

class `beem.price.Order(base, quote=None, blockchain_instance=None, **kwargs)`
Bases: `beem.price.Price`

This class inherits `beem.price.Price` but has the `base` and `quote` Amounts not only be used to represent the price (as a ratio of base and quote) but instead has those amounts represent the amounts of an actual order!

Parameters `blockchain_instance` ([Steem](#)) – Steem instance

Note: If an order is marked as deleted, it will carry the ‘deleted’ key which is set to `True` and all other data be `None`.

class `beem.price.Price(price=None, base=None, quote=None, base_asset=None, blockchain_instance=None, **kwargs)`
Bases: `dict`

This class deals with all sorts of prices of any pair of assets to simplify dealing with the tuple:

(quote, base)

each being an instance of `beem.amount.Amount`. The amount themselves define the price.

Note: The price (floating) is derived as base/quote

Parameters

- **args** (*list*) – Allows to deal with different representations of a price
- **base** (`Asset`) – Base asset
- **quote** (`Asset`) – Quote asset
- **blockchain_instance** (`Steem`) – Steem instance

Returns All data required to represent a price

Return type dictionary

Way to obtain a proper instance:

- args is a str with a price and two assets
- args can be a floating number and base and quote being instances of `beem.asset.Asset`
- args can be a floating number and base and quote being instances of str
- args can be dict with keys price, base, and quote (*graphene balances*)
- args can be dict with keys base and quote
- args can be dict with key receives (filled orders)
- args being a list of [quote, base] both being instances of `beem.amount.Amount`
- args being a list of [quote, base] both being instances of str (amount symbol)
- base and quote being instances of `beem.asset.Amount`

This allows instantiations like:

- `Price("0.315 SBD/STEEM")`
- `Price(0.315, base="SBD", quote="STEEM")`
- `Price(0.315, base=Asset("SBD"), quote=Asset("STEEM"))`
- `Price({"base": {"amount": 1, "asset_id": "SBD"}, "quote": {"amount": 10, "asset_id": "SBD"}})`
- `Price(quote="10 STEEM", base="1 SBD")`
- `Price("10 STEEM", "1 SBD")`
- `Price(Amount("10 STEEM"), Amount("1 SBD"))`
- `Price(1.0, "SBD/STEEM")`

Instances of this class can be used in regular mathematical expressions (+-*/%) such as:

```
>>> from beem.price import Price
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> Price("0.3314 SBD/STEEM", blockchain_instance=stm) * 2
0.662804 SBD/STEEM
>>> Price(0.3314, "SBD", "STEEM", blockchain_instance=stm)
0.331402 SBD/STEEM
```

as_base(*base*)

Returns the price instance so that the base asset is base.

Note: This makes a copy of the object!

```
>>> from beem.price import Price
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> Price("0.3314 SBD/STEEM", blockchain_instance=stm).as_base("STEEM")
3.017483 STEEM/SBD
```

as_quote(*quote*)

Returns the price instance so that the quote asset is quote.

Note: This makes a copy of the object!

```
>>> from beem.price import Price
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> Price("0.3314 SBD/STEEM", blockchain_instance=stm).as_quote("SBD")
3.017483 STEEM/SBD
```

copy() → a shallow copy of D

invert()

Invert the price (e.g. go from SBD/STEEM into STEEM/SBD)

```
>>> from beem.price import Price
>>> from beem import Steem
>>> stm = Steem("https://api.steemit.com")
>>> Price("0.3314 SBD/STEEM", blockchain_instance=stm).invert()
3.017483 STEEM/SBD
```

json()

market

Open the corresponding market

Returns Instance of `beem.market.Market` for the corresponding pair of assets.

symbols()

`beem.price.check_asset`(*other, self, stm*)

beem.rc

```
class beem.rc.RC (blockchain_instance=None, **kwargs)
    Bases: object

    account_create_dict (account_create_dict)
        Calc RC costs for account create

    account_update_dict (account_update_dict)
        Calc RC costs for account update

    claim_account (tx_size=300)
        Claim account

    comment (tx_size=1000, permink_length=10, parent_permlink_length=10)
        Calc RC for a comment

    comment_dict (comment_dict)
        Calc RC costs for a comment dict object

    Example for calculating RC costs
```

```
from beem.rc import RC
comment_dict = {
    "permlink": "test", "author": "holger80",
    "body": "test", "parent_permlink": "",
    "parent_author": "", "title": "test",
    "json_metadata": {"foo": "bar"}
}

rc = RC()
print(rc.comment_from_dict(comment_dict))
```

```
create_claimed_account_dict (create_claimed_account_dict)
    Calc RC costs for claimed account create

custom_json (tx_size=444, follow_id=False)

custom_json_dict (custom_json_dict)
    Calc RC costs for a custom_json

    Example for calculating RC costs
```

```
from beem.rc import RC
from collections import OrderedDict
custom_json_dict = {
    "json": [
        "reblog", OrderedDict([("account", "xeroc"), (
            "author", "chainsquad"),
            ("permlink", "streemian-
com-to-open-its-doors-and-offer-a-20-discount")
        ])
    ],
    "required_auths": [],
    "required_posting_auths": ["xeroc"],
    "id": "follow"
}

rc = RC()
print(rc.comment(custom_json_dict))
```

```
get_authority_byte_count(auth)
get_resource_count(tx_size,           execution_time_count,           state_bytes_count=0,
                   new_account_op_count=0, market_op_count=0)
Creates the resource_count dictionary based on tx_size, state_bytes_count, new_account_op_count and
market_op_count
```

```
get_tx_size(op)
Returns the tx size of an operation
```

```
transfer(tx_size=290, market_op_count=1)
Calc RC of a transfer
```

```
transfer_dict(transfer_dict)
Calc RC costs for a transfer dict object
```

Example for calculating RC costs

```
from beem.rc import RC
from beem.amount import Amount
transfer_dict = {
    "from": "foo", "to": "baar",
    "amount": Amount("111.110 STEEM"),
    "memo": "Fooo"
}

rc = RC()
print(rc.comment(transfer_dict))
```

```
vote(tx_size=210)
Calc RC for a vote
```

```
vote_dict(vote_dict)
Calc RC costs for a vote
```

Example for calculating RC costs

```
from beem.rc import RC
vote_dict = {
    "voter": "foobara", "author": "foobarc",
    "permlink": "foobard", "weight": 1000
}

rc = RC()
print(rc.comment(vote_dict))
```

beem.snapshot

```
class beem.snapshot.AccountSnapshot(account,                               account_history=[],
                                         blockchain_instance=None, **kwargs)
```

Bases: list

This class allows to easily access Account history

Parameters

- **account_name** (*str*) – Name of the account
- **blockchain_instance** (*Steem*) – Steem instance

build (*only_ops*=[], *exclude_ops*=[], *enable_rewards*=*False*, *enable_out_votes*=*False*, *enable_in_votes*=*False*)
Builds the account history based on all account operations

Parameters

- **only_ops** (*array*) – Limit generator by these operations (*optional*)
- **exclude_ops** (*array*) – Exclude these operations from generator (*optional*)

build_curation_arrays (*end_date*=*None*, *sum_days*=7)
Build curation arrays

build_rep_arrays ()
Build reputation arrays

build_sp_arrays ()
Builds the own_sp and eff_sp array

build_vp_arrays ()
Build vote power arrays

get_account_history (*start*=*None*, *stop*=*None*, *use_block_num*=*True*)
Uses account history to fetch all related ops

Parameters

- **start** (*int, datetime*) – start number/date of transactions to return (*optional*)
- **stop** (*int, datetime*) – stop number/date of transactions to return (*optional*)
- **use_block_num** (*bool*) – if true, start and stop are block numbers, otherwise virtual OP count numbers.

get_data (*timestamp*=*None*, *index*=0)
Returns snapshot for given timestamp

get_ops (*start*=*None*, *stop*=*None*, *use_block_num*=*True*, *only_ops*=[], *exclude_ops*=[])
Returns ops in the given range

parse_op (*op*, *only_ops*=[], *enable_rewards*=*False*, *enable_out_votes*=*False*, *enable_in_votes*=*False*)
Parse account history operation

reset ()
Resets the arrays not the stored account history

search (*search_str*, *start*=*None*, *stop*=*None*, *use_block_num*=*True*)
Returns ops in the given range

update (*timestamp*, *own*, *delegated_in*=*None*, *delegated_out*=*None*, *steem*=0, *sbd*=0)
Updates the internal state arrays

Parameters

- **timestamp** (*datetime*) – datetime of the update
- **own** (*amount.Amount*, *float*) – vests
- **delegated_in** (*dict*) – Incoming delegation
- **delegated_out** (*dict*) – Outgoing delegation
- **steem** (*amount.Amount*, *float*) – steem
- **sbd** (*amount.Amount*, *float*) – sbd

update_in_vote (*timestamp*, *weight*, *op*)

```
update_out_vote (timestamp, weight)
update_rewards (timestamp, curation_reward, author_vests, author_steam, author_sbd)
```

beem.steem

```
class beem.steem.Steem(node='',          rpcuser=None,          rpcpassword=None,          debug=False,
                      data_refresh_time_seconds=900, **kwargs)
Bases: beem.blockchaininstance.BlockChainInstance
```

Connect to the Steem network.

Parameters

- **node** (*str*) – Node to connect to (*optional*)
- **rpcuser** (*str*) – RPC user (*optional*)
- **rpcpassword** (*str*) – RPC password (*optional*)
- **nobroadcast** (*bool*) – Do **not** broadcast a transaction! (*optional*)
- **unsigned** (*bool*) – Do **not** sign a transaction! (*optional*)
- **debug** (*bool*) – Enable Debugging (*optional*)
- **keys** (*array, dict, string*) – Predefine the wif keys to shortcut the wallet database (*optional*)
- **wif** (*array, dict, string*) – Predefine the wif keys to shortcut the wallet database (*optional*)
- **offline** (*bool*) – Boolean to prevent connecting to network (defaults to `False`) (*optional*)
- **expiration** (*int*) – Delay in seconds until transactions are supposed to expire (*optional*) (default is 30)
- **blocking** (*str*) – Wait for broadcasted transactions to be included in a block and return full transaction (can be “head” or “irreversible”)
- **bundle** (*bool*) – Do not broadcast transactions right away, but allow to bundle operations. It is not possible to send out more than one vote operation and more than one comment operation in a single broadcast (*optional*)
- **appbase** (*bool*) – Use the new appbase rpc protocol on nodes with version 0.19.4 or higher. The settings has no effect on nodes with version of 0.19.3 or lower.
- **num_retries** (*int*) – Set the maximum number of reconnects to the nodes before NumRetriesReached is raised. Disabled for -1. (default is -1)
- **num_retries_call** (*int*) – Repeat num_retries_call times a rpc call on node error (default is 5)
- **timeout** (*int*) – Timeout setting for https nodes (default is 60)
- **use_sc2** (*bool*) – When True, a steemconnect object is created. Can be used for broadcast posting op or creating hot_links (default is `False`)
- **steemconnect** (*SteemConnect*) – A SteemConnect object can be set manually, set use_sc2 to True
- **custom_chains** (*dict*) – custom chain which should be added to the known chains

Three wallet operation modes are possible:

- **Wallet Database:** Here, the steemlibs load the keys from the locally stored wallet SQLite database (see `storage.py`). To use this mode, simply call `Steem()` without the `keys` parameter
- **Providing Keys:** Here, you can provide the keys for your accounts manually. All you need to do is add the wif keys for the accounts you want to use as a simple array using the `keys` parameter to `Steem()`.
- **Force keys:** This mode is for advanced users and requires that you know what you are doing. Here, the `keys` parameter is a dictionary that overwrite the `active`, `owner`, `posting` or `memo` keys for any account. This mode is only used for *foreign* signatures!

If no node is provided, it will connect to default nodes of `http://geo.steem.pl`. Default settings can be changed with:

```
steem = Steem(<host>)
```

where `<host>` starts with `https://`, `ws://` or `wss://`.

The purpose of this class is to simplify interaction with Steem.

The idea is to have a class that allows to do this:

```
>>> from beem import Steem
>>> steem = Steem()
>>> print(steem.get_blockchain_version())
```

This class also deals with edits, votes and reading content.

Example for adding a custom chain:

```
from beem import Steem
stm = Steem(node=["https://mytstnet.com"], custom_chains={"MYTESTNET": {
    'chain_assets': [{ 'asset': 'SBD', 'id': 0, 'precision': 3, 'symbol': 'SBD' },
                     { 'asset': 'STEEM', 'id': 1, 'precision': 3, 'symbol': 'STEEM' },
                     { 'asset': 'VESTS', 'id': 2, 'precision': 6, 'symbol': 'VESTS' }],
    'chain_id': '79276aea5d4877d9a25892eaa01b0adf019d3e5cb12a97478df3298ccdd01674',
    'min_version': '0.0.0',
    'prefix': 'MTN'
}}
```

chain_params

get_network (`use_stored_data=True, config=None`)

Identify the network

Parameters `use_stored_data` (`bool`) – if True, stored data will be returned. If stored data are empty or old, `refresh_data()` is used.

Returns Network parameters

Return type dictionary

get_sbd_per_rshares (`not_broadcasted_vote_rshares=0, use_stored_data=True`)

Returns the current rshares to SBD ratio

get_steam_per_mvest (`time_stamp=None, use_stored_data=True`)

Returns the MVEST to STEEM ratio

Parameters `time_stamp (int)` – (optional) if set, return an estimated STEEM per MVEST ratio for the given time stamp. If unset the current ratio is returned (default). (can also be a datetime object)

hardfork

is_steeem

rshares_to_sbd (`rshares, not_broadcasted_vote=False, use_stored_data=True`)

Calculates the current SBD value of a vote

rshares_to_vote_pct (`rshares, post_rshares=0, steem_power=None, vests=None, voting_power=10000, use_stored_data=True`)

Obtain the voting percentage for a desired rshares value for a given Steem Power or vesting shares and voting_power Give either steem_power or vests, not both. When the output is greater than 10000 or less than -10000, the given absolute rshares are too high

Returns the required voting percentage (100% = 10000)

Parameters

- `rshares (number)` – desired rshares value
- `steem_power (number)` – Steem Power
- `vests (number)` – vesting shares
- `voting_power (int)` – voting power (100% = 10000)

sbd_symbol

get the current chains symbol for SBD (e.g. “TBD” on testnet)

sbd_to_rshares (`sbd, not_broadcasted_vote=False, use_stored_data=True`)

Obtain the r-shares from SBD

Parameters

- `sbd (str, int, amount.Amount)` – SBD
- `not_broadcasted_vote (bool)` – not_broadcasted or already broadcasted vote (True = not_broadcasted vote). Only impactful for very high amounts of SBD. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

sbd_to_vote_pct (`sbd, post_rshares=0, steem_power=None, vests=None, voting_power=10000, not_broadcasted_vote=True, use_stored_data=True`)

Obtain the voting percentage for a desired SBD value for a given Steem Power or vesting shares and voting power Give either Steem Power or vests, not both. When the output is greater than 10000 or smaller than -10000, the SBD value is too high.

Returns the required voting percentage (100% = 10000)

Parameters

- `sbd (str, int, amount.Amount)` – desired SBD value
- `steem_power (number)` – Steem Power
- `vests (number)` – vesting shares
- `not_broadcasted_vote (bool)` – not_broadcasted or already broadcasted vote (True = not_broadcasted vote). Only impactful for very high amounts of SBD. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

sp_to_rshares (*steem_power*, *post_rshares=0*, *voting_power=10000*, *vote_pct=10000*,
use_stored_data=True)
Obtain the r-shares from Steem power

Parameters

- **steem_power** (*number*) – Steem Power
 - **post_rshares** (*int*) – rshares of post which is voted
 - **voting_power** (*int*) – voting power (100% = 10000)
 - **vote_pct** (*int*) – voting percentage (100% = 10000)

sp_to_sbd(*sp*, *post_rshares*=0, *voting_power*=10000, *vote_pct*=10000, *not_broadcasted_vote*=True, *use_stored_data*=True)

Obtain the resulting SBD vote value from Steem power

Parameters

- **steem_power** (*number*) – Steem Power
 - **post_rshares** (*int*) – rshares of post which is voted
 - **voting_power** (*int*) – voting power (100% = 10000)
 - **vote_pct** (*int*) – voting percentage (100% = 10000)
 - **not_broadcasted_vote** (*bool*) – not_broadcasted or already broadcasted vote (True = not_broadcasted vote).

Only impactful for very big votes. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

sp_to_vests (*sp*, *timestamp=None*, *use_stored_data=True*)

Converts SP to vests

Parameters

- **sp** (*float*) – Steem power to convert
 - **timestamp** (*datetime*) – (Optional) Can be used to calculate the conversion rate from the past

steem_symbol

get the current chains symbol for STEEM (e.g. "TESTS" on testnet)

vests_symbol

get the current chains symbol for VESTS

vests_to_rshares(*vests*, *post_rshares*=0, *voting_power*=10000, *vote_pct*=10000, *subtract_dust_threshold*=True, *use_stored_data*=True)

Obtain the r-shares from vests

Parameters

- **vests** (*number*) – vesting shares
 - **post_rshares** (*int*) – rshares of post which is voted
 - **voting_power** (*int*) – voting power (100% = 10000)
 - **vote_pct** (*int*) – voting percentage (100% = 10000)

vests_to_sbd(vests, post_rshares=0, voting_power=10000, vote_pct=10000,
not广播投票=True, 使用存储数据=True)

Obtain the resulting SBD vote value from vests

Parameters

- **vests** (*number*) – vesting shares
- **post_rshares** (*int*) – rshares of post which is voted
- **voting_power** (*int*) – voting power (100% = 10000)
- **vote_pct** (*int*) – voting percentage (100% = 10000)
- **not_broadcasted_vote** (*bool*) – not_broadcasted or already broadcasted vote (True = not_broadcasted vote).

Only impactful for very big votes. Slight modification to the value calculation, as the not_broadcasted vote rshares decreases the reward pool.

vests_to_sp (*vests*, *timestamp=None*, *use_stored_data=True*)

Converts vests to SP

Parameters

- **vests/float vests** (*amount.Amount*) – Vests to convert
- **timestamp** (*int*) – (Optional) Can be used to calculate the conversion rate from the past

beem.steemconnect

class beem.steemconnect.**SteemConnect** (*blockchain_instance=None*, **args*, ***kwargs*)

Bases: object

Parameters scope (*str*) – comma separated string with scopes login,offline,vote,comment,delete_comment,comment_options,custom_json,claim_reward_balance

```
# Run the login_app in examples and login with a account
from beem import Steem
from beem.steemconnect import SteemConnect
from beem.comment import Comment
sc2 = SteemConnect(client_id="beem.app")
steem = Steem(steemconnect=sc2)
steem.wallet.unlock("supersecret-passphrase")
post = Comment("author/permlink", blockchain_instance=steem)
post.upvote(voter="test") # replace "test" with your account
```

Examples for creating steemconnect v2 urls for broadcasting in browser:

```
from beem import Steem
from beem.account import Account
from beem.steemconnect import SteemConnect
from pprint import pprint
steem = Steem(nobroadcast=True, unsigned=True)
sc2 = SteemConnect(blockchain_instance=steem)
acc = Account("test", blockchain_instance=steem)
pprint(sc2.url_from_tx(acc.transfer("test1", 1, "STEEM", "test")))
```

```
'https://steemconnect.com/sign/transfer?from=test&to=test1&amount=1.000+STEEM&
↪memo=test'
```

```

from beem import Steem
from beem.transactionbuilder import TransactionBuilder
from beembase import operations
from beem.steemconnect import SteemConnect
from pprint import pprint
stm = Steem(nobroadcast=True, unsigned=True)
sc2 = SteemConnect(blockchain_instance=stm)
tx = TransactionBuilder(blockchain_instance=stm)
op = operations.Transfer(**{"from": 'test',
                           "to": 'test1',
                           "amount": '1.000 STEEM',
                           "memo": 'test'})
tx.appendOps(op)
pprint(sc2.url_from_tx(tx.json()))

```

```
'https://steemconnect.com/sign/transfer?from=test&to=test1&amount=1.000+STEEM&
↪memo=test'
```

broadcast (*operations, username=None*)

Broadcast an operation

Sample operations:

```
[
  [
    'vote', {
      'voter': 'gandalf',
      'author': 'gtg',
      'permlink': 'steem-pressure-4-need-for-speed',
      'weight': 10000
    }
  ]
]
```

create_hot_sign_url (*operation, params, redirect_uri=None*)

Creates a link for broadcasting an operation

Parameters

- **operation** (*str*) – operation name (e.g.: vote)
- **params** (*dict*) – operation dict params
- **redirect_uri** (*str*) – Redirects to this uri, when set

get_access_token (*code*)

get_login_url (*redirect_uri, **kwargs*)

Returns a login url for receiving token from steemconnect

headers

me (*username=None*)

Calls the me function from steemconnect

```

from beem.steemconnect import SteemConnect
sc2 = SteemConnect()
sc2.steem.wallet.unlock("supersecret-passphrase")
sc2.me(username="test")

```

refresh_access_token (*code, scope*)

```
revoke_token (access_token)
set_access_token (access_token)
    Is needed for broadcast () and me ()

set_username (username, permission='posting')
    Set a username for the next broadcast () or me () operation. The necessary token is fetched from the wallet

update_user_metadata (metadata)

url_from_tx (tx, redirect_uri=None)
    Creates a link for broadcasting an operation
```

Parameters

- **tx** (*dict*) – includes the operation, which should be broadcast
- **redirect_uri** (*str*) – Redirects to this uri, when set

beem.storage

```
class beem.storage.Configuration
```

Bases: *beem.storage.DataDir*

This is the configuration storage that stores key/value pairs in the *config* table of the SQLite3 database.

```
blockchain = 'hive'
```

```
checkBackup ()
```

Backup the SQL database every 7 days

```
config_defaults = {'client_id': '', 'default_chain': 'hive', 'default_path': "48'/"}
```

```
create_table ()
```

Create the new table in the SQLite database

```
delete (key)
```

Delete a key from the configuration store

```
exists_table ()
```

Check if the database table exists

```
get (key, default=None)
```

Return the key if exists or a default value

```
items ()
```

```
nodelist = [{'url': 'https://api.steemit.com', 'version': '0.20.2', 'type': 'appbase'}]
    Default configuration
```

```
nodes = ['https://anyx.io', 'http://anyx.io', 'https://api.hivekings.com', 'https://ap...
```

```
class beem.storage.DataDir
```

Bases: *object*

This class ensures that the user's data is stored in its OS preotected user directory:

OSX:

- *~/Library/Application Support/<AppName>*

Windows:

- *C:Documents and Settings<User>Application DataLocal Settings<AppAuthor><AppName>*

- *C:Documents and Settings<User>Application Data<AppAuthor><AppName>*

Linux:

- *~/.local/share/<AppName>*

Furthermore, it offers an interface to generated backups in the *backups/* directory every now and then.

```
appauthor = 'beem'
appname = 'beem'
clean_data(backupdir='backups')
    Delete files older than 70 days
data_dir = '/home/docs/.local/share/beem'
mkdir_p()
    Ensure that the directory in which the data is stored exists
recover_with_latest_backup(backupdir='backups')
    Replace database with latest backup
refreshBackup()
    Make a new backup
sqlDataBaseFile = '/home/docs/.local/share/beem/beem.sqlite'
sqlite3_backup(backupdir)
    Create timestamped database copy
sqlite3_copy(src, dst)
    Copy sql file from src to dst
storageDatabase = 'beem.sqlite'

class beem.storage.Key
    Bases: beem.storage.DataDir
```

This is the key storage that stores the public key and the (possibly encrypted) private key in the *keys* table in the SQLite3 database.

```
add(wif, pub)
    Add a new public/private key pair (correspondence has to be checked elsewhere!)
```

Parameters

- **pub** (*str*) – Public key
- **wif** (*str*) – Private key

```
create_table()
    Create the new table in the SQLite database
```

```
delete(pub)
    Delete the key identified as pub
```

Parameters **pub** (*str*) – Public key

```
exists_table()
    Check if the database table exists
```

```
getPrivateKeyForPublicKey(pub)
    Returns the (possibly encrypted) private key that corresponds to a public key
```

Parameters **pub** (*str*) – Public key

The encryption scheme is BIP38

getPublicKeys (*prefix='STM'*)

Returns the public keys stored in the database

updateWif (*pub, wif*)

Change the wif to a pubkey

Parameters

- **pub** (*str*) – Public key
- **wif** (*str*) – Private key

wipe (*sure=False*)

Purge the entire wallet. No keys will survive this!

class beem.storage.MasterPassword (*password*)

Bases: object

The keys are encrypted with a Masterpassword that is stored in the configurationStore. It has a checksum to verify correctness of the password

changePassword (*newpassword*)

Change the password

config_key = 'encrypted_master_password'

This key identifies the encrypted master password stored in the confirmation

decryptEncryptedMaster()

Decrypt the encrypted masterpassword

decrypted_master = ''

deriveChecksum (*s*)

Derive the checksum

getEncryptedMaster()

Obtain the encrypted masterkey

newMaster()

Generate a new random masterpassword

password = ''

saveEncrytpedMaster()

Store the encrypted master password in the configuration store

static wipe (*sure=False*)

Remove all keys from configStorage

class beem.storage.Token

Bases: beem.storage.DataDir

This is the token storage that stores the public username and the (possibly encrypted) token in the *token* table in the SQLite3 database.

add (*name, token*)

Add a new public/private token pair (correspondence has to be checked elsewhere!)

Parameters

- **name** (*str*) – Public name
- **token** (*str*) – Private token

```
create_table()
    Create the new table in the SQLite database

delete(name)
    Delete the key identified as name

    Parameters name (str) – Public name

exists_table()
    Check if the database table exists

getPublicNames()
    Returns the public names stored in the database

getTokenForPublicName(name)
    Returns the (possibly encrypted) private token that corresponds to a public name

    Parameters pub (str) – Public name

    The encryption scheme is BIP38

updateToken(name, token)
    Change the token to a name

    Parameters
        • name (str) – Public name
        • token (str) – Private token

wipe(sure=False)
    Purge the entire wallet. No keys will survive this!

beem.storage.get_default_config_storage()
beem.storage.get_default_key_storage()
beem.storage.get_default_token_storage()
```

beem.transactionbuilder

```
class beem.transactionbuilder.TransactionBuilder (tx={}, use_condenser_api=True,
                                                 blockchain_instance=None,
                                                 **kwargs)
```

Bases: dict

This class simplifies the creation of transactions by adding operations and signers. To build your own transactions and sign them

Parameters

- **tx** (*dict*) – transaction (Optional). If not set, the new transaction is created.
- **expiration** (*int*) – Delay in seconds until transactions are supposed to expire (*optional*) (default is 30)
- **steem_instance** (*Steem*) – If not set, `shared_blockchain_instance()` is used

```
from beem.transactionbuilder import TransactionBuilder
from beembase.operations import Transfer
from beem import Steem
wif = "5KQwrPbwL6PhXujxW37FSSQZ1JiwsST4cqQzDeyXtP79zkvFD3"
stm = Steem(nobroadcast=True, keys={'active': wif})
```

(continues on next page)

(continued from previous page)

```
tx = TransactionBuilder(steem_instance=stm)
transfer = {"from": "test", "to": "test1", "amount": "1 STEEM", "memo": ""}
tx.appendOps(Transfer(transfer))
tx.appendSigner("test", "active") # or tx.appendWif(wif)
signed_tx = tx.sign()
broadcast_tx = tx.broadcast()
```

addSigningInformation (*account, permission, reconstruct_tx=False*)

This is a private method that adds side information to a unsigned/partial transaction in order to simplify later signing (e.g. for multisig or coldstorage)

Not needed when “appendWif” was already or is going to be used

FIXME: Does not work with owner keys!

Parameters **reconstruct_tx** (*bool*) – when set to False and tx is already contructed, it will not reconstructed and already added signatures remain

appendMissingSignatures ()

Store which accounts/keys are supposed to sign the transaction

This method is used for an offline-signer!

appendOps (*ops, append_to=None*)

Append op(s) to the transaction builder

Parameters **ops** (*list*) – One or a list of operations

appendSigner (*account, permission*)

Try to obtain the wif key from the wallet by telling which account and permission is supposed to sign the transaction It is possible to add more than one signer.

appendWif (*wif*)

Add a wif that should be used for signing of the transaction.

Parameters **wif** (*string*) – One wif key to use for signing a transaction.

broadcast (*max_block_age=-1*)

Broadcast a transaction to the steem network Returns the signed transaction and clears itself after broadcast

Clears itself when broadcast was not successfully.

Parameters **max_block_age** (*int*) – parameter only used for appbase ready nodes

clear ()

Clear the transaction builder and start from scratch

clearWifs ()

Clear all stored wifs

constructTx (*ref_block_num=None, ref_block_prefix=None*)

Construct the actual transaction and store it in the class's dict store

get_parent ()

TransactionBuilders don't have parents, they are their own parent

get_potential_signatures ()

Returns public key from signature

get_required_signatures (*available_keys=[]*)

Returns public key from signature

```

get_transaction_hex()
    Returns a hex value of the transaction

is_empty()
    Check if ops is empty

json (with_prefix=False)
    Show the transaction as plain json

list_operations()
    List all ops

searchPath (account, perm)

setPath (path)

set_expiration (p)
    Set expiration date

sign (reconstruct_tx=True)
    Sign a provided transaction with the provided key(s) One or many wif keys to use for signing a transaction.
    The wif keys can be provided by “appendWif” or the signer can be defined “appendSigner”. The wif keys
    from all signer that are defined by “appendSigner” will be loaded from the wallet.

        Parameters reconstruct_tx (bool) – when set to False and tx is already contracted, it
            will not reconstructed and already added signatures remain

verify_authority()
    Verify the authority of the signed transaction

```

beem.utils

```

beem.utils.addTzInfo (t, timezone='UTC')
    Returns a datetime object with tzinfo added

beem.utils.assets_from_string (text)
    Correctly split a string containing an asset pair.

    Splits the string into two assets with the separator being one of the following: :, /, or -.

beem.utils.construct_authorperm (*args)
    Create a post identifier from comment/post object or arguments. Examples:

```

```

>>> from beem.utils import construct_authorperm
>>> print(construct_authorperm('username', 'permlink'))
@username/permlink
>>> print(construct_authorperm({'author': 'username', 'permlink':
    ↪'permlink'}))
@username/permlink

```

```

beem.utils.construct_authorpermvoter (*args)
    Create a vote identifier from vote object or arguments. Examples:

```

```

>>> from beem.utils import construct_authorpermvoter
>>> print(construct_authorpermvoter('username', 'permlink', 'voter'))
@username/permlink|voter
>>> print(construct_authorpermvoter({'author': 'username', 'permlink':
    ↪'permlink', 'voter': 'voter'}))
@username/permlink|voter

```

```

beem.utils.derive_beneficiaries (beneficiaries)

```

```
beem.utils.derive_permalink(title, parent_permalink=None, parent_author=None,
                           max_permalink_length=256, with_suffix=True)
Derive a permalink from a comment title (for root level comments) or the parent permalink and optionally the parent author (for replies).
```

```
beem.utils.derive_tags(tags)
```

```
beem.utils.findall_patch_hunks(body=None)
```

```
beem.utils.formatTime(t)
Properly Format Time for permlinks
```

```
beem.utils.formatTimeFromNow(secs=0)
Properly Format Time that is x seconds in the future
```

Parameters `secs` (`int`) – Seconds to go in the future ($x>0$) or the past ($x<0$)

Returns Properly formated time for Graphene (%Y-%m-%dT%H:%M:%S)

Return type str

```
beem.utils.formatTimeString(t)
Properly Format Time for permlinks
```

```
beem.utils.formatTimedelta(td)
Format timedelta to String
```

```
beem.utils.formatToTimeStamp(t)
Returns a timestamp integer
```

Parameters `t` (`datetime`) – datetime object

Returns Timestamp as integer

```
beem.utils.load_dirty_json(dirty_json)
```

```
beem.utils.make_patch(a, b, n=3)
```

```
beem.utils.parse_time(block_time)
Take a string representation of time from the blockchain, and parse it into datetime object.
```

```
beem.utils.remove_from_dict(obj, keys=[], keep_keys=True)
Prune a class or dictionary of all but keys (keep_keys=True). Prune a class or dictionary of specified keys.(keep_keys=False).
```

```
beem.utils.reputation_to_score(rep)
Converts the account reputation value into the reputation score
```

```
beem.utils.resolve_authorperm(identifier)
Correctly split a string containing an authorperm.
```

Splits the string into author and permalink with the following separator: /.

Examples:

```
>>> from beem.utils import resolve_authorperm
>>> author, permalink = resolve_authorperm('https://d.tube/#!/v/pottlund/
...m5cqkd1a')
>>> author, permalink = resolve_authorperm("https://steemit.com/witness-
...category/@gtg/24lfrm-gtg-witness-log")
>>> author, permalink = resolve_authorperm("@gtg/24lfrm-gtg-witness-log")
>>> author, permalink = resolve_authorperm("https://busy.org/@gtg/24lfrm-
...gtg-witness-log")
```

`beem.utils.resolve_authorpermvoter(identifier)`

Correctly split a string containing an authorpermvoter.

Splits the string into author and permlink with the following separator: / and |.

`beem.utils.resolve_root_identifier(url)`

`beem.utils.sanitize_permalink(permalink)`

`beem.utils.seperate_yaml_dict_from_body(content)`

beem.vote

`class beem.vote.AccountVotes(account, start=None, stop=None, raw_data=False, lazy=False, full=False, blockchain_instance=None, **kwargs)`

Bases: `beem.vote.VotesObject`

Obtain a list of votes for an account Lists the last 100+ votes on the given account.

Parameters

- `account` (`str`) – Account name
- `steem_instance` (`Steem`) – Steem() instance to use when accesing a RPC

`class beem.vote.ActiveVotes(authorperm, lazy=False, full=False, blockchain_instance=None, **kwargs)`

Bases: `beem.vote.VotesObject`

Obtain a list of votes for a post

Parameters

- `authorperm` (`str`) – authorperm link
- `steem_instance` (`Steem`) – Steem() instance to use when accesing a RPC

`class beem.vote.Vote(voter, authorperm=None, full=False, lazy=False, blockchain_instance=None, **kwargs)`

Bases: `beem.blockchainobject.BlockchainObject`

Read data about a Vote in the chain

Parameters

- `authorperm` (`str`) – perm link to post/comment
- `steem_instance` (`Steem`) – Steem() instance to use when accesing a RPC

```
>>> from beem.vote import Vote
>>> from beem import Steem
>>> stm = Steem()
>>> v = Vote("@gtg/steem-pressure-4-need-for-speed|gandalf", steem_instance=stm)
```

`authorperm`

`json()`

`percent`

`refresh()`

`rep`

`reputation`

```
rshares
sbd
time
type_id = 11
votee
voter
weight

class beem.vote.VotesObject
Bases: list

get_list(var='voter', voter=None, votee=None, start=None, stop=None, start_percent=None,
         stop_percent=None, sort_key='time', reverse=True)
get_sorted_list(sort_key='time', reverse=True)
printAsTable(voter=None, votee=None, start=None, stop=None, start_percent=None,
             stop_percent=None, sort_key='time', reverse=True, allow_refresh=True, re-
             turn_str=False, **kwargs)
print_stats(return_str=False, **kwargs)
```

beem.wallet

```
class beem.wallet.Wallet(blockchain_instance=None, *args, **kwargs)
Bases: object
```

The wallet is meant to maintain access to private keys for your accounts. It either uses manually provided private keys or uses a SQLite database managed by storage.py.

Parameters

- **rpc** (*SteemNodeRPC*) – RPC connection to a Steem node
- **keys** (*array, dict, str*) – Predefine the wif keys to shortcut the wallet database

Three wallet operation modes are possible:

- **Wallet Database:** Here, beem loads the keys from the locally stored wallet SQLite database (see storage.py). To use this mode, simply call `beem.steem.Steem` without the `keys` parameter
- **Providing Keys:** Here, you can provide the keys for your accounts manually. All you need to do is add the wif keys for the accounts you want to use as a simple array using the `keys` parameter to `beem.steem.Steem`.
- **Force keys:** This mode is for advanced users and requires that you know what you are doing. Here, the `keys` parameter is a dictionary that overwrite the `active`, `owner`, `posting` or `memo` keys for any account. This mode is only used for *foreign* signatures!

A new wallet can be created by using:

```
from beem import Steem
steem = Steem()
steem.wallet.wipe(True)
steem.wallet.create("supersecret-passphrase")
```

This will raise `beem.exceptions.WalletExists` if you already have a wallet installed.

The wallet can be unlocked for signing using

```
from beem import Steem
steem = Steem()
steem.wallet.unlock("supersecret-passphrase")
```

A private key can be added by using the `addPrivateKey()` method that is available **after** unlocking the wallet with the correct passphrase:

```
from beem import Steem
steem = Steem()
steem.wallet.unlock("supersecret-passphrase")
steem.wallet.addPrivateKey("5xxxxxxxxxxxxxxxxxxxxx")
```

Note: The private key has to be either in hexadecimal or in wallet import format (wif) (starting with a 5).

MasterPassword = None

addPrivateKey (wif)

Add a private key to the wallet database

Parameters wif (str) – Private key

addToken (name, token)

changePassphrase (new_pwd)

Change the passphrase for the wallet database

clear_local_keys ()

Clear all manually provided keys

clear_local_token ()

Clear all manually provided token

configStorage = None

create (pwd)

Alias for `newWallet ()`

Parameters pwd (str) – Passphrase for the created wallet

created ()

Do we have a wallet database already?

decrypt_token (enctoken)

Decrypt a wif key

decrypt_wif (encwif)

Decrypt a wif key

deriveChecksum (s)

Derive the checksum

encrypt_token (token)

Encrypt a token key

encrypt_wif (wif)

Encrypt a wif key

getAccount (pub)

Get the account data for a public key (first account found for this public key)

Parameters pub (str) – Public key

getAccountFromPrivateKey (*wif*)
Obtain account name from private key

getAccountFromPublicKey (*pub*)
Obtain the first account name from public key

Parameters **pub** (*str*) – Public key

Note: this returns only the first account with the given key. To get all accounts associated with a given public key, use [*getAccountsFromPublicKey\(\)*](#).

getAccounts ()
Return all accounts installed in the wallet database

getAccountsFromPublicKey (*pub*)
Obtain all account names associated with a public key

Parameters **pub** (*str*) – Public key

getActiveKeyForAccount (*name*)
Obtain owner Active Key for an account from the wallet database

getActiveKeysForAccount (*name*)
Obtain list of all owner Active Keys for an account from the wallet database

getAllAccounts (*pub*)
Get the account data for a public key (all accounts found for this public key)

Parameters **pub** (*str*) – Public key

getKeyForAccount (*name, key_type*)
Obtain *key_type* Private Key for an account from the wallet database

Parameters

- **name** (*str*) – Account name
- **key_type** (*str*) – key type, has to be one of “owner”, “active”, “posting” or “memo”

getKeyType (*account, pub*)
Get key type

Parameters

- **account** (*Account, dict*) – Account data
- **pub** (*str*) – Public key

getKeysForAccount (*name, key_type*)
Obtain a List of *key_type* Private Keys for an account from the wallet database

Parameters

- **name** (*str*) – Account name
- **key_type** (*str*) – key type, has to be one of “owner”, “active”, “posting” or “memo”

getMemoKeyForAccount (*name*)
Obtain owner Memo Key for an account from the wallet database

getOwnerKeyForAccount (*name*)
Obtain owner Private Key for an account from the wallet database

getOwnerKeysForAccount (*name*)
Obtain list of all owner Private Keys for an account from the wallet database

```
getPostingKeyForAccount (name)
    Obtain owner Posting Key for an account from the wallet database

getPostingKeysForAccount (name)
    Obtain list of all owner Posting Keys for an account from the wallet database

getPrivateKeyForPublicKey (pub)
    Obtain the private key for a given public key

    Parameters pub (str) – Public Key

getPublicKeys ()
    Return all installed public keys

getPublicNames ()
    Return all installed public token

getTokenForAccountName (name)
    Obtain the private token for a given public name

    Parameters name (str) – Public name

keyMap = {}

keyStorage = None

keys = {}

lock ()
    Lock the wallet database

locked ()
    Is the wallet database locked?

masterpassword = None

newWallet (pwd)
    Create a new wallet database

    Parameters pwd (str) – Passphrase for the created wallet

prefix

removeAccount (account)
    Remove all keys associated with a given account

    Parameters account (str) – name of account to be removed

removePrivateKeyFromPublicKey (pub)
    Remove a key from the wallet database

    Parameters pub (str) – Public key

removeTokenFromPublicName (name)
    Remove a token from the wallet database

    Parameters name (str) – token to be removed

rpc

setKeys (loadkeys)
    This method is strictly only for in memory keys that are passed to Wallet/Steem with the keys argument

setToken (loadtoken)
    This method is strictly only for in memory token that are passed to Wallet/Steem with the token argument

token = {}
```

```
tokenStorage = None
```

```
tryUnlockFromEnv()
```

Try to fetch the unlock password from UNLOCK environment variable and keyring when no password is given.

```
unlock(pwd=None)
```

Unlock the wallet database

```
unlocked()
```

Is the wallet database unlocked?

```
wipe(sure=False)
```

Purge all data in wallet database

beem.witness

```
class beem.witness.GetWitnesses(name_list, batch_limit=100, lazy=False, full=True, blockchain_instance=None, **kwargs)
```

Bases: *beem.witness.WitnessesObject*

Obtain a list of witnesses

Parameters

- **name_list** (*list*) – list of witnesses to fetch
- **batch_limit** (*int*) – (optional) maximum number of witnesses to fetch per call, defaults to 100
- **steem_instance** (*Steem*) – Steem() instance to use when accessing a RPCcreator = Witness(creator, steem_instance=self)

```
from beem.witness import GetWitnesses
w = GetWitnesses(["gtg", "jest"])
print(w[0].json())
print(w[1].json())
```

```
class beem.witness.ListWitnesses(from_account='', limit=100, lazy=False, full=False, blockchain_instance=None, **kwargs)
```

Bases: *beem.witness.WitnessesObject*

List witnesses ranked by name

Parameters

- **from_account** (*str*) – Witness name from which the lists starts (default = "")
- **limit** (*int*) – Limits the number of shown witnesses (default = 100)
- **steem_instance** (*Steem*) – Steem instance to use when accesing a RPC

```
>>> from beem.witness import ListWitnesses
>>> ListWitnesses(from_account="gtg", limit=100)
<ListWitnesses gtg>
```

```
class beem.witness.Witness(owner, full=False, lazy=False, blockchain_instance=None, **kwargs)
```

Bases: *beem.blockchainobject.BlockchainObject*

Read data about a witness in the chain

Parameters

- **account_name** (*str*) – Name of the witness
- **steem_instance** (*Steem*) – Steem instance to use when accesing a RPC

```
>>> from beem.witness import Witness
>>> Witness("gtg")
<Witness gtg>
```

account**feed_publish** (*base*, *quote=None*, *account=None*)

Publish a feed price as a witness.

Parameters

- **base** (*float*) – USD Price of STEEM in SBD (implied price)
- **quote** (*float*) – (optional) Quote Price. Should be 1.000 (default), unless we are adjusting the feed to support the peg.
- **account** (*str*) – (optional) the source account for the transfer if not self[“owner”]

is_active**json** ()**refresh** ()**type_id = 3****update** (*signing_key*, *url*, *props*, *account=None*)

Update witness

Parameters

- **signing_key** (*str*) – Signing key
- **url** (*str*) – URL
- **props** (*dict*) – Properties
- **account** (*str*) – (optional) witness account name

Properties::

```
{
    "account_creation_fee": x,
    "maximum_block_size": x,
    "sbd_interest_rate": x,
}
```

class beem.witness.**Witnesses** (*lazy=False*, *full=True*, *blockchain_instance=None*, ***kwargs*)
Bases: *beem.witness.WitnessesObject*

Obtain a list of **active** witnesses and the current schedule

Parameters **steem_instance** (*Steem*) – Steem instance to use when accesing a RPC

```
>>> from beem.witness import Witnesses
>>> Witnesses()
<Witnesses >
```

refresh ()

```
class beem.witness.WitnessesObject
Bases: list

    get_votes_sum()

    printAsTable(sort_key='votes', reverse=True, return_str=False, **kwargs)

class beem.witness.WitnessesRankedByVote(from_account='',      limit=100,      lazy=False,
                                         full=False,      blockchain_instance=None,
                                         **kwargs)
Bases: beem.witness.WitnessesObject
```

Obtain a list of witnesses ranked by Vote

Parameters

- **from_account** (*str*) – Witness name from which the lists starts (default = "")
- **limit** (*int*) – Limits the number of shown witnesses (default = 100)
- **steem_instance** (*Steem*) – Steem instance to use when accesing a RPC

```
>>> from beem.witness import WitnessesRankedByVote
>>> WitnessesRankedByVote(limit=100)
<WitnessesRankedByVote >
```

```
class beem.witness.WitnessesVotedByAccount(account,      lazy=False,      full=True,
                                             blockchain_instance=None, **kwargs)
Bases: beem.witness.WitnessesObject
```

Obtain a list of witnesses which have been voted by an account

Parameters

- **account** (*str*) – Account name
- **steem_instance** (*Steem*) – Steem instance to use when accesing a RPC

```
>>> from beem.witness import WitnessesVotedByAccount
>>> WitnessesVotedByAccount("gtg")
<WitnessesVotedByAccount gtg>
```

3.7.2 beemapi Modules

beemapi.exceptions

```
exception beemapi.exceptions.ApiNotSupported
Bases: beemapi.exceptions.RPCError
```

```
exception beemapi.exceptions.CallRetriesReached
Bases: Exception
```

CallRetriesReached Exception. Only for internal use

```
exception beemapi.exceptions.FollowApiNotEnabled
Bases: beemapi.exceptions.RPCError
```

```
exception beemapi.exceptions.InvalidEndpointUrl
Bases: Exception
```

```
exception beemapi.exceptions.MissingRequiredActiveAuthority
Bases: beemapi.exceptions.RPCError
```

```

exception beemapi.exceptions.NoAccessApi
    Bases: beemapi.exceptions.RPCError

exception beemapi.exceptions.NoApiWithName
    Bases: beemapi.exceptions.RPCError

exception beemapi.exceptions.NoMethodWithName
    Bases: beemapi.exceptions.RPCError

exception beemapi.exceptions.NumRetriesReached
    Bases: Exception

        NumRetriesReached Exception.

exception beemapi.exceptions.RPCConnection
    Bases: Exception

        RPCConnection Exception.

exception beemapi.exceptions.RPCError
    Bases: Exception

        RPCError Exception.

exception beemapi.exceptions.RPCErrorDoRetry
    Bases: Exception

        RPCErrorDoRetry Exception.

exception beemapi.exceptions.TimeoutException
    Bases: Exception

exception beemapi.exceptions.UnauthorizedError
    Bases: Exception

        UnauthorizedError Exception.

exception beemapi.exceptions.UnhandledRPCError
    Bases: beemapi.exceptions.RPCError

exception beemapi.exceptions.UnkownKey
    Bases: beemapi.exceptions.RPCError

exception beemapi.exceptions.UnnecessarySignatureDetected
    Bases: Exception

exception beemapi.exceptions.VotedBeforeWaitTimeReached
    Bases: Exception

exception beemapi.exceptions.WorkingNodeMissing
    Bases: Exception

beemapi.exceptions.decodeRPCErrorMsg (e)
    Helper function to decode the raised Exception and give it a python Exception class

```

beemapi.graphenerpc

Note: This is a low level class that can be used in combination with GrapheneClient

This class allows to call API methods exposed by the witness node via websockets. It does **not** support notifications and is not run asynchronously.

graphennewsrpc.

```
class beemapi.graphenerpc.GrapheneRPC(urls, user=None, password=None, **kwargs)
Bases: object
```

This class allows to call API methods synchronously, without callbacks.

It logs warnings and errors.

Parameters

- **urls** (*str*) – Either a single Websocket/Http URL, or a list of URLs
- **user** (*str*) – Username for Authentication
- **password** (*str*) – Password for Authentication
- **num_retries** (*int*) – Try x times to num_retries to a node on disconnect, -1 for indefinitely (default is 100)
- **num_retries_call** (*int*) – Repeat num_retries_call times a rpc call on node error (default is 5)
- **timeout** (*int*) – Timeout setting for https nodes (default is 60)
- **autoconnect** (*bool*) – When set to false, connection is performed on the first rpc call (default is True)
- **use_condenser** (*bool*) – Use the old condenser_api rpc protocol on nodes with version 0.19.4 or higher. The settings has no effect on nodes with version of 0.19.3 or lower.
- **custom_chains** (*dict*) – custom chain which should be added to the known chains

Available APIs:

- database
- network_node
- network_broadcast

Usage:

```
from beemapi.graphenerpc import GrapheneRPC
ws = GrapheneRPC("wss://steemd.pevo.science", "", "")
print(ws.get_account_count())

ws = GrapheneRPC("https://api.steemit.com", "", "")
print(ws.get_account_count())
```

Note: This class allows to call methods available via websocket. If you want to use the notification subsystem, please use GrapheneWebsocket instead.

error_cnt

error_cnt_call

get_network (*props=None*)

Identify the connected network. This call returns a dictionary with keys chain_id, core_symbol and prefix

get_request_id()

Get request id.

get_use_appbase()
Returns True if appbase ready and appbase calls are set

is_appbase_ready()
Check if node is appbase ready

next()
Switches to the next node url

num_retries

num_retries_call

request_send(payload)

rpcclose()
Close Websocket

rpcconnect(next_url=True)
Connect to next url in a loop.

rpceexec(payload)
Execute a call by sending the payload.

Parameters **payload** (*json*) – Payload data

Raises

- **ValueError** – if the server does not respond in proper JSON format
- **RPCError** – if the server returns an error

rpclogin(user, password)
Login into Websocket

version_string_to_int(network_version)

ws_send(payload)

class beemapi.graphenerpc.SessionInstance

Bases: object

Singelton for the Session Instance

instance = None

beemapi.graphenerpc.**create_ws_instance(use_ssl=True, enable_multithread=True)**
Get websocket instance

beemapi.graphenerpc.**set_session_instance(instance)**
Set session instance

beemapi.graphenerpc.**shared_session_instance()**
Get session instance

beemapi.node

class beemapi.node.Node(*url*)
Bases: object

class beemapi.node.Nodes(*urls, num_retries, num_retries_call*)
Bases: list

Stores Node URLs and error counts

```
disable_node()
    Disable current node

error_cnt
error_cnt_call
export_working_nodes()
increase_error_cnt()
    Increase node error count for current node

increase_error_cnt_call()
    Increase call error count for current node

next()
node
num_retries_call_reached
reset_error_cnt()
    Set node error count for current node to zero

reset_error_cnt_call()
    Set call error count for current node to zero

set_node_urls(urls)
sleep_and_check_retries(errorMsg=None, sleep=True, call_retry=False, showMsg=True)
    Sleep and check if num_retries is reached

url
working_nodes_count
```

beemapi.noderpc

```
class beemapi.noderpc.NodeRPC(*args, **kwargs)
Bases: beemapi.graphenerpc.GrapheneRPC
```

This class allows to call API methods exposed by the witness node via websockets / rpc-json.

Parameters

- **urls** (*str*) – Either a single Websocket/Http URL, or a list of URLs
- **user** (*str*) – Username for Authentication
- **password** (*str*) – Password for Authentication
- **num_retries** (*int*) – Try x times to num_retries to a node on disconnect, -1 for indefinitely
- **num_retries_call** (*int*) – Repeat num_retries_call times a rpc call on node error (default is 5)
- **timeout** (*int*) – Timeout setting for https nodes (default is 60)
- **use_condenser** (*bool*) – Use the old condenser_api rpc protocol on nodes with version 0.19.4 or higher. The settings has no effect on nodes with version of 0.19.3 or lower.

```
get_account(name, **kwargs)
Get full account details from account name
```

Parameters **name** (*str*) – Account name

rpceexec(*payload*)

Execute a call by sending the payload. It makes use of the GrapheneRPC library. In here, we mostly deal with Steem specific error handling

Parameters **payload**(*json*) – Payload data

Raises

- **ValueError** – if the server does not respond in proper JSON format
- **RPCError** – if the server returns an error

set_next_node_on_empty_reply(*next_node_on_empty_reply=True*)

Switch to next node on empty reply for the next rpc call

beemapi.websocket

This class allows subscribe to push notifications from the Steem node.

```
from pprint import pprint
from beemapi.websocket import NodeWebsocket

ws = NodeWebsocket(
    "wss://gtg.steem.house:8090",
    accounts=["test"],
    on_block=print,
)

ws.run_forever()
```

```
class beemapi.websocket.NodeWebsocket(urls, user="", password="", only_block_id=False,
                                       on_block=None, keep_alive=25, num_retries=-1,
                                       timeout=60, *args, **kwargs)
```

Create a websocket connection and request push notifications

Parameters

- **urls**(*str*) – Either a single Websocket URL, or a list of URLs
- **user**(*str*) – Username for Authentication
- **password**(*str*) – Password for Authentication
- **keep_alive**(*int*) – seconds between a ping to the backend (defaults to 25seconds)

After instanciating this class, you can add event slots for:

- `on_block`

which will be called accordingly with the notification message received from the Steem node:

```
ws = NodeWebsocket(
    "wss://gtg.steem.house:8090",
)
ws.on_block += print
ws.run_forever()
```

_NodeWebsocket__set_subscriptions()

set subscriptions ot on_block function

__events__ = ['on_block']

```
__getattr__(name)
    Map all methods to RPC calls and pass through the arguments

__init__(urls, user='', password='', only_block_id=False, on_block=None, keep_alive=25,
         num_retries=-1, timeout=60, *args, **kwargs)
    Initialize self. See help(type(self)) for accurate signature.

_module_ = 'beemap.api.websocket'

_ping()
    Send keep_alive request

cancel_subscriptions()
    cancel_all_subscriptions removed from api

close()
    Closes the websocket connection and waits for the ping thread to close

get_request_id()
    Generates next request id

on_close(ws)
    Called when websocket connection is closed

on_error(ws, error)
    Called on websocket errors

on_message(ws, reply, *args)
    This method is called by the websocket connection on every message that is received. If we receive a
    notice, we hand over post-processing and signalling of events to process_notice.

on_open(ws)
    This method will be called once the websocket connection is established. It will
    • login,
    • register to the database api, and
    • subscribe to the objects defined if there is a callback/slot available for callbacks

process_block(data)
    This method is called on notices that need processing. Here, we call the on_block slot.

reset_subscriptions(accounts=[])
    Reset subscriptions

rpceexec(payload)
    Execute a call by sending the payload.

    Parameters payload (json) – Payload data

    Raises
    • ValueError – if the server does not respond in proper JSON format
    • RPCError – if the server returns an error

run_forever()
    This method is used to run the websocket app continuously. It will execute callbacks as defined and try to
    stay connected with the provided APIs

stop()
    Stop running Websocket
```

3.7.3 beembase Modules

beembase.memo

`beembase.memo.decode_memo(priv, message)`

Decode a message with a shared secret between Alice and Bob

Parameters

- `priv` (`PrivateKey`) – Private Key (of Bob)
- `message` (`base58encoded`) – Encrypted Memo message

Returns Decrypted message

Return type str

Raises `ValueError` – if message cannot be decoded as valid UTF-8 string

`beembase.memo.decode_memo_bts(priv, pub, nonce, message)`

Decode a message with a shared secret between Alice and Bob

Parameters

- `priv` (`PrivateKey`) – Private Key (of Bob)
- `pub` (`PublicKey`) – Public Key (of Alice)
- `nonce` (`int`) – Nonce used for Encryption
- `message` (`bytes`) – Encrypted Memo message

Returns Decrypted message

Return type str

Raises `ValueError` – if message cannot be decoded as valid UTF-8 string

`beembase.memo.encode_memo(priv, pub, nonce, message, **kwargs)`

Encode a message with a shared secret between Alice and Bob

Parameters

- `priv` (`PrivateKey`) – Private Key (of Alice)
- `pub` (`PublicKey`) – Public Key (of Bob)
- `nonce` (`int`) – Random nonce
- `message` (`str`) – Memo message

Returns Encrypted message

Return type hex

`beembase.memo.encode_memo_bts(priv, pub, nonce, message)`

Encode a message with a shared secret between Alice and Bob

Parameters

- `priv` (`PrivateKey`) – Private Key (of Alice)
- `pub` (`PublicKey`) – Public Key (of Bob)
- `nonce` (`int`) – Random nonce
- `message` (`str`) – Memo message

Returns Encrypted message

Return type hex

`beembase.memo.get_shared_secret(priv, pub)`

Derive the share secret between priv and pub

Parameters

- **priv** (`Base58`) – Private Key
- **pub** (`Base58`) – Public Key

Returns Shared secret

Return type hex

The shared secret is generated such that:

```
Pub(Alice) * Priv(Bob) = Pub(Bob) * Priv(Alice)
```

`beembase.memo.init_aes(shared_secret, nonce)`

Initialize AES instance

Parameters

- **shared_secret** (`hex`) – Shared Secret to use as encryption key
- **nonce** (`int`) – Random nonce

Returns AES instance and checksum of the encryption key

Return type length 2 tuple

`beembase.memo.init_aes_bts(shared_secret, nonce)`

Initialize AES instance

Parameters

- **shared_secret** (`hex`) – Shared Secret to use as encryption key
- **nonce** (`int`) – Random nonce

Returns AES instance

Return type AES

beembase.objects

class `beembase.objects.Amount(d, prefix='STM')`

Bases: object

class `beembase.objects.Beneficiaries(*args, **kwargs)`

Bases: `beemgraphenebase.objects.GrapheneObject`

class `beembase.objects.Beneficiary(*args, **kwargs)`

Bases: `beemgraphenebase.objects.GrapheneObject`

class `beembase.objects.CommentOptionExtensions(o)`

Bases: `beemgraphenebase.types.Static_variant`

Serialize Comment Payout Beneficiaries.

Parameters **beneficiaries** (`list`) – A static_variant containing beneficiaries.

Example:

```
[0, {  
    'beneficiaries': [  
        {'account': 'furion', 'weight': 10000}  
    ]  
}]
```

```
class beembase.objects.ExchangeRate (*args, **kwargs)
Bases: beemgraphenebase.objects.GrapheneObject

class beembase.objects.Extension (d)
Bases: beemgraphenebase.types.Array

class beembase.objects.Memo (*args, **kwargs)
Bases: beemgraphenebase.objects.GrapheneObject

class beembase.objects.Operation (*args, **kwargs)
Bases: beemgraphenebase.objects.Operation

    getOperationNameForId (i)
        Convert an operation id into the corresponding string

    json ()
    operations ()

class beembase.objects.Permission (*args, **kwargs)
Bases: beemgraphenebase.objects.GrapheneObject

class beembase.objects.Price (*args, **kwargs)
Bases: beemgraphenebase.objects.GrapheneObject

class beembase.objects.SocialActionCommentCreate (o)
Bases: beemgraphenebase.objects.GrapheneObject

class beembase.objects.SocialActionCommentDelete (i)
Bases: beemgraphenebase.objects.GrapheneObject

class beembase.objects.SocialActionCommentUpdate (i)
Bases: beemgraphenebase.objects.GrapheneObject

class beembase.objects.SocialActionVariant (o)
Bases: beemgraphenebase.types.Static_variant

class beembase.objects.WitnessProps (*args, **kwargs)
Bases: beemgraphenebase.objects.GrapheneObject
```

beembase.objecttypes

```
beembase.objecttypes.object_type = {'account': 2, 'account_history': 18, 'block_summary': 1}
```

beembase.operationids

`beembase.operationids.getOperationNameForId(i)`
Convert an operation id into the corresponding string

beembase.operationids.ops = ['vote', 'comment', 'transfer', 'transfer_to_vesting', 'withdraw']
Operation ids

beembase.operations

```
beembase.operationids.getOperationNameForId(i)
    Convert an operation id into the corresponding string
```

```
beembase.operationids.ops = ['vote', 'comment', 'transfer', 'transfer_to_vesting', 'withdrawal']
    Operation ids
```

beembase.signedtransactions

```
class beembase.signedtransactions.Signed_Transaction(*args, **kwargs)
Bases: beemgraphenebase.signedtransactions.Signed_Transaction
```

Create a signed transaction and offer method to create the signature

Parameters

- **refNum** (num) – parameter ref_block_num (see `beembase.transactions.getBlockParams()`)
- **refPrefix** (num) – parameter ref_block_prefix (see `beembase.transactions.getBlockParams()`)
- **expiration** (str) – expiration date
- **operations** (array) – array of operations
- **custom_chains** (dict) – custom chain which should be added to the known chains

```
add_custom_chains(custom_chain)
```

```
getKnownChains()
```

```
getOperationKlass()
```

```
sign(wifkeys, chain='STEEM')
```

Sign the transaction with the provided private keys.

Parameters

- **wifkeys** (array) – Array of wif keys
- **chain** (str) – identifier for the chain

```
verify(pubkeys=[], chain='STEEM', recover_parameter=False)
```

Returned pubkeys have to be checked if they are existing

beembase.ledgertransactions

```
class beembase.ledgertransactions.Ledger_Transaction(*args, **kwargs)
Bases: beemgraphenebase.unsignedtransactions.Unsigned_Transaction
```

Create an unsigned transaction and offer method to send it to a ledger device for signing

Parameters

- **refNum** (num) – parameter ref_block_num (see `beembase.transactions.getBlockParams()`)
- **refPrefix** (num) – parameter ref_block_prefix (see `beembase.transactions.getBlockParams()`)
- **expiration** (str) – expiration date

- **operations** (*array*) – array of operations
- **custom_chains** (*dict*) – custom chain which should be added to the known chains

```
add_custom_chains(custom_chain)
getKnownChains()
getOperationKlass()
get_pubkey(path="48'/13'/0'/0'0'", request_screen_approval=False, prefix='STM')
sign(path="48'/13'/0'/0'0'", chain='STEEM')
```

beembase.transactions

```
beembase.transactions.getBlockParams(ws)
Auxiliary method to obtain ref_block_num and ref_block_prefix. Requires a websocket connection to a witness node!
```

3.7.4 beemgraphenebase Modules

beemgraphenebase.account

```
class beemgraphenebase.account.Address(address=None, pubkey=None, prefix='STM')
Bases: object
```

Address class

This class serves as an address representation for Public Keys.

Parameters

- **address** (*str*) – Base58 encoded address (defaults to None)
- **pubkey** (*str*) – Base58 encoded pubkey (defaults to None)
- **prefix** (*str*) – Network prefix (defaults to STM)

Example:

```
Address ("STMFN9r6VYzBK8EKtMewfNbfiGCr56pHDBFi")
```

```
derive256address_with_version(version=56)
```

Derive address using RIPEMD160 (SHA256(x)) and adding version + checksum

```
derivesha256address()
```

Derive address using RIPEMD160 (SHA256(x))

```
derivesha512address()
```

Derive address using RIPEMD160 (SHA512(x))

```
get_public_key()
```

Returns the pubkey

```
class beemgraphenebase.account.BrainKey(brainkey=None, sequence=0)
```

Bases: object

Brainkey implementation similar to the graphene-ui web-wallet.

Parameters

- **brainkey** (*str*) – Brain Key
- **sequence** (*int*) – Sequence number for consecutive keys

Keys in Graphene are derived from a seed brain key which is a string of 16 words out of a predefined dictionary with 49744 words. It is a simple single-chain key derivation scheme that is not compatible with BIP44 but easy to use.

Given the brain key, a private key is derived as:

```
privkey = SHA256(SHA512(brainkey + " " + sequence))
```

Incrementing the sequence number yields a new key that can be regenerated given the brain key.

```
get_blind_private()
    Derive private key from the brain key (and no sequence number)

get_brainkey()
    Return brain key of this instance

get_private()
    Derive private key from the brain key and the current sequence number

get_private_key()

get_public()

get_public_key()

next_sequence()
    Increment the sequence number by 1

normalize(brainkey)
    Correct formating with single whitespace syntax and no trailing space

suggest(word_count=16)
    Suggest a new random brain key. Randomness is provided by the operating system using os.urandom().

class beemgraphenebase.account.Mnemonic
    Bases: object

    BIP39 mnemonic implementation

    check(mnemonic)
        Checks the mnemonic word list is valid :param list mnemonic: mnemonic word list with lenght of 12, 15, 18, 21, 24 :returns: True, when valid

    check_word(word)

    expand(mnemonic)
        Expands all words given in a list

    expand_word(prefix)
        Expands a word when sufficient chars are given

        Parameters prefix (str) – first chars of a valid dict word

    generate(strength=128)
        Generates a word list based on the given strength

        Parameters strength (int) – initial entropy strength, must be one of [128, 160, 192, 224, 256]
```

```
classmethod normalize_string(txt)
    Normalizes strings

to_entropy(words)

to_mnemonic(data)

classmethod to_seed(mnemonic, passphrase="")
    Returns a seed based on bip39
```

Parameters

- **mnemonic** (*str*) – string containing a valid mnemonic word list
- **passphrase** (*str*) – optional, passphrase can be set to modify the returned seed.

```
class beemgraphenebase.account.MnemonicKey(word_list=None, passphrase="", account_sequence=0, key_sequence=0, prefix='STM')
```

Bases: object

This class derives a private key from a BIP39 mnemonic implementation

```
generate_mnemonic(passphrase="", strength=256)

get_path()

get_private()
    Derive private key from the account_sequence, the role and the key_sequence

get_private_key()

get_public()

get_public_key()

next_account_sequence()
    Increment the account sequence number by 1

next_sequence()
    Increment the key sequence number by 1

set_mnemonic(word_list, passphrase="")

set_path(path)

set_path_BIP32(path)

set_path_BIP44(account_sequence=0, chain_sequence=0, key_sequence=0, hardened_address=True)

set_path_BIP48(network_index=13, role='owner', account_sequence=0, key_sequence=0)

class beemgraphenebase.account.PasswordKey(account, password, role='active', prefix='STM')
```

Bases: object

This class derives a private key given the account name, the role and a password. It leverages the technology of Brainkeys and allows people to have a secure private key by providing a passphrase only.

```
get_private()
    Derive private key from the account, the role and the password

get_private_key()

get_public()

get_public_key()
```

normalize (seed)

Correct formating with single whitespace syntax and no trailing space

class beemgraphenebase.account.**PrivateKey** (*wif=None, prefix='STM'*)

Bases: *beemgraphenebase.account.PublicKey*

Derives the compressed and uncompressed public keys and constructs two instances of *PublicKey*:

Parameters

- **wif** (*str*) – Base58check-encoded wif key
- **prefix** (*str*) – Network prefix (defaults to STM)

Example:

```
PrivateKey("5HqUkGuo62BfcJU5vNhTXKJRJuUi9QSE6jp8C3uBJ2BVhtB8WSd")
```

Compressed vs. Uncompressed:

- **PrivateKey("w-i-f").pubkey**: Instance of *PublicKey* using compressed key.
- **PrivateKey("w-i-f").pubkey.address**: Instance of *Address* using compressed key.
- **PrivateKey("w-i-f").uncompressed**: Instance of *PublicKey* using uncompressed key.
- **PrivateKey("w-i-f").uncompressed.address**: Instance of *Address* using uncompressed key.

child (offset256)

Derive new private key from this key and a sha256 “offset”

compressedpubkey ()

Derive uncompressed public key

derive_from_seed (offset)

Derive private key using “generate_from_seed” method. Here, the key itself serves as a *seed*, and *offset* is expected to be a sha256 digest.

derive_private_key (sequence)

Derive new private key from this private key and an arbitrary sequence number

get_public_key ()

Returns the pubkey

get_secret ()

Get sha256 digest of the wif key.

class beemgraphenebase.account.**PublicKey** (*pk, prefix='STM'*)

Bases: *beemgraphenebase.account.Address*

This class deals with Public Keys and inherits Address.

Parameters

- **pk** (*str*) – Base58 encoded public key
- **prefix** (*str*) – Network prefix (defaults to STM)

Example:

```
PublicKey("STM6UtYWWs3rkZGV8JA86qrgkG6tyFksgECefKE1MiH4HkLD8PFGL")
```

Note: By default, graphene-based networks deal with **compressed** public keys. If an **uncompressed** key is required, the method *unCompressed()* can be used:

```
PublicKey("xxxxxx").unCompressed()
```

compressed()

Derive compressed public key

get_public_key()

Returns the pubkey

point()

Return the point for the public key

unCompressed()

Derive uncompressed key

```
beemgraphenebase.account.binary_search(a, x, lo=0, hi=None)
```

beemgraphenebase.base58

```
class beemgraphenebase.base58.Base58(data, prefix='GPH')
```

Bases: object

Base58 base class

This class serves as an abstraction layer to deal with base58 encoded strings and their corresponding hex and binary representation throughout the library.

Parameters

- **data**(hex, wif, bip38 encrypted wif, base58 string) – Data to initialize object, e.g. pubkey data, address data, ...
- **prefix**(str) – Prefix to use for Address/PubKey strings (defaults to GPH)

Returns Base58 object initialized with data

Return type *Base58*

Raises ValueError – if data cannot be decoded

- **bytes**(Base58) : Returns the raw data
- **str**(Base58) : Returns the readable Base58CheckEncoded data.
- **repr**(Base58) : Gives the hex representation of the data.
- **format**(Base58, _format) : Formats the instance according to _format
 - "btc": prefixed with 0x80. Yields a valid btc address
 - "wif": prefixed with 0x00. Yields a valid wif key
 - "bts": prefixed with BTS
 - etc.

```
beemgraphenebase.base58.b58decode(v)
```

```
beemgraphenebase.base58.b58encode(v)
```

```
beemgraphenebase.base58.base58CheckDecode(s, skip_first_bytes=True)
```

```
beemgraphenebase.base58.base58CheckEncode(version, payload)
```

```
beemgraphenebase.base58.base58decode(base58_str)
beemgraphenebase.base58.base58encode(hexstring)
beemgraphenebase.base58.doublesha256(s)
beemgraphenebase.base58.gphBase58CheckDecode(s)
beemgraphenebase.base58.gphBase58CheckEncode(s)
beemgraphenebase.base58.log = <Logger beemgraphenebase.base58 (WARNING)>
    Default Prefix
beemgraphenebase.base58.ripemd160(s)
```

beemgraphenebase.bip32

```
class beemgraphenebase.bip32.BIP32Key(secret, chain, depth, index, fpr, public=False, testnet=False)
Bases: object

Address()
    Return compressed public key address

CKDpriv(i)
    Create a child key of index ‘i’.
    If the most significant bit of ‘i’ is set, then select from the hardened key set, otherwise, select a regular child key.
    Returns a BIP32Key constructed with the child key parameters, or None if i index would result in an invalid key.

CKDpub(i)
    Create a publicly derived child key of index ‘i’.
    If the most significant bit of ‘i’ is set, this is an error.
    Returns a BIP32Key constructed with the child key parameters, or None if index would result in invalid key.

ChainCode()
    Return chain code as string

ChildKey(i)
    Create and return a child key of this one at index ‘i’.
    The index ‘i’ should be summed with BIP32_HARDEN to indicate to use the private derivation algorithm.

ExtendedKey(private=True, encoded=True)
    Return extended private or public key as string, optionally base58 encoded

Fingerprint()
    Return key fingerprint as string

Identifier()
    Return key identifier as string

P2WPKHoP2SHAddress()
    Return P2WPKH over P2SH segwit address

PrivateKey()
    Return private key as string
```

```
PublicKey()
    Return compressed public key encoding

SetPublic()
    Convert a private BIP32Key into a public one

WalletImportFormat()
    Returns private key encoded for wallet import

dump()
    Dump key fields mimicking the BIP0032 test vector format

static fromEntropy(entropy, public=False, testnet=False)
    Create a BIP32Key using supplied entropy >= MIN_ENTROPY_LEN

static fromExtendedKey(xkey, public=False)
    Create a BIP32Key by importing from extended private or public key string

    If public is True, return a public-only key regardless of input type.

hmac(data)
    Calculate the HMAC-SHA512 of input data using the chain code as key.

    Returns a tuple of the left and right halves of the HMAC

beemgraphenebase.bip32.int_to_hex(x)

beemgraphenebase.bip32.parse_path(nstr, as_bytes=False)

beemgraphenebase.bip32.test()
```

beemgraphenebase.bip38

```
exception beemgraphenebase.bip38.SaltException
    Bases: Exception

beemgraphenebase.bip38.decrypt(encrypted_privkey, passphrase)
    BIP0038 non-ec-multiply decryption. Returns WIF privkey.

Parameters
    • encrypted_privkey (Base58) – Private key
    • passphrase (str) – UTF-8 encoded passphrase for decryption

Returns BIP0038 non-ec-multiply decrypted key

Return type Base58

Raises SaltException – if checksum verification failed (e.g. wrong password)
```

```
beemgraphenebase.bip38.encrypt(privkey, passphrase)
    BIP0038 non-ec-multiply encryption. Returns BIP0038 encrypted privkey.
```

```
Parameters
    • privkey (Base58) – Private key
    • passphrase (str) – UTF-8 encoded passphrase for encryption

Returns BIP0038 non-ec-multiply encrypted wif key

Return type Base58
```

beemgraphenebase.ecdsasig

```
beemgraphenebase.ecdsasig.compressedPubkey (pk)
beemgraphenebase.ecdsasig.recoverPubkeyParameter (message, digest, signature, pubkey)
    Use to derive a number that allows to easily recover the public key from the signature
beemgraphenebase.ecdsasig.recover_public_key (digest, signature, i, message=None)
    Recover the public key from the the signature
beemgraphenebase.ecdsasig.sign_message (message, wif, hashfn=<built-in function
                                                openssl_sha256>)
    Sign a digest with a wif key
Parameters wif (str) – Private key in
beemgraphenebase.ecdsasig.verify_message (message, signature, hashfn=<built-in function
                                                openssl_sha256>, recover_parameter=None)
```

beemgraphenebase.objects

```
class beemgraphenebase.objects.GrapheneObject (data=None)
Bases: object
Core abstraction class
This class is used for any JSON reflected object in Graphene.


- instance.__json__(): encodes data into json format
- bytes(instance): encodes data into wire format
- str(instances): dumps json object as string

json()
toJson()
class beemgraphenebase.objects.Operation (op)
Bases: object
getOperationNameForId (i)
    Convert an operation id into the corresponding string
operations()
beemgraphenebase.objects.isArgsThisClass (self, args)
```

beemgraphenebase.objecttypes

```
beemgraphenebase.objecttypes.object_type = {'OBJECT_TYPE_COUNT': 3, 'account': 2, 'base':
Object types for object ids
```

beemgraphenebase.operations

```
beemgraphenebase.operationids.operations = {'demooepration': 0}
Operation ids
```

beemgraphenebase.signedtransactions

class beemgraphenebase.signedtransactions.**Signed_Transaction** (*args, **kwargs)
 Bases: *beemgraphenebase.objects.GrapheneObject*

Create a signed transaction and offer method to create the signature

Parameters

- **refNum** (num) – parameter ref_block_num (see *beembase.transactions.getBlockParams()*)
- **refPrefix** (num) – parameter ref_block_prefix (see *beembase.transactions.getBlockParams()*)
- **expiration** (str) – expiration date
- **operations** (array) – array of operations

derSigToHexSig(s)
 Format DER to HEX signature

deriveDigest(chain)

getChainParams(chain)

getKnownChains()

getOperationKlass()

id

The transaction id of this transaction

sign(wifkeys, chain=None)
 Sign the transaction with the provided private keys.

Parameters

- **wifkeys** (array) – Array of wif keys
- **chain** (str) – identifier for the chain

verify(pubkeys=[], chain=None, recover_parameter=False)
 Returned pubkeys have to be checked if they are existing

beemgraphenebase.unsignedtransactions

class beemgraphenebase.unsignedtransactions.**GrapheneObjectASN1**(data=None)
 Bases: object

Core abstraction class

This class is used for any JSON reflected object in Graphene.

- **instance.__json__()**: encodes data into json format
- **bytes(instance)**: encodes data into wire format
- **str(instances)**: dumps json object as string

json()

toJson()

```
class beemgraphenebase.unsignedtransactions.UnsignedTransaction(*args,  
**kwargs)
```

Bases: *beemgraphenebase.unsignedtransactions.GrapheneObjectASN1*

Create an unsigned transaction with ASN1 encoder for using it with ledger

Parameters

- **refNum** (*num*) – parameter ref_block_num (see *beembase.transactions.getBlockParams()*)
- **refPrefix** (*num*) – parameter ref_block_prefix (see *beembase.transactions.getBlockParams()*)
- **expiration** (*str*) – expiration date
- **operations** (*array*) – array of operations

build_apdu (*path*=“48’/13’/0’/0’/0”, *chain*=*None*)

build_apdu_pubkey (*path*=“48’/13’/0’/0’/0”, *request_screen_approval*=*False*)

build_path (*role*, *account_index*, *key_index*)

derSigToHexSig (*s*)

Format DER to HEX signature

deriveDigest (*chain*)

getChainParams (*chain*)

getKnownChains ()

getOperationKlass ()

id

The transaction id of this transaction

3.8 Contributing to beem

We welcome your contributions to our project.

3.8.1 Repository

The repository of beem is currently located at:

<https://github.com/holgern/beem>

3.8.2 Flow

This project makes heavy use of [git flow](#). If you are not familiar with it, then the most important thing for your to understand is that:

pull requests need to be made against the develop branch

3.8.3 How to Contribute

0. Familiarize yourself with [contributing on github](#)
1. Fork or branch from the master.
2. Create commits following the commit style
3. Start a pull request to the master branch
4. Wait for a @holger80 or another member to review

3.8.4 Issues

Feel free to submit issues and enhancement requests.

3.8.5 Contributing

Please refer to each project's style guidelines and guidelines for submitting patches and additions. In general, we follow the "fork-and-pull" Git workflow.

1. **Fork** the repo on GitHub
2. **Clone** the project to your own machine
3. **Commit** changes to your own branch
4. **Push** your work back up to your fork
5. Submit a **Pull request** so that we can review your changes

Note: Be sure to merge the latest from "upstream" before making a pull request!

3.8.6 Copyright and Licensing

This library is open sources under the MIT license. We require your to release your code under that license as well.

3.9 Support and Questions

Help and discussion channel for beem can be found here:

- <https://discord.gg/4HM592V>

3.10 Indices and Tables

- genindex
- modindex

CHAPTER 4

Indices and tables

- genindex
- modindex
- search

Python Module Index

b

beem.account, 71
beem.aes, 93
beem.amount, 94
beem.ascichart, 95
beem.asset, 97
beem.block, 97
beem.blockchain, 99
beem.blockchaininstance, 106
beem.blockchainobject, 105
beem.comment, 118
beem.conveyor, 123
beem.discussions, 125
beem.exceptions, 132
beem.hive, 134
beem.hivesigner, 139
beem.imageuploader, 141
beem.instance, 141
beem.market, 142
beem.memo, 148
beem.message, 150
beem.nodelist, 150
beem.notify, 151
beem.price, 152
beem.rc, 155
beem.snapshot, 156
beem.steem, 158
beem.steemconnect, 162
beem.storage, 164
beem.transactionbuilder, 167
beem.utils, 169
beem.vote, 171
beem.wallet, 172
beem.witness, 176
beemapi.exceptions, 178
beemapi.graphenerpc, 179
beemapi.node, 181
beemapi.noderpc, 182
beembase.ledgertransactions, 188

beembase.memo, 185
beembase.objects, 186
beembase.objecttypes, 187
beembase.operationids, 188
beembase.signedtransactions, 188
beembase.transactions, 189
beemgraphenebase.account, 189
beemgraphenebase.base58, 193
beemgraphenebase.bip32, 194
beemgraphenebase.bip38, 195
beemgraphenebase.ecdsasig, 196
beemgraphenebase.objects, 196
beemgraphenebase.objecttypes, 196
beemgraphenebase.operationids, 196
beemgraphenebase.signedtransactions, 197
beemgraphenebase.unsignedtransactions, 197

Symbols

```
-account_creation_fee
    <account_creation_fee>
        beempy-witnesscreate command line
            option, 52
        beempy-witnessproperties command
            line option, 54
        beempy-witnessupdate command line
            option, 55
-account_subsidy_budget
    <account_subsidy_budget>
        beempy-witnessproperties command
            line option, 54
-account_subsidy_decay
    <account_subsidy_decay>
        beempy-witnessproperties command
            line option, 54
-active <active>
    beempy-changekeys command line
        option, 24
    beempy-newaccount command line
        option, 37
-ascii
    beempy-orderbook command line
        option, 39
    beempy-pricehistory command line
        option, 43
    beempy-tradehistory command line
        option, 47
-auto_vest
    beempy-powerdownroute command line
        option, 42
-chart
    beempy-orderbook command line
        option, 39
-claim_all_sbd
    beempy-claimreward command line
        option, 25
-claim_all_steam
    beempy-claimreward command line
        option, 25
    beempy-delkey command line option,
        29
    beempy-deltoken command line
        option, 30
-direction <direction>
    beempy-votes command line option, 51
-fee <fee>
    beempy-claimaccount command line
        option, 25
-file <file>
    beempy-broadcast command line
        option, 22
-hours <hours>
    beempy-tradehistory command line
        option, 47
-key <key>
    beempy-updatememokey command line
        option, 49
-limit <limit>
    beempy-witnesses command line
        option, 53
-maximum_block_size
    <maximum_block_size>
        beempy-witnesscreate command line
            option, 52
        beempy-witnessproperties command
            line option, 54
        beempy-witnessupdate command line
            option, 55
-memo <memo>
    beempy-changekeys command line
        option, 24
    beempy-newaccount command line
        option, 37
```

```
-new_signing_key <new_signing_key>
    beempy-witnessproperties command
        line option, 54
-only-https
    beempy-updatenodes command line
        option, 49
-only-wss
    beempy-updatenodes command line
        option, 49
-orderid <orderid>
    beempy-buy command line option, 23
    beempy-sell command line option, 45
-owner <owner>
    beempy-changekeys command line
        option, 24
    beempy-newaccount command line
        option, 37
-path <path>
    beempy command line option, 20
-payout <payout>
    beempy-curation command line
        option, 27
-percentage <percentage>
    beempy-powerdownroute command line
        option, 42
-permission <permission>
    beempy-allow command line option, 21
    beempy-disallow command line
        option, 30
-posting <posting>
    beempy-changekeys command line
        option, 24
    beempy-newaccount command line
        option, 37
-raw
    beempy-pingnode command line
        option, 40
-remove
    beempy-pingnode command line
        option, 40
-results
    beempy-nextnode command line
        option, 37
-reward_sbd <reward_sbd>
    beempy-claimreward command line
        option, 25
-reward_steam <reward_steam>
    beempy-claimreward command line
        option, 25
-reward_vests <reward_vests>
    beempy-claimreward command line
        option, 25
-roles <roles>
    beempy-importaccount command line
        option, 33
-sbd_interest_rate <sbd_interest_rate>
    beempy-witnesscreate command line
        option, 52
    beempy-witnessproperties command
        line option, 54
    beempy-witnessupdate command line
        option, 55
-show-date
    beempy-orderbook command line
        option, 39
-signing_key <signing_key>
    beempy-witnessupdate command line
        option, 55
-sort
    beempy-pingnode command line
        option, 40
-strength <strength>
    beempy-keygen command line option,
        34
-support-peg
    beempy-witnessfeed command line
        option, 54
-threading
    beempy-pingnode command line
        option, 40
-threshold <threshold>
    beempy-allow command line option, 21
    beempy-disallow command line
        option, 30
-to <to>
    beempy-powerup command line option,
        43
-unsafe-import-key <unsafe_import_key>
    beempy-addkey command line option,
        20
    beempy-parsewif command line
        option, 39
-unsafe-import-token
    <unsafe_import_token>
    beempy-addtoken command line
        option, 21
-url
    beempy-currentnode command line
        option, 27
-url <url>
    beempy-witnesscreate command line
        option, 52
    beempy-witnessproperties command
        line option, 54
    beempy-witnessupdate command line
        option, 55
-version
    beempy command line option, 20
```

```

beempy-currentnode command line
    option, 27
-weight <weight>
    beempy-allow command line option, 21
-what <what>
    beempy-follow command line option,
        32
    beempy-mute command line option, 36
-wipe
    beempy-createwallet command line
        option, 26
-witness <witness>
    beempy-witnessupdate command line
        option, 55
-a, -account <account>
    beempy-allow command line option, 21
    beempy-approvewitness command line
        option, 22
    beempy-buy command line option, 23
    beempy-cancel command line option,
        23
    beempy-changerecovery command line
        option, 24
    beempy-convert command line option,
        26
    beempy-curation command line
        option, 26
    beempy-customjson command line
        option, 28
    beempy-delegate command line
        option, 28
    beempy-delete command line option,
        28
    beempy-delprofile command line
        option, 29
    beempy-delproxy command line
        option, 30
    beempy-disallow command line
        option, 30
    beempy-disapprovewitness command
        line option, 31
    beempy-download command line
        option, 31
    beempy-downvote command line
        option, 32
    beempy-follow command line option,
        32
    beempy-keygen command line option,
        34
    beempy-mute command line option, 36
    beempy-newaccount command line
        option, 37
    beempy-post command line option, 41
    beempy-powerdown command line
        option, 42
    beempy-powerdownroute command line
        option, 42
    beempy-powerup command line option,
        43
    beempy-reblog command line option,
        43
    beempy-reply command line option, 44
    beempy-sell command line option, 45
    beempy-setprofile command line
        option, 46
    beempy-setproxy command line
        option, 46
    beempy-transfer command line
        option, 48
    beempy-unfollow command line
        option, 48
    beempy-updatememokey command line
        option, 49
    beempy-uploadimage command line
        option, 49
    beempy-upvote command line option,
        50
-a, -all
    beempy-notifications command line
        option, 38
-a, -author
    beempy-pending command line option,
        40
    beempy-rewards command line option,
        44
-a, -ledger-approval
    beempy-listkeys command line
        option, 35
-a, -max-account-index
    <max_account_index>
    beempy-listaccounts command line
        option, 35
-b, -base <base>
    beempy-witnessfeed command line
        option, 54
-b, -beneficiaries <beneficiaries>
    beempy-post command line option, 41
-b, -reblogs
    beempy-notifications command line
        option, 38
-c, -comment
    beempy-pending command line option,
        39
    beempy-rewards command line option,
        44
-c, -community <community>
    beempy-post command line option, 41
-c, -create-claimed-account

```

```
beempy-newaccount command line
    option, 37
-c, -create-password
    beempy-keygen command line option,
        35
-d, -days <days>
    beempy-curation command line
        option, 27
    beempy-pending command line option,
        40
    beempy-rewards command line option,
        45
    beempy-tradehistory command line
        option, 47
    beempy-votes command line option, 51
-d, -no-broadcast
    beempy command line option, 19
-d, -percent-steem-dollars
    <percent_steem_dollars>
    beempy-post command line option, 41
-e, -expires <expires>
    beempy command line option, 20
-e, -export <export>
    beempy-curation command line
        option, 27
    beempy-download command line
        option, 31
    beempy-keygen command line option,
        35
    beempy-votes command line option, 51
-e, -no-patch-on-edit
    beempy-post command line option, 41
-e, -permlink
    beempy-pending command line option,
        40
    beempy-rewards command line option,
        44
-e, -steem
    beempy-updatenodes command line
        option, 49
-f, -follows
    beempy-notifications command line
        option, 38
-f, -from <_from>
    beempy-pending command line option,
        40
-g, -tags <tags>
    beempy-post command line option, 41
-h, -height <height>
    beempy-orderbook command line
        option, 39
    beempy-pricehistory command line
        option, 43
    beempy-tradehistory command line
        option, 47
-h, -hive
    beempy command line option, 20
    beempy-updatenodes command line
        option, 49
-i, -file <file>
    beempy-sign command line option, 47
-i, -import-password
    beempy-keygen command line option,
        34
-i, -import-pub <import_pub>
    beempy-changekeys command line
        option, 24
    beempy-newaccount command line
        option, 37
-i, -incoming
    beempy-votes command line option, 51
-i, -sbd-to-steem
    beempy-ticker command line option,
        47
    beempy-tradehistory command line
        option, 47
-k, -account-keys
    beempy-keygen command line option,
        34
-k, -keys <keys>
    beempy command line option, 20
-l, -create-link
    beempy command line option, 19
-l, -import-word-list
    beempy-keygen command line option,
        34
-l, -length <length>
    beempy-curation command line
        option, 27
    beempy-pending command line option,
        39
    beempy-rewards command line option,
        44
-l, -limit <limit>
    beempy-notifications command line
        option, 38
    beempy-orderbook command line
        option, 39
    beempy-tradehistory command line
        option, 47
-l, -lock
    beempy-walletinfo command line
        option, 52
-m, -limit <limit>
    beempy-curation command line
        option, 26
-m, -mark_as_read
    beempy-notifications command line
```

```

        option, 38
-m, -max-accepted-payout
    <max_accepted_payout>
    beempy-post command line option, 41
-m, -path <path>
    beempy-keygen command line option,
        34
-n, -image-name <image_name>
    beempy-uploadimage command line
        option, 49
-n, -network <network>
    beempy-keygen command line option,
        34
-n, -no-parse-body
    beempy-post command line option, 41
-n, -node <node>
    beempy command line option, 19
-n, -number <number>
    beempy-claimaccount command line
        option, 25
-o, -offline
    beempy command line option, 19
-o, -outfile <outfile>
    beempy-sign command line option, 47
-o, -outgoing
    beempy-votes command line option, 51
-p, -no-wallet
    beempy command line option, 19
-p, -pair <pair>
    beempy-setprofile command line
        option, 46
-p, -passphrase
    beempy-keygen command line option,
        34
-p, -path <path>
    beempy-listkeys command line
        option, 35
-p, -permlink
    beempy-curation command line
        option, 27
-p, -permlink <permlink>
    beempy-post command line option, 41
-p, -post
    beempy-pending command line option,
        39
    beempy-rewards command line option,
        44
-q, -quote <quote>
    beempy-witnessfeed command line
        option, 54
-r, -replies
    beempy-notifications command line
        option, 38
-r, -reply-identifier
    <reply_identifier>
    beempy-post command line option, 41
-r, -role <role>
    beempy-keygen command line option,
        34
    beempy-listaccounts command line
        option, 35
-s, -max-sequence <max_sequence>
    beempy-listaccounts command line
        option, 35
-s, -only-sum
    beempy-pending command line option,
        39
    beempy-rewards command line option,
        44
-s, -save
    beempy-download command line
        option, 31
-s, -sequence <sequence>
    beempy-keygen command line option,
        34
-s, -short
    beempy-curation command line
        option, 27
-s, -show
    beempy-updatenodes command line
        option, 49
-s, -signing-account <signing_account>
    beempy-featureflags command line
        option, 32
    beempy-userdata command line
        option, 50
-s, -steem
    beempy command line option, 20
-t, -active
    beempy-customjson command line
        option, 28
-t, -mentions
    beempy-notifications command line
        option, 38
-t, -test
    beempy-updatenodes command line
        option, 49
-t, -title
    beempy-curation command line
        option, 27
    beempy-pending command line option,
        40
    beempy-rewards command line option,
        45
-t, -title <title>
    beempy-post command line option, 41
    beempy-reply command line option, 44

```

```
-t, -token
    beempy command line option, 20
-t, -trx <trx>
    beempy-verify command line option,
      51
-u, -export-pub <export_pub>
    beempy-keygen command line option,
      35
-u, -unlock
    beempy-walletinfo command line
      option, 52
-u, -use-api
    beempy-verify command line option,
      51
-u, -use-ledger
    beempy command line option, 20
-v, -curation
    beempy-pending command line option,
      39
    beempy-rewards command line option,
        44
-v, -min-vote <min_vote>
    beempy-curation command line
      option, 26
-v, -verbose <verbose>
    beempy command line option, 20
-v, -votes
    beempy-notifications command line
      option, 38
-w, -max-vote <max_vote>
    beempy-curation command line
      option, 26
-w, -weight <weight>
    beempy-downvote command line
      option, 32
    beempy-upvote command line option,
      50
-w, -width <width>
    beempy-orderbook command line
      option, 39
    beempy-pricehistory command line
      option, 43
    beempy-tradehistory command line
      option, 47
-w, -wif <wif>
    beempy-keygen command line option,
      35
    beempy-newaccount command line
      option, 37
-x, -min-performance <min_performance>
    beempy-curation command line
      option, 27
-x, -unsigned
    beempy command line option, 19
-y, -max-performance <max_performance>
    beempy-curation command line
      option, 27
_NodeWebsocket__set_subscriptions()
    (beemapi.websocket.NodeWebsocket method),
      183
__events__ (beemapi.websocket.NodeWebsocket
      attribute), 183
__getattr__() (beemapi.websocket.NodeWebsocket
      method), 183
__init__() (beemapi.websocket.NodeWebsocket
      method), 184
__module__ (beemapi.websocket.NodeWebsocket
      attribute), 184
_ping() (beemapi.websocket.NodeWebsocket method),
      184
```

A

```
abort() (beem.blockchain.Pool method), 104
ACCOUNT
    beempy-balance command line option,
      22
    beempy-changekeys command line
      option, 24
    beempy-claimreward command line
      option, 25
    beempy-featureflags command line
      option, 32
    beempy-follower command line
      option, 33
    beempy-following command line
      option, 33
    beempy-importaccount command line
      option, 33
    beempy-interest command line
      option, 34
    beempy-muter command line option, 36
    beempy-muting command line option,
      36
    beempy-notifications command line
      option, 38
    beempy-openorders command line
      option, 38
    beempy-permissions command line
      option, 40
    beempy-power command line option, 42
    beempy-userdata command line
      option, 50
    beempy-votes command line option, 51
    beempy-witnesses command line
      option, 53
account (beem.witness.Witness attribute), 177
Account (class in beem.account), 71
```

account_create_dict() (*beem.rc.RC method*), 155
 account_update_dict() (*beem.rc.RC method*), 155
 AccountDoesNotExistException, 132
 AccountExistsException, 132
 ACCOUNTNAME
 beempy-newaccount command line option, 37
 accountopenorders() (*beem.market.Market method*), 143
 ACCOUNTS
 beempy-pending command line option, 40
 beempy-rewards command line option, 45
 Accounts (*class in beem.account*), 93
 AccountSnapshot (*class in beem.snapshot*), 156
 AccountsObject (*class in beem.account*), 93
 AccountVotes (*class in beem.vote*), 171
 ActiveVotes (*class in beem.vote*), 171
 adapt_on_series() (*beem.asciichart.AsciiChart method*), 95
 add() (*beem.storage.Key method*), 165
 add() (*beem.storage.Token method*), 166
 add_axis() (*beem.asciichart.AsciiChart method*), 96
 add_curve() (*beem.asciichart.AsciiChart method*), 96
 add_custom_chains() (*beem-base.ledgertransactions.Ledger_Transaction method*), 189
 add_custom_chains() (*beem-base.signedtransactions.Signed_Transaction method*), 188
 addPrivateKey() (*beem.wallet.Wallet method*), 173
 Address (*class in beemgraphenebase.account*), 189
 Address() (*beemgraphenebase.bip32.BIP32Key method*), 194
 addSigningInformation() (*beem.transactionbuilder.TransactionBuilder method*), 168
 addToken() (*beem.wallet.Wallet method*), 173
 addTzInfo() (*in module beem.utils*), 169
 AESCipher (*class in beem.aes*), 93
 alive() (*beem.blockchain.Pool method*), 104
 allow() (*beem.account.Account method*), 72
 AMOUNT
 beempy-buy command line option, 23
 beempy-convert command line option, 26
 beempy-delegate command line option, 28
 beempy-powerdown command line option, 42
 beempy-powerup command line option, 43
 beempy-sell command line option, 45
 beempy-transfer command line option, 48
 amount (*beem.amount.Amount attribute*), 95
 Amount (*class in beem.amount*), 94
 Amount (*class in beembase.objects*), 186
 amount_decimal (*beem.amount.Amount attribute*), 95
 ApiNotSupported, 178
 appauthor (*beem.storage.DataDir attribute*), 165
 appendMissingSignatures() (*beem.transactionbuilder.TransactionBuilder method*), 168
 appendOps() (*beem.transactionbuilder.TransactionBuilder method*), 168
 appendSigner() (*beem.transactionbuilder.TransactionBuilder method*), 168
 appendWif() (*beem.transactionbuilder.TransactionBuilder method*), 168
 appname (*beem.storage.DataDir attribute*), 165
 approvewitness() (*beem.account.Account method*), 72
 as_base() (*beem.price.Price method*), 154
 as_quote() (*beem.price.Price method*), 154
 AsciiChart (*class in beem.asciichart*), 95
 ASSET
 beempy-buy command line option, 23
 beempy-sell command line option, 45
 beempy-transfer command line option, 48
 asset (*beem.amount.Amount attribute*), 95
 asset (*beem.asset.Asset attribute*), 97
 Asset (*class in beem.asset*), 97
 AssetDoesNotExistException, 132
 assets_from_string() (*in module beem.utils*), 169
 author (*beem.comment.Comment attribute*), 118
 AUTHORPERM
 beempy-beneficiaries command line option, 22
 beempy-curation command line option, 27
 beempy-reply command line option, 44
 authorperm (*beem.comment.Comment attribute*), 118
 authorperm (*beem.vote.Vote attribute*), 171
 available_balances (*beem.account.Account attribute*), 72
 awaitTxConfirmation() (*beem.blockchain.Blockchain method*), 99

B

b58decode() (*in module beemgraphenebase.base58*),

193
b58encode () (*in module* `beemgraphenebase.base58`), 193
backed_token_symbol
 (*beem.blockchaininstance.BlockChainInstance attribute*), 107
balances (*beem.account.Account attribute*), 72
`Base58` (*class in* `beemgraphenebase.base58`), 193
`base58CheckDecode()` (*in module* `beem-graphenebase.base58`), 193
`base58CheckEncode()` (*in module* `beem-graphenebase.base58`), 193
`base58decode()` (*in module* `beem-graphenebase.base58`), 193
`base58encode()` (*in module* `beem-graphenebase.base58`), 194
`BatchedCallsNotSupported`, 132
`beem.account` (*module*), 71
`beem.aes` (*module*), 93
`beem.amount` (*module*), 94
`beem.asciichart` (*module*), 95
`beem.asset` (*module*), 97
`beem.block` (*module*), 97
`beem.blockchain` (*module*), 99
`beem.blockchaininstance` (*module*), 106
`beem.blockchainobject` (*module*), 105
`beem.comment` (*module*), 118
`beem.conveyor` (*module*), 123
`beem.discussions` (*module*), 125
`beem.exceptions` (*module*), 132
`beem.hive` (*module*), 134
`beem.hivesigner` (*module*), 139
`beem.imageuploader` (*module*), 141
`beem.instance` (*module*), 141
`beem.market` (*module*), 142
`beem.memo` (*module*), 148
`beem.message` (*module*), 150
`beem.nodelist` (*module*), 150
`beem.notify` (*module*), 151
`beem.price` (*module*), 152
`beem.rc` (*module*), 155
`beem.snapshot` (*module*), 156
`beem.steem` (*module*), 158
`beem.steemconnect` (*module*), 162
`beem.storage` (*module*), 164
`beem.transactionbuilder` (*module*), 167
`beem.utils` (*module*), 169
`beem.vote` (*module*), 171
`beem.wallet` (*module*), 172
`beem.witness` (*module*), 176
`beemapi.exceptions` (*module*), 178
`beemapi.graphenerpc` (*module*), 179
`beemapi.node` (*module*), 181
`beemapi.noderpc` (*module*), 182
`beembase.ledgertransactions` (*module*), 188
`beembase.memo` (*module*), 185
`beembase.objects` (*module*), 186
`beembase.objecttypes` (*module*), 187
`beembase.operationids` (*module*), 188
`beembase.signedtransactions` (*module*), 188
`beembase.transactions` (*module*), 189
`beemgraphenebase.account` (*module*), 189
`beemgraphenebase.base58` (*module*), 193
`beemgraphenebase.bip32` (*module*), 194
`beemgraphenebase.bip38` (*module*), 195
`beemgraphenebase.ecdsasig` (*module*), 196
`beemgraphenebase.objects` (*module*), 196
`beemgraphenebase.objecttypes` (*module*), 196
`beemgraphenebase.operationids` (*module*), 196
`beemgraphenebase.signedtransactions` (*module*), 197
`beemgraphenebase.unsignedtransactions` (*module*), 197
`beempy` command line option
 `-path <path>`, 20
 `-version`, 20
 `-d, -no-broadcast`, 19
 `-e, -expires <expires>`, 20
 `-h, -hive`, 20
 `-k, -keys <keys>`, 20
 `-l, -create-link`, 19
 `-n, -node <node>`, 19
 `-o, -offline`, 19
 `-p, -no-wallet`, 19
 `-s, -steem`, 20
 `-t, -token`, 20
 `-u, -use-ledger`, 20
 `-v, -verbose <verbose>`, 20
 `-x, -unsigned`, 19
`beempy-addkey` command line option
 `-unsafe-import-key <unsafe_import_key>`, 20
`beempy-addtoken` command line option
 `-unsafe-import-token <unsafe_import_token>`, 21
 `NAME`, 21
`beempy-allow` command line option
 `-permission <permission>`, 21
 `-threshold <threshold>`, 21
 `-weight <weight>`, 21
 `-a, -account <account>`, 21
 `FOREIGN_ACCOUNT`, 21
`beempy-approvewitness` command line option
 `-a, -account <account>`, 22
 `WITNESS`, 22
`beempy-balance` command line option

```

ACCOUNT, 22
beempy-beneficiaries command line
    option
AUTHORPERM, 22
BENEFICIARIES, 22
beempy-broadcast command line option
    -file <file>, 22
beempy-buy command line option
    -orderid <orderid>, 23
    -a, -account <account>, 23
AMOUNT, 23
ASSET, 23
PRICE, 23
beempy-cancel command line option
    -a, -account <account>, 23
    ORDERID, 23
beempy-changekeys command line option
    -active <active>, 24
    -memo <memo>, 24
    -owner <owner>, 24
    -posting <posting>, 24
    -i, -import-pub <import_pub>, 24
    ACCOUNT, 24
beempy-changerecovery command line
    option
    -a, -account <account>, 24
    NEW_RECOVERY_ACCOUNT, 24
beempy-claimaccount command line
    option
    -fee <fee>, 25
    -n, -number <number>, 25
    CREATOR, 25
beempy-claimreward command line option
    -claim_all_sbd, 25
    -claim_all_steam, 25
    -claim_all_vests, 25
    -reward_sbd <reward_sbd>, 25
    -reward_steam <reward_steam>, 25
    -reward_vests <reward_vests>, 25
    ACCOUNT, 25
beempy-convert command line option
    -a, -account <account>, 26
    AMOUNT, 26
beempy-createwallet command line
    option
    -wipe, 26
beempy-curation command line option
    -payout <payout>, 27
    -a, -account <account>, 26
    -d, -days <days>, 27
    -e, -export <export>, 27
    -l, -length <length>, 27
    -m, -limit <limit>, 26
    -p, -permlink, 27
    -s, -short, 27
    -t, -title, 27
    -v, -min-vote <min_vote>, 26
    -w, -max-vote <max_vote>, 26
    -x, -min-performance
        <min_performance>, 27
    -y, -max-performance
        <max_performance>, 27
    AUTHORPERM, 27
beempy-currentnode command line option
    -url, 27
    -version, 27
beempy-customjson command line option
    -a, -account <account>, 28
    -t, -active, 28
    JSON_DATA, 28
    JSONID, 28
beempy-delegate command line option
    -a, -account <account>, 28
    AMOUNT, 28
    TO_ACCOUNT, 28
beempy-delete command line option
    -a, -account <account>, 28
    POST, 29
beempy-delkey command line option
    -confirm, 29
    PUB, 29
beempy-delprofile command line option
    -a, -account <account>, 29
    VARIABLE, 29
beempy-delproxy command line option
    -a, -account <account>, 30
beempy-deltoken command line option
    -confirm, 30
    NAME, 30
beempy-disallow command line option
    -permission <permission>, 30
    -threshold <threshold>, 30
    -a, -account <account>, 30
    FOREIGN_ACCOUNT, 30
beempy-disapprovewitness command line
    option
    -a, -account <account>, 31
    WITNESS, 31
beempy-download command line option
    -a, -account <account>, 31
    -e, -export <export>, 31
    -s, -save, 31
    PERMLINK, 31
beempy-downvote command line option
    -a, -account <account>, 32
    -w, -weight <weight>, 32
    POST, 32

```

```
beempy-featureflags command line
    option
        -s, -signing-account
            <signing_account>, 32
        ACCOUNT, 32
beempy-follow command line option
    -what <what>, 32
    -a, -account <account>, 32
        FOLLOW, 32
beempy-follower command line option
    ACCOUNT, 33
beempy-following command line option
    ACCOUNT, 33
beempy-importaccount command line
    option
        -roles <roles>, 33
    ACCOUNT, 33
beempy-info command line option
    OBJECTS, 34
beempy-interest command line option
    ACCOUNT, 34
beempy-keygen command line option
    -strength <strength>, 34
    -a, -account <account>, 34
    -c, -create-password, 35
    -e, -export <export>, 35
    -i, -import-password, 34
    -k, -account-keys, 34
    -l, -import-word-list, 34
    -m, -path <path>, 34
    -n, -network <network>, 34
    -p, -passphrase, 34
    -r, -role <role>, 34
    -s, -sequence <sequence>, 34
    -u, -export-pub <export_pub>, 35
    -w, -wif <wif>, 35
beempy-listaccounts command line
    option
        -a, -max-account-index
            <max_account_index>, 35
        -r, -role <role>, 35
        -s, -max-sequence <max_sequence>, 35
beempy-listkeys command line option
    -a, -ledger-approval, 35
    -p, -path <path>, 35
beempy-mute command line option
    -what <what>, 36
    -a, -account <account>, 36
        MUTE, 36
beempy-muter command line option
    ACCOUNT, 36
beempy-muting command line option
    ACCOUNT, 36
beempy-newaccount command line option
    -active <active>, 37
    -memo <memo>, 37
    -owner <owner>, 37
    -posting <posting>, 37
    -a, -account <account>, 37
    -c, -create-claimed-account, 37
    -i, -import-pub <import_pub>, 37
    -w, -wif <wif>, 37
        ACCOUNTNAME, 37
beempy-nextnode command line option
    -results, 37
beempy-notifications command line
    option
        -a, -all, 38
        -b, -reblogs, 38
        -f, -follows, 38
        -l, -limit <limit>, 38
        -m, -mark_as_read, 38
        -r, -replies, 38
        -t, -mentions, 38
        -v, -votes, 38
    ACCOUNT, 38
beempy-openorders command line option
    ACCOUNT, 38
beempy-orderbook command line option
    -ascii, 39
    -chart, 39
    -show-date, 39
    -h, -height <height>, 39
    -l, -limit <limit>, 39
    -w, -width <width>, 39
beempy-parsewif command line option
    -unsafe-import-key
        <unsafe_import_key>, 39
beempy-pending command line option
    -a, -author, 40
    -c, -comment, 39
    -d, -days <days>, 40
    -e, -permalink, 40
    -f, -from <_from>, 40
    -l, -length <length>, 39
    -p, -post, 39
    -s, -only-sum, 39
    -t, -title, 40
    -v, -curation, 39
    ACCOUNTS, 40
beempy-permissions command line option
    ACCOUNT, 40
beempy-pingnode command line option
    -raw, 40
    -remove, 40
    -sort, 40
    -threading, 40
beempy-post command line option
```

```

-a, -account <account>, 41
-b, -beneficiaries <beneficiaries>, 41
-c, -community <community>, 41
-d, -percent-steem-dollars
    <percent_steem_dollars>, 41
-e, -no-patch-on-edit, 41
-g, -tags <tags>, 41
-m, -max-accepted-payout
    <max_accepted_payout>, 41
-n, -no-parse-body, 41
-p, -permlink <permlink>, 41
-r, -reply_identifier
    <reply_identifier>, 41
-t, -title <title>, 41
    MARKDOWN_FILE, 41
beempy-power command line option
    ACCOUNT, 42
beempy-powerdown command line option
    -a, -account <account>, 42
    AMOUNT, 42
beempy-powerdownroute command line
    option
    -auto_vest, 42
    -percentage <percentage>, 42
    -a, -account <account>, 42
    TO, 42
beempy-powerup command line option
    -to <to>, 43
    -a, -account <account>, 43
    AMOUNT, 43
beempy-pricehistory command line
    option
    -ascii, 43
    -h, -height <height>, 43
    -w, -width <width>, 43
beempy-reblog command line option
    -a, -account <account>, 43
    IDENTIFIER, 44
beempy-reply command line option
    -a, -account <account>, 44
    -t, -title <title>, 44
    AUTHOPERM, 44
    BODY, 44
beempy-rewards command line option
    -a, -author, 44
    -c, -comment, 44
    -d, -days <days>, 45
    -e, -permlink, 44
    -l, -length <length>, 44
    -p, -post, 44
    -s, -only-sum, 44
    -t, -title, 45
    -v, -curation, 44
                                ACCOUNTS, 45
                                beempy-sell command line option
                                    -orderid <orderid>, 45
                                    -a, -account <account>, 45
                                    AMOUNT, 45
                                    ASSET, 45
                                    PRICE, 45
                                beempy-set command line option
                                    KEY, 46
                                    VALUE, 46
                                beempy-setprofile command line option
                                    -a, -account <account>, 46
                                    -p, -pair <pair>, 46
                                    VALUE, 46
                                    VARIABLE, 46
                                beempy-setproxy command line option
                                    -a, -account <account>, 46
                                    PROXY, 46
                                beempy-sign command line option
                                    -i, -file <file>, 47
                                    -o, -outfile <outfile>, 47
                                beempy-ticker command line option
                                    -i, -sbd-to-steem, 47
                                beempy-tradehistory command line
                                    option
                                    -ascii, 47
                                    -hours <hours>, 47
                                    -d, -days <days>, 47
                                    -h, -height <height>, 47
                                    -i, -sbd-to-steem, 47
                                    -l, -limit <limit>, 47
                                    -w, -width <width>, 47
                                beempy-transfer command line option
                                    -a, -account <account>, 48
                                    AMOUNT, 48
                                    ASSET, 48
                                    MEMO, 48
                                    TO, 48
                                beempy-unfollow command line option
                                    -a, -account <account>, 48
                                    UNFOLLOW, 48
                                beempy-updatememokey command line
                                    option
                                    -key <key>, 49
                                    -a, -account <account>, 49
                                beempy-updatenodes command line option
                                    -only-https, 49
                                    -only-wss, 49
                                    -e, -steem, 49
                                    -h, -hive, 49
                                    -s, -show, 49
                                    -t, -test, 49
                                beempy-uploadimage command line option
                                    -a, -account <account>, 49

```

```

-n, -image-name <image_name>, 49
IMAGE, 49
beempy-upvote command line option
-a, -account <account>, 50
-w, -weight <weight>, 50
POST, 50
beempy-userdata command line option
-s, -signing-account
<signing_account>, 50
ACCOUNT, 50
beempy-verify command line option
-t, -trx <trx>, 51
-u, -use-api, 51
BLOCKNUMBER, 51
beempy-votes command line option
-direction <direction>, 51
-d, -days <days>, 51
-e, -export <export>, 51
-i, -incoming, 51
-o, -outgoing, 51
ACCOUNT, 51
beempy-walletinfo command line option
-l, -lock, 52
-u, -unlock, 52
beempy-witness command line option
WITNESS, 52
beempy-witnesscreate command line
option
-account_creation_fee
<account_creation_fee>, 52
-maximum_block_size
<maximum_block_size>, 52
-sbd_interest_rate
<sbd_interest_rate>, 52
-url <url>, 52
PUB_SIGNING_KEY, 52
WITNESS, 52
beempy-witnessdisable command line
option
WITNESS, 53
beempy-witnessenable command line
option
SIGNING_KEY, 53
WITNESS, 53
beempy-witnesses command line option
-limit <limit>, 53
ACCOUNT, 53
beempy-witnessfeed command line option
-support-peg, 54
-b, -base <base>, 54
-q, -quote <quote>, 54
WIF, 54
WITNESS, 54
beempy-witnessproperties command line
option
-account_creation_fee
<account_creation_fee>, 54
-account_subsidy_budget
<account_subsidy_budget>, 54
-account_subsidy_decay
<account_subsidy_decay>, 54
-maximum_block_size
<maximum_block_size>, 54
-new_signing_key <new_signing_key>,
54
-sbd_interest_rate
<sbd_interest_rate>, 54
-url <url>, 54
WIF, 54
WITNESS, 54
beempy-witnessupdate command line
option
-account_creation_fee
<account_creation_fee>, 55
-maximum_block_size
<maximum_block_size>, 55
-sbd_interest_rate
<sbd_interest_rate>, 55
-signing_key <signing_key>, 55
-url <url>, 55
-witness <witness>, 55
BENEFICIARIES
beempy-beneficiaries command line
option, 22
Beneficiaries (class in beembase.objects), 186
Beneficiary (class in beembase.objects), 186
binary_search() (in module beem-
graphenebase.account), 193
BIP32Key (class in beemgraphenebase.bip32), 194
Block (class in beem.block), 97
block_num (beem.block.Block attribute), 98
block_num (beem.block.BlockHeader attribute), 98
block_time () (beem.blockchain.Blockchain method),
100
block_timestamp () (beem.blockchain.Blockchain
method), 100
blockchain (beem.storage.Configuration attribute),
164
Blockchain (class in beem.blockchain), 99
BlockChainInstance (class
in beem.blockchaininstance), 106
BlockchainObject (class
in beem.blockchainobject), 105
BlockDoesNotExistException, 133
BlockHeader (class in beem.block), 98
BLOCKNUMBER
beempy-verify command line option,
```

51
blocks() (*beem.blockchain.Blockchain method*), 100
BlockWaitTimeExceeded, 133
blog_history() (*beem.account.Account method*), 72
BODY
 beempy-reply command line option, 44
body (*beem.comment.Comment attribute*), 118
BrainKey (*class in beemgraphenebase.account*), 189
broadcast() (*beem.blockchaininstance.BlockChainInstance method*), 107
broadcast() (*beem.hivesigner.HiveSigner method*), 139
broadcast() (*beem.steemconnect.SteemConnect method*), 163
broadcast() (*beem.transactionbuilder.TransactionBuilder method*), 168
btc_usd_ticker() (*beem.market.Market static method*), 143
build() (*beem.snapshot.AccountSnapshot method*), 156
build_apdu() (*beem-graphenebase.unsignedtransactions.Unsigned_Transaktion method*), 198
build_apdu_pubkey() (*beem-graphenebase.unsignedtransactions.Unsigned_Transaktion method*), 198
build_curation_arrays() (*beem.snapshot.AccountSnapshot 157*)
build_path() (*beem-graphenebase.unsignedtransactions.Unsigned_Transaktion method*), 198
build_rep_arrays() (*beem.snapshot.AccountSnapshot 157*)
build_sp_arrays() (*beem.snapshot.AccountSnapshot 157*)
build_vp_arrays() (*beem.snapshot.AccountSnapshot 157*)
buy() (*beem.market.Market method*), 143

C

cache() (*beem.blockchainobject.BlockchainObject method*), 105
CallRetriesReached, 178
cancel() (*beem.market.Market method*), 143
cancel_subscriptions()
 (*beemapi.websocket.NodeWebsocket method*), 184
cancel_transfer_from_savings()
 (*beem.account.Account method*), 73
category (*beem.comment.Comment attribute*), 118

chain_params (*beem.blockchaininstance.BlockChainInstance attribute*), 107
chain_params (*beem.hive.Hive attribute*), 136
chain_params (*beem.steem.Steem attribute*), 159
ChainCode() (*beemgraphenebase.bip32.BIP32Key method*), 194
change_recovery_account()
 (*beem.account.Account method*), 73
changePassphrase() (*beem.wallet.Wallet method*), 173
changePassword() (*beem.storage.MasterPassword method*), 166
check() (*beemgraphenebase.account.Mnemonic method*), 190
check_asset() (*in module beem.amount*), 95
check_asset() (*in module beem.price*), 154
check_word() (*beem-graphenebase.account.Mnemonic 190 method*), 190
checkBackup() (*beem.storage.Configuration method*), 164
ChildKey() (*beemgraphenebase.bip32.BIP32Key method*), 194
CKDpriv() (*beemgraphenebase.bip32.BIP32Key method*), 194
CKDpub() (*beemgraphenebase.bip32.BIP32Key method*), 194
claim_account() (*beem.blockchaininstance.BlockChainInstance method*), 108
claim_account() (*beem.rc.RC method*), 155
claim_reward_balance() (*beem.account.Account method*), 73
clean_data() (*beem.storage.DataDir method*), 165
clear() (*beem.blockchaininstance.BlockChainInstance method*), 108
clear() (*beem.transactionbuilder.TransactionBuilder method*), 168
clear_cache() (*beem.blockchainobject.BlockchainObject static method*), 105
clear_cache() (*in module beem.instance*), 141
clear_cache_from_expired_items()
 (*beem.blockchainobject.BlockchainObject method*), 105
clear_data() (*beem.asciichart.AsciiChart method*), 96
clear_data() (*beem.blockchaininstance.BlockChainInstance method*), 108
clear_expired_items()
 (*beem.blockchainobject.ObjectCache method*), 106
clear_local_keys() (*beem.wallet.Wallet method*), 173

clear_local_token() (beem.wallet.Wallet method), 173
clearWifs() (beem.transactionbuilder.TransactionBuilder method), 168
close() (beem.notify.Notify method), 152
close() (beemapi.websocket.NodeWebSocket method), 184
Comment (class in beem.comment), 118
comment() (beem.rc.RC method), 155
comment_dict() (beem.rc.RC method), 155
Comment_discussions_by_payout (class in beem.discussions), 125
comment_history() (beem.account.Account method), 74
comment_options() (beem.blockchaininstance.BlockChainInstance method), 108
CommentOptionExtensions (class in beem-base.objects), 186
compressed() (beem-graphenebase.account.PublicKey method), 193
compressedpubkey() (beem-graphenebase.account.PrivateKey method), 192
compressedPubkey() (in module beem-graphenebase.ecdsasig), 196
config (beem.instance.SharedInstance attribute), 141
config_defaults (beem.storage.Configuration attribute), 164
config_key (beem.storage.MasterPassword attribute), 166
configStorage (beem.wallet.Wallet attribute), 173
Configuration (class in beem.storage), 164
connect() (beem.blockchaininstance.BlockChainInstance method), 108
construct_authorperm() (in module beem.utils), 169
construct_authorpermvoter() (in module beem.utils), 169
constructTx() (beem.transactionbuilder.TransactionBuilder method), 168
ContentDoesNotExistException, 133
convert() (beem.account.Account method), 74
Conveyor (class in beem.conveyor), 123
copy() (beem.amount.Amount method), 95
copy() (beem.price.Price method), 154
create() (beem.wallet.Wallet method), 173
create_account() (beem.blockchaininstance.BlockChainInstance method), 108
create_claimed_account() (beem.blockchaininstance.BlockChainInstance method), 109
create_claimed_account_dict() (beem.rc.RC
method), 155
create_hot_sign_url() (beem.hivesigner.HiveSigner method), 140
create_hot_sign_url() (beem.steemconnect.SteemConnect method), 163
create_table() (beem.storage.Configuration method), 164
create_table() (beem.storage.Key method), 165
create_table() (beem.storage.Token method), 166
create_ws_instance() (in module beemapi.graphenerpc), 181
created() (beem.wallet.Wallet method), 173
CREATOR
 beempy-claimaccount command line option, 25
curation_penalty_compensation_SBD() (beem.comment.Comment method), 118
curation_stats() (beem.account.Account method), 74
custom_json() (beem.blockchaininstance.BlockChainInstance method), 110
custom_json() (beem.rc.RC method), 155
custom_json_dict() (beem.rc.RC method), 155

D

data_dir (beem.storage.DataDir attribute), 165
DataDir (class in beem.storage), 164
decode_memo() (in module beembase.memo), 185
decode_memo_bts() (in module beembase.memo), 185
decodeRPCErrorMsg() (in module beemapi.exceptions), 179
decrypt() (beem.aes.AESCipher method), 94
decrypt() (beem.memo.Memo method), 150
decrypt() (in module beemgraphenebase.bip38), 195
decrypt_token() (beem.wallet.Wallet method), 173
decrypt_wif() (beem.wallet.Wallet method), 173
decrypted_master (beem.storage.MasterPassword attribute), 166
decryptEncryptedMaster() (beem.storage.MasterPassword method), 166
default_handler() (in module beem.blockchain), 105
delegate_vesting_shares() (beem.account.Account method), 74
delete() (beem.comment.Comment method), 118
delete() (beem.storage.Configuration method), 164
delete() (beem.storage.Key method), 165
delete() (beem.storage.Token method), 167
depth (beem.comment.Comment attribute), 119
derive256address_with_version() (beem-graphenebase.account.Address method), 189

derive_beneficiaries() (*in module beem.utils*), 169
 derive_from_seed() (*beem-graphenebase.account.PrivateKey method*), 192
 derive_permalink() (*in module beem.utils*), 170
 derive_private_key() (*beem-graphenebase.account.PrivateKey method*), 192
 derive_tags() (*in module beem.utils*), 170
 deriveChecksum() (*beem.storage.MasterPassword method*), 166
 deriveChecksum() (*beem.wallet.Wallet method*), 173
 deriveDigest() (*beem-graphenebase.signedtransactions.Signed_Transaction method*), 197
 deriveDigest() (*beem-graphenebase.unsignedtransactions.Unsigned_Transaction method*), 198
 derivesha256address() (*beem-graphenebase.account.Address method*), 189
 derivesha512address() (*beem-graphenebase.account.Address method*), 189
 derSigToHexSig() (*beem-graphenebase.signedtransactions.Signed_Transaction method*), 197
 derSigToHexSig() (*beem-graphenebase.unsignedtransactions.Unsigned_Transaction method*), 198
 disable_node() (*beemapi.node.Nodes method*), 181
 disallow() (*beem.account.Account method*), 75
 disapprovewitness() (*beem.account.Account method*), 75
 Discussions (*class in beem.discussions*), 126
 Discussions_by_active (*class in beem.discussions*), 126
 Discussions_by_author_before_date (*class in beem.discussions*), 126
 Discussions_by_blog (*class in beem.discussions*), 127
 Discussions_by_cashout (*class in beem.discussions*), 127
 Discussions_by_children (*class in beem.discussions*), 128
 Discussions_by_comments (*class in beem.discussions*), 128
 Discussions_by_created (*class in beem.discussions*), 129
 Discussions_by_feed (*class in beem.discussions*), 129
 Discussions_by_hot (*class in beem.discussions*), 129
 Discussions_by_promoted (*beem.discussions*), 130
 Discussions_by_trending (*beem.discussions*), 130
 Discussions_by_votes (*beem.discussions*), 130
 done() (*beem.blockchain.Pool method*), 104
 doublesha256() (*in module beem-graphenebase.base58*), 194
 downvote() (*beem.comment.Comment method*), 119
 dump() (*beemgraphenebase.bip32.BIP32Key method*), 195

E

encrypt() (*beem.aes.AESCipher method*), 94
 encrypt() (*beem.memo.Memo method*), 150
 encrypt() (*in module beemgraphenebase.bip38*), 195
 encrypt_token() (*beem.wallet.Wallet method*), 173
 encrypt_wif() (*beem.wallet.Wallet method*), 173
 enqueue() (*beem.blockchain.Pool method*), 105
 ensure_full() (*beem.account.Account method*), 75
 error_cnt (*beemapi.graphenerpc.GrapheneRPC attribute*), 180
 error_cnt (*beemapi.node.Nodes attribute*), 182
 error_cnt_call (*beemapi.graphenerpc.GrapheneRPC attribute*), 180
 error_cnt_call (*beemapi.node.Nodes attribute*), 182
 estimate_curation_SBD() (*beem.comment.Comment method*), 119
 estimate_virtual_op_num() (*beem.account.Account method*), 75
 ExchangeRate (*class in beembase.objects*), 187
 exists_table() (*beem.storage.Configuration method*), 164
 exists_table() (*beem.storage.Key method*), 165
 exists_table() (*beem.storage.Token method*), 167
 expand() (*beemgraphenebase.account.Mnemonic method*), 190
 expand_word() (*beem-graphenebase.account.Mnemonic method*), 190
 export_working_nodes() (*beemapi.node.Nodes method*), 182
 ExtendedKey() (*beemgraphenebase.bip32.BIP32Key method*), 194
 Extension (*class in beembase.objects*), 187

F

feed_history() (*beem.account.Account method*), 76
feed_publish() (*beem.witness.Witness method*), 177
FilledOrder (*class in beem.price*), 152
finalizeOp() (*beem.blockchaininstance.BlockChainInstance method*), 111
find_change_recovery_account_requests() (*beem.blockchain.Blockchain method*), 100
find_rc_accounts() (*beem.blockchain.Blockchain method*), 100
findall_patch_hunks() (*in module beem.utils*), 170
Fingerprint() (*beemgraphenebase.bip32.BIP32Key method*), 194
FOLLOW
 beempy-follow command line option, 32
follow() (*beem.account.Account method*), 76
FollowApiNotEnabled, 178
FOREIGN_ACCOUNT
 beempy-allow command line option, 21
 beempy-disallow command line option, 30
formatTime() (*in module beem.utils*), 170
formatTimedelta() (*in module beem.utils*), 170
formatTimeFromNow() (*in module beem.utils*), 170
formatTimeString() (*in module beem.utils*), 170
formatToTimeStamp() (*in module beem.utils*), 170
fromEntropy() (*beemgraphenebase.bip32.BIP32Key static method*), 195
fromExtendedKey() (*beemgraphenebase.bip32.BIP32Key static method*), 195

G

generate() (*beemgraphenebase.account.Mnemonic method*), 190
generate_mnemonic() (*beemgraphenebase.account.MnemonicKey method*), 191
get() (*beem.blockchainobject.ObjectCache method*), 106
get() (*beem.storage.Configuration method*), 164
get_access_token() (*beem.hivesigner.HiveSigner method*), 140
get_access_token() (*beem.steemconnect.SteemConnect method*), 163
get_account() (*beemapi.noderpc.NodeRPC method*), 182
get_account_bandwidth() (*beem.account.Account method*), 76
get_account_count() (*beem.blockchain.Blockchain method*), 101
get_account_history() (*beem.account.Account method*), 76
get_account_history() (*beem.snapshot.AccountSnapshot method*), 157
get_account_posts() (*beem.account.Account method*), 77
get_account_reputations() (*beem.blockchain.Blockchain method*), 101
get_account_votes() (*beem.account.Account method*), 77
get_all_accounts() (*beem.blockchain.Blockchain method*), 101
get_all_replies() (*beem.comment.Comment method*), 119
get_api_methods() (*beem.blockchaininstance.BlockChainInstance method*), 111
get_apis() (*beem.blockchaininstance.BlockChainInstance method*), 111
get_author_rewards() (*beem.comment.Comment method*), 119
get_authority_byte_count() (*beem.rc.RC method*), 155
get_balance() (*beem.account.Account method*), 77
get_balances() (*beem.account.Account method*), 78
get_bandwidth() (*beem.account.Account method*), 78
get_beneficiaries_pct() (*beem.comment.Comment method*), 119
get_blind_private() (*beemgraphenebase.account.BrainKey method*), 190
get_block_interval() (*beem.blockchaininstance.BlockChainInstance method*), 111
get_blockchain_name() (*beem.blockchaininstance.BlockChainInstance method*), 111
get_blockchain_version() (*beem.blockchaininstance.BlockChainInstance method*), 111
get_blog() (*beem.account.Account method*), 78
get_blog_authors() (*beem.account.Account method*), 79
get_blog_entries() (*beem.account.Account method*), 79
get_brainkey() (*beemgraphenebase.account.BrainKey method*), 190
get_cache_auto_clean() (*beem.blockchainobject.BlockchainObject method*), 105
get_cache_expiration()

```

(beem.blockchainobject.BlockchainObject
method), 105
get_chain_properties()
    (beem.blockchaininstance.BlockChainInstance
method), 111
get_config() (beem.blockchaininstance.BlockChainInstance
method), 112
get_conversion_requests()
    (beem.account.Account method), 79
get_creator() (beem.account.Account method), 80
get_curation_penalty()
    (beem.comment.Comment method), 119
get_curation_reward() (beem.account.Account
method), 80
get_curation_rewards()
    (beem.comment.Comment method), 120
get_current_block()
    (beem.blockchain.Blockchain method), 101
get_current_block_num()
    (beem.blockchain.Blockchain method), 101
get_current_median_history()
    (beem.blockchaininstance.BlockChainInstance
method), 112
get_data() (beem.snapshot.AccountSnapshot
method), 157
get_default_config_storage() (in module
beem.storage), 167
get_default_key_storage() (in module
beem.storage), 167
get_default_nodes()
    (beem.blockchaininstance.BlockChainInstance
method), 112
get_default_token_storage() (in module
beem.storage), 167
get_discussions() (beem.discussions.Discussions
method), 126
get_downvote_manabar() (beem.account.Account
method), 80
get_downvoting_power() (beem.account.Account
method), 80
get_dust_threshold()
    (beem.blockchaininstance.BlockChainInstance
method), 112
get_dynamic_global_properties()
    (beem.blockchaininstance.BlockChainInstance
method), 112
get_effective_vesting_shares()
    (beem.account.Account method), 80
get_escrow() (beem.account.Account method), 80
get_estimated_block_num()
    (beem.blockchain.Blockchain method), 101
get_expiring_vesting_delegations()
    (beem.account.Account method), 80
get_feature_flag() (beem.conveyor.Conveyor
method), 123
get_feature_flags() (beem.conveyor.Conveyor
method), 123
get_feed() (beem.account.Account method), 81
get_feed_entries() (beem.account.Account
method), 81
get_feed_history()
    (beem.blockchaininstance.BlockChainInstance
method), 112
get_follow_count() (beem.account.Account
method), 82
get_followers() (beem.account.Account method),
82
get_following() (beem.account.Account method),
82
get_hardfork_properties()
    (beem.blockchaininstance.BlockChainInstance
method), 112
get_hbd_per_rshares() (beem.hive.Hive
method), 136
get_hive_nodes() (beem.nodelist.NodeList
method), 150
get_hive_per_mvest() (beem.hive.Hive method),
136
get_list() (beem.vote.VotesObject method), 172
get_login_url() (beem.hivesigner.HiveSigner
method), 140
get_login_url() (beem.steemconnect.SteemConnect
method), 163
get_manabar() (beem.account.Account method), 82
get_manabar_recharge_time()
    (beem.account.Account method), 82
get_manabar_recharge_time_str()
    (beem.account.Account method), 82
get_manabar_recharge_timedelta()
    (beem.account.Account method), 82
get_median_price()
    (beem.blockchaininstance.BlockChainInstance
method), 112
get_muters() (beem.account.Account method), 82
get_mutings() (beem.account.Account method), 82
get_network() (beem.blockchaininstance.BlockChainInstance
method), 112
get_network() (beem.hive.Hive method), 136
get_network() (beem.steem.Steem method), 159
get_network() (beemapi.graphenerpc.GrapheneRPC
method), 180
get_nodes() (beem.nodelist.NodeList method), 151
get_notifications() (beem.account.Account
method), 82
get_ops() (beem.snapshot.AccountSnapshot method),
157
get_owner_history() (beem.account.Account
method), 82

```

```

get_parent() (beem.comment.Comment method), graphenebase.account.PublicKey method),  
120 193
get_parent() (beem.transactionbuilder.TransactionBuilder method), get_rc() (beem.account.Account method), 83  
168 get_rc_cost() (beem.blockchaininstance.BlockChainInstance method), 112
get_path() (beemgraphenebase.account.MnemonicKey method), get_rc_manabar() (beem.account.Account method),  
191 83
get_potential_signatures() get_reblogged_by() (beem.comment.Comment method), 120
(beem.transactionbuilder.TransactionBuilder method), 168 get_recharge_time() (beem.account.Account method),  
190 83
get_private() (beem- get_recharge_time_str() (beem.account.Account method), 83
graphenebase.account.BrainKey method), get_recharge_timedelta() (beem.account.Account method), 83
190 get_recovery_request() (beem.account.Account method), 83
get_private() (beem- get_replies() (beem.comment.Comment method),  
graphenebase.account.MnemonicKey method), 120
191 get_reputation() (beem.account.Account method),  
190 84
get_private() (beem- get_request_id() (beemapi.graphenerpc.GrapheneRPC method), 180
graphenebase.account.PasswordKey method), get_request_id() (beemapi.websocket.NodeWebsocket method), 184
get_private_key() (beem- get_required_signatures() (beem.transactionbuilder.TransactionBuilder method), 168
graphenebase.account.BrainKey method), get_reserve_ratio()  
190 (beem.blockchaininstance.BlockChainInstance method), 112
get_private_key() (beem- get_resource_count() (beem.rc.RC method), 156
graphenebase.account.MnemonicKey method), get_resource_params()  
191 (beem.blockchaininstance.BlockChainInstance method), 112
get_pubkey() (beem- get_resource_pool()  
base.ledgertransactions.Ledger_Transaction (beem.blockchaininstance.BlockChainInstance method), 113
method), 189 get_reward_funds()  
(beem.blockchaininstance.BlockChainInstance method), 113
get_public() (beem- get_rewards() (beem.comment.Comment method),  
graphenebase.account.BrainKey method), 120
190 get_savings_withdrawals()  
(beem.account.Account method), 84
get_public() (beem- get_sbd_per_rshares() (beem.steem.Steem method), 159
graphenebase.account.MnemonicKey method),  
191 get_secret()  
(beem.graphenebase.account.PrivateKey method),  
192
get_public_key() (beem- get_shared_secret() (in module beem-  
graphenebase.account.PasswordKey method), 186
base.memo), 186
get_public_key() (beem- get_similar_account_names()  
graphenebase.account.PrivateKey method), 192  
(beem.account.Account method), 84
get_public_key()

```

```

get_similar_account_names()
    (beem.blockchain.Blockchain method, 102)
get_sorted_list()          (beem.vote.VotesObject
    method), 172
get_steam_nodes()          (beem.nodelist.NodeList
    method), 151
get_steam_per_mvest()      (beem.steem.Steem
    method), 159
get_steam_power()          (beem.account.Account
    method), 84
get_string() (beem.market.Market method), 144
get_tags_used_by_author()
    (beem.account.Account method), 84
get_testnet() (beem.nodelist.NodeList method),
    151
get_token_power()          (beem.account.Account
    method), 84
get_transaction()          (beem.blockchain.Blockchain
    method), 102
get_transaction_hex()
    (beem.blockchain.Blockchain method), 102
get_transaction_hex()
    (beem.transactionbuilder.TransactionBuilder
    method), 168
get_tx_size() (beem.rc.RC method), 156
get_use_appbase()
    (beemapi.graphenerpc.GrapheneRPC method),
    180
get_user_data()            (beem.conveyor.Conveyor
    method), 124
get_vesting_delegations()
    (beem.account.Account method), 84
get_vests() (beem.account.Account method), 85
get_vote() (beem.account.Account method), 85
get_vote_pct_for_SBD()    (beem.account.Account
    method), 85
get_vote_pct_for_vote_value()
    (beem.account.Account method), 85
get_vote_with_curation()
    (beem.comment.Comment method), 121
get_votes() (beem.comment.Comment method), 121
get_votes_sum()            (beem.witness.WitnessesObject
    method), 178
get_voting_power()          (beem.account.Account
    method), 85
get_voting_value()          (beem.account.Account
    method), 85
get_voting_value_SBD()     (beem.account.Account
    method), 85
get_withdraw_routes()       (beem.account.Account
    method), 85
get_witness_schedule()
    (beem.blockchaininstance.BlockChainInstance
    method), 113
getAccount() (beem.wallet.Wallet method), 173
getAccountFromPrivateKey()
    (beem.wallet.Wallet method), 173
getAccountFromPublicKey()
    (beem.wallet.Wallet method), 174
getAccounts() (beem.wallet.Wallet method), 174
getAccountsFromPublicKey()
    (beem.wallet.Wallet method), 174
getActiveKeyForAccount()   (beem.wallet.Wallet
    method), 174
getActiveKeysForAccount()
    (beem.wallet.Wallet method), 174
getAllAccounts()           (beem.wallet.Wallet method),
    174
getBlockParams()           (in module beem-
    base.transactions), 189
getcache() (beem.blockchainobject.BlockchainObject
    method), 105
getChainParams()            (beem-
    graphenebase.signedtransactions.Signed_Transaction
    method), 197
getChainParams()            (beem-
    graphenebase.unsignedtransactions.Unsigned_Transaction
    method), 198
getEncryptedMaster()        (beem.storage.MasterPassword
    method), 166
getKeyForAccount()          (beem.wallet.Wallet method),
    174
getKeysForAccount()          (beem.wallet.Wallet
    method), 174
getKeyType() (beem.wallet.Wallet method), 174
getKnownChains()            (beem-
    base.ledgertransactions.Ledger_Transaction
    method), 189
getKnownChains()            (beem-
    graphenebase.signedtransactions.Signed_Transaction
    method), 188
getKnownChains()            (beem-
    graphenebase.signedtransactions.Signed_Transaction
    method), 197
getKnownChains()            (beem-
    graphenebase.unsignedtransactions.Unsigned_Transaction
    method), 198
getMemoKeyForAccount()       (beem.wallet.Wallet
    method), 174
getOperationKlass()          (beem-
    base.ledgertransactions.Ledger_Transaction
    method), 189
getOperationKlass()          (beem-
    base.signedtransactions.Signed_Transaction
    method), 188
getOperationKlass()          (beem-
    graphenebase.signedtransactions.Signed_Transaction
    method)

```

method), 197
getOperationKlass() (beem-graphenebase.unsignedtransactions.Unsigned_Transaction_vote_pct method), 198
getOperationNameForId() (beem-base.objects.Operation method), 187
getOperationNameForId() (beem-graphenebase.objects.Operation method), 196
getOperationNameForId() (in module beem-base.operationids), 188
getOwnerKeyForAccount() (beem-wallet.Wallet method), 174
getOwnerKeysForAccount() (beem-wallet.Wallet method), 174
getPostingKeyForAccount() (beem-wallet.Wallet method), 174
getPostingKeysForAccount() (beem-wallet.Wallet method), 175
getPrivateKeyForPublicKey() (beem-storage.Key method), 165
getPrivateKeyForPublicKey() (beem-wallet.Wallet method), 175
getPublicKeys() (beem-storage.Key method), 166
getPublicKeys() (beem-wallet.Wallet method), 175
getPublicNames() (beem-storage.Token method), 167
getPublicNames() (beem-wallet.Wallet method), 175
getSimilarAccountNames() (beem-account.Account method), 76
getTokenForAccountName() (beem-wallet.Wallet method), 175
getTokenForPublicName() (beem-storage.Token method), 167
GetWitnesses (class in beem.witness), 176
gphBase58CheckDecode() (in module beem-graphenebase.base58), 194
gphBase58CheckEncode() (in module beem-graphenebase.base58), 194
GrapheneObject (class in beem-graphenebase.objects), 196
GrapheneObjectASN1 (class in beem-graphenebase.unsignedtransactions), 197
GrapheneRPC (class in beemapi.graphenerpc), 180

H

hardfork (beem-blockchaininstance.BlockChainInstance attribute), 113
hardfork (beem-hive.Hive attribute), 136
hardfork (beem-steem.Steem attribute), 160
has_voted() (beem-account.Account method), 86
hash_op() (beem-blockchain.Blockchain static method), 102
hbd_symbol (beem-hive.Hive attribute), 136
hbd_to_rshares() (beem-hive.Hive method), 136
headers (beem-hivesigner.HiveSigner attribute), 140
headers (beem-steemconnect.SteemConnect attribute), 163
healthcheck() (beem-conveyor.Conveyor method), 124
history() (beem-account.Account method), 86
history_reverse() (beem-account.Account method), 87
Hive (class in beem-hive), 134
hive_btc_ticker() (beem-market.Market static method), 144
hive_symbol (beem-hive.Hive attribute), 137
hive_usd_implied() (beem-market.Market method), 144
HiveSigner (class in beem-hivesigner), 139
hmac() (beemgraphenebase.bip32.BIP32Key method), 195
hp_to_hbd() (beem-hive.Hive method), 137
hp_to_rshares() (beem-hive.Hive method), 137
hp_to_vests() (beem-hive.Hive method), 137

I

id (beem-comment.Comment attribute), 121
id (beemgraphenebase.signedtransactions.Signed_Transaction attribute), 197
id (beemgraphenebase.unsignedtransactions.Unsigned_Transaction attribute), 198
IDENTIFIER
beempy-reblog command line option, 44
Identifier() (beemgraphenebase.bip32.BIP32Key method), 194
idle() (beem-blockchain.Pool method), 105
IMAGE
beempy-uploadimage command line option, 49
ImageUploader (class in beem-imageuploader), 141
increase_error_cnt() (beemapi.node.Nodes method), 182
increase_error_cnt_call() (beemapi.node.Nodes method), 182
info() (beem-blockchaininstance.BlockChainInstance method), 113
init_aes() (in module beembase.memo), 186
init_aes_bts() (in module beembase.memo), 186
instance (beem-instance.SharedInstance attribute), 141
instance (beemapi.graphenerpc.SessionInstance attribute), 181
InsufficientAuthorityError, 133

int_to_hex() (*in module beemgraphenebase.bip32*), 195
 interest() (*beem.account.Account method*), 88
 InvalidAssetException, 133
 InvalidEndpointUrl, 178
 InvalidMemoKeyException, 133
 InvalidMessageSignature, 133
 InvalidWifiError, 133
 invert() (*beem.price.Price method*), 154
 is_active (*beem.witness.Witness attribute*), 177
 is_appbase_ready()
 (*beemapi.graphenerpc.GrapheneRPC method*), 181
 is_comment() (*beem.comment.Comment method*), 121
 is_connected() (*beem.blockchaininstance.BlockChainInstance method*), 113
 is_empty() (*beem.transactionbuilder.TransactionBuilder method*), 169
 is_fully_loaded (*beem.account.Account attribute*), 88
 is_hive (*beem.blockchaininstance.BlockChainInstance attribute*), 113
 is_hive (*beem.hive.Hive attribute*), 137
 is_irreversible_mode()
 (*beem.blockchain.Blockchain method*), 102
 is_main_post() (*beem.comment.Comment method*), 121
 is_pending() (*beem.comment.Comment method*), 121
 is_steam (*beem.blockchaininstance.BlockChainInstance attribute*), 113
 is_steam (*beem.steem.Steem attribute*), 160
 isArgsThisClass() (*in module beemgraphenebase.objects*), 196
 iscached() (*beem.blockchainobject.BlockchainObject method*), 105
 items() (*beem.blockchainobject.BlockchainObject method*), 105
 items() (*beem.storage.Configuration method*), 164

J

join() (*beem.blockchain.Pool method*), 105
 json() (*beem.account.Account method*), 88
 json() (*beem.amount.Amount method*), 95
 json() (*beem.block.Block method*), 98
 json() (*beem.block.BlockHeader method*), 98
 json() (*beem.blockchainobject.BlockchainObject method*), 105
 json() (*beem.comment.Comment method*), 121
 json() (*beem.price.FilledOrder method*), 152
 json() (*beem.price.Price method*), 154
 json() (*beem.transactionbuilder.TransactionBuilder method*), 169

json() (*beem.vote.Vote method*), 171
 json() (*beem.witness.Witness method*), 177
 json() (*beembase.objects.Operation method*), 187
 json() (*beemgraphenebase.objects.GrapheneObject method*), 196
 json() (*beemgraphenebase.unsignedtransactions.GrapheneObjectASNI method*), 197
 JSON_DATA
 beempy-customjson command line option, 28
 json_metadata (*beem.account.Account attribute*), 88
 json_metadata (*beem.comment.Comment attribute*), 121
 json_operations (*beem.block.Block attribute*), 98
 json_transactions (*beem.block.Block attribute*), 98
 JSONID
 beempy-customjson command line option, 28

K

KEY
 beempy-set command line option, 46
 Key (*class in beem.storage*), 165
 keyMap (*beem.wallet.Wallet attribute*), 175
 keys (*beem.wallet.Wallet attribute*), 175
 keyStorage (*beem.wallet.Wallet attribute*), 175

L

Ledger_Transaction (*class in beembase.ledgertransactions*), 188
 list_all_subscriptions()
 (*beem.account.Account method*), 88
 list_change_recovery_account_requests()
 (*beem.blockchain.Blockchain method*), 102
 list_drafts() (*beem.conveyor.Conveyor method*), 124
 list_operations()
 (*beem.transactionbuilder.TransactionBuilder method*), 169
 listen() (*beem.notify.Notify method*), 152
 ListWitnesses (*class in beem.witness*), 176
 load_dirty_json() (*in module beem.utils*), 170
 lock() (*beem.wallet.Wallet method*), 175
 locked() (*beem.wallet.Wallet method*), 175
 log (*in module beemgraphenebase.base58*), 194

M

make_patch() (*in module beem.utils*), 170
 mark_notifications_as_read()
 (*beem.account.Account method*), 88
 MARKDOWN_FILE
 beempy-post command line option, 41
 market (*beem.price.Price attribute*), 154

Market (*class in beem.market*), 142
 market_history () (*beem.market.Market method*), 144
 market_history_buckets ()
 (*beem.market.Market method*), 144
 MasterPassword (*beem.wallet.Wallet attribute*), 173
 masterpassword (*beem.wallet.Wallet attribute*), 175
 MasterPassword (*class in beem.storage*), 166
 me () (*beem.hivesigner.HiveSigner method*), 140
 me () (*beem.steemconnect.SteemConnect method*), 163
 MEMO
 beempy-transfer command line
 option, 48
 Memo (*class in beem.memo*), 148
 Memo (*class in beembase.objects*), 187
 Message (*class in beem.message*), 150
 MissingKeyError, 133
 MissingRequiredActiveAuthority, 178
 mkdir_p () (*beem.storage.DataDir method*), 165
 Mnemonic (*class in beemgraphenebase.account*), 190
 MnemonicKey (*class in beemgraphenebase.account*), 191
 move_current_node_to_front ()
 (*beem.blockchaininstance.BlockChainInstance method*), 113
 MUTE
 beempy-mute command line option, 36
 mute () (*beem.account.Account method*), 89

N

NAME
 beempy-addtoken command line
 option, 21
 beempy-deltoken command line
 option, 30
 name (*beem.account.Account attribute*), 89
 new_chart () (*beem.asciichart.AsciiChart method*), 96
 NEW_RECOVERY_ACCOUNT
 beempy-changerecovery command line
 option, 24
 new_tx () (*beem.blockchaininstance.BlockChainInstance method*), 113
 newMaster () (*beem.storage.MasterPassword method*), 166
 newWallet () (*beem.blockchaininstance.BlockChainInstance method*), 113
 newWallet () (*beem.wallet.Wallet method*), 175
 next () (*beemapi.graphenerpc.GrapheneRPC method*), 181
 next () (*beemapi.node.Nodes method*), 182
 next_account_sequence () (*beemgraphenebase.account.MnemonicKey method*), 191
 next_sequence ()
 (*beemgraphenebase.account.BrainKey method*), 190
 next_sequence () (*beemgraphenebase.account.MnemonicKey method*), 191
 NoAccessApi, 178
 NoApiWithName, 179
 node (*beemapi.node.Nodes attribute*), 182
 Node (*class in beemapi.node*), 181
 nodelist (*beem.storage.Configuration attribute*), 164
 NodeList (*class in beem.nodelist*), 150
 NodeRPC (*class in beemapi.noderpc*), 182
 nodes (*beem.storage.Configuration attribute*), 164
 Nodes (*class in beemapi.node*), 181
 NodeWebsocket (*class in beemapi.websocket*), 183
 NoMethodWithName, 179
 normalize () (*beemgraphenebase.account.BrainKey method*), 190
 normalize () (*beemgraphenebase.account.PasswordKey method*), 191
 normalize_string () (*beemgraphenebase.account.Mnemonic class method*), 190
 Notify (*class in beem.notify*), 151
 NoWalletException, 133
 NoWriteAccess, 133
 num_retries (*beemapi.graphenerpc.GrapheneRPC attribute*), 181
 num_retries_call (*beemapi.graphenerpc.GrapheneRPC attribute*), 181
 num_retries_call_reached
 (*beemapi.node.Nodes attribute*), 182
 NumRetriesReached, 179

O

object_type (*in module beembase.objecttypes*), 187
 object_type (*in module beemgraphenebase.objecttypes*), 196
 ObjectCache (*class in beem.blockchainobject*), 106
 OBJECTS
 beempy-info command line option, 34
 OfflineHasNRPCEException, 133
 on_close () (*beemapi.websocket.NodeWebsocket method*), 184
 on_error () (*beemapi.websocket.NodeWebsocket method*), 184
 on_message () (*beemapi.websocket.NodeWebsocket method*), 184
 on_open () (*beemapi.websocket.NodeWebsocket method*), 184
 Operation (*class in beembase.objects*), 187
 Operation (*class in beemgraphenebase.objects*), 196

operations (*beem.block.Block attribute*), 98
 operations (in module *beem-graphenebase.operationids*), 196
 operations () (*beembase.objects.Operation method*), 187
 operations () (*beemgraphenebase.objects.Operation method*), 196
 ops (in module *beembase.operationids*), 188
 ops () (*beem.blockchain.Blockchain method*), 103
 ops_statistics () (*beem.block.Block method*), 98
 ops_statistics () (*beem.blockchain.Blockchain method*), 103
 Order (*class in beem.price*), 152
 orderbook () (*beem.market.Market method*), 144
 ORDERID
 beempy-cancel command line option, 23

P

P2WPKHoP2SHAddress ()
 (*beem-graphenebase.bip32.BIP32Key method*), 194
 parent_author (*beem.comment.Comment attribute*), 121
 parent_permalink (*beem.comment.Comment attribute*), 121
 parse_op () (*beem.snapshot.AccountSnapshot method*), 157
 parse_path () (in module *beemgraphenebase.bip32*), 195
 parse_time () (in module *beem.utils*), 170
 password (*beem.storage.MasterPassword attribute*), 166
 PasswordKey (*class in beemgraphenebase.account*), 191
 percent (*beem.vote.Vote attribute*), 171
 Permission (*class in beembase.objects*), 187
 PERMLINK
 beempy-download command line option, 31
 permalink (*beem.comment.Comment attribute*), 121
 plot () (*beem.asciichart.AsciiChart method*), 96
 point () (*beemgraphenebase.account.PublicKey method*), 193
 Pool (*class in beem.blockchain*), 104
 POST
 beempy-delete command line option, 29
 beempy-downvote command line option, 32
 beempy-upvote command line option, 50
 post () (*beem.blockchaininstance.BlockChainInstance method*), 113
 Post_discussions_by_payout (class in *beem.discussions*), 131
 posting_json_metadata (*beem.account.Account attribute*), 89
 precision (*beem.asset.Asset attribute*), 97
 prefix (*beem.blockchaininstance.BlockChainInstance attribute*), 114
 prefix (*beem.wallet.Wallet attribute*), 175
 prehash_message () (*beem.conveyor.Conveyor method*), 124
 PRICE
 beempy-buy command line option, 23
 beempy-sell command line option, 45
 Price (*class in beem.price*), 152
 Price (*class in beembase.objects*), 187
 print_info () (*beem.account.Account method*), 89
 print_stats () (*beem.vote.VotesObject method*), 172
 print_summarize_table ()
 (*beem.account.AccountsObject method*), 93
 printAsTable () (*beem.account.AccountsObject method*), 93
 printAsTable () (*beem.vote.VotesObject method*), 172
 printAsTable () (*beem.witness.WitnessesObject method*), 178
 PrivateKey (*class in beemgraphenebase.account*), 192
 PrivateKey () (*beemgraphenebase.bip32.BIP32Key method*), 194
 process_block () (*beem.notify.Notify method*), 152
 process_block () (*beemapi.websocket.NodeWebsocket method*), 184
 profile (*beem.account.Account attribute*), 89
 PROXY
 beempy-setproxy command line option, 46
 PUB
 beempy-delkey command line option, 29
 PUB_SIGNING_KEY
 beempy-witnesscreate command line option, 52
 PublicKey (*class in beemgraphenebase.account*), 192
 PublicKey () (*beemgraphenebase.bip32.BIP32Key method*), 194

Q

quantize () (in module *beem.amount*), 95
 Query (*class in beem.discussions*), 131

R

RankedPosts (*class in beem.comment*), 122
 RC (*class in beem.rc*), 155

recent_trades() (*beem.market.Market method*), 145
RecentByPath (*class in beem.comment*), 122
RecentReplies (*class in beem.comment*), 122
recover_public_key() (*in module beem-graphenebase.ecdsasig*), 196
recover_with_latest_backup() (*beem.storage.DataDir method*), 165
recoverPubkeyParameter() (*in module beem-graphenebase.ecdsasig*), 196
refresh() (*beem.account.Account method*), 89
refresh() (*beem.asset.Asset method*), 97
refresh() (*beem.block.Block method*), 98
refresh() (*beem.block.BlockHeader method*), 98
refresh() (*beem.comment.Comment method*), 121
refresh() (*beem.vote.Vote method*), 171
refresh() (*beem.witness.Witness method*), 177
refresh() (*beem.witness.Witnesses method*), 177
refresh_access_token() (*beem.hivesigner.HiveSigner method*), 140
refresh_access_token() (*beem.steemconnect.SteemConnect method*), 163
refresh_data() (*beem.blockchaininstance.BlockChainInstance method*), 114
refreshBackup() (*beem.storage.DataDir method*), 165
remove_draft() (*beem.conveyor.Conveyor method*), 125
remove_from_dict() (*in module beem.utils*), 170
removeAccount() (*beem.wallet.Wallet method*), 175
removePrivateKeyFromPublicKey() (*beem.wallet.Wallet method*), 175
removeTokenFromPublicName() (*beem.wallet.Wallet method*), 175
rep (*beem.account.Account attribute*), 89
rep (*beem.vote.Vote attribute*), 171
Replies_by_last_update (*class in beem.discussions*), 132
reply() (*beem.comment.Comment method*), 121
reply_history() (*beem.account.Account method*), 89
reputation (*beem.vote.Vote attribute*), 171
reputation_to_score() (*in module beem.utils*), 170
request_send() (*beemapi.graphenerpc.GrapheneRPC method*), 181
reset() (*beem.snapshot.AccountSnapshot method*), 157
reset_error_cnt() (*beemapi.node.Nodes method*), 182
reset_error_cnt_call() (*beemapi.node.Nodes method*), 182
reset_subscriptions() (*beem.notify.Notify* method), 152
reset_subscriptions() (*beemapi.websocket.NodeWebsocket method*), 184
resolve_authorperm() (*in module beem.utils*), 170
resolve_authorpermvoter() (*in module beem.utils*), 170
resolve_root_identifier() (*in module beem.utils*), 171
resteem() (*beem.comment.Comment method*), 121
results() (*beem.blockchain.Pool method*), 105
revoke_token() (*beem.hivesigner.HiveSigner method*), 140
revoke_token() (*beem.steemconnect.SteemConnect method*), 164
reward (*beem.comment.Comment attribute*), 122
reward_balances (*beem.account.Account attribute*), 89
ripemd160() (*in module beemgraphenebase.base58*), 194
rpc (*beem.wallet.Wallet attribute*), 175
rpcclose() (*beemapi.graphenerpc.GrapheneRPC method*), 181
rpcconnect() (*beemapi.graphenerpc.GrapheneRPC method*), 181
RPCConnection, 179
RPCConnectionRequired, 133
RPCError, 179
RPCErrorDoRetry, 179
rpccexec() (*beemapi.graphenerpc.GrapheneRPC method*), 181
rpccexec() (*beemapi.noderpc.NodeRPC method*), 182
rpccexec() (*beemapi.websocket.NodeWebsocket method*), 184
rpcclogin() (*beemapi.graphenerpc.GrapheneRPC method*), 181
rshares (*beem.vote.Vote attribute*), 171
rshares_to_hbd() (*beem.hive.Hive method*), 138
rshares_to_sbd() (*beem.steem.Steem method*), 160
rshares_to_vote_pct() (*beem.hive.Hive method*), 138
rshares_to_vote_pct() (*beem.steem.Steem method*), 160
run() (*beem.blockchain.Pool method*), 105
run() (*beem.blockchain.Worker method*), 105
run_forever() (*beemapi.websocket.NodeWebsocket method*), 184

S

SaltException, 195
sanitize_permalink() (*in module beem.utils*), 171
save_draft() (*beem.conveyor.Conveyor method*), 125

```

saveEncrytpedMaster()                               method), 191
    (beem.storage.MasterPassword      method), 191
    166
saving_balances (beem.account.Account attribute), 191
    89
sbd (beem.vote.Vote attribute), 172
sbd_symbol (beem.steem.Steem attribute), 160
sbd_to_rshares () (beem.steem.Steem method), 160
sbd_to_vote_pct () (beem.steem.Steem method), 160
search () (beem.snapshot.AccountSnapshot method), 157
searchPath () (beem.transactionbuilder.TransactionBuilder method), 169
sell () (beem.market.Market method), 146
seperate_yaml_dict_from_body () (in module
    beem.utils), 171
SessionInstance (class in beemapi.graphenerpc), 181
set_access_token () (beem.hivesigner.HiveSigner method), 140
set_access_token () (beem.steemconnect.SteemConnect method), 164
set_cache_auto_clean () (beem.blockchainobject.BlockchainObject method), 105
set_cache_expiration () (beem.blockchainobject.BlockchainObject method), 105
set_default_account () (beem.blockchaininstance.BlockChainInstance method), 115
set_default_nodes () (beem.blockchaininstance.BlockChainInstance method), 115
set_default_vote_weight () (beem.blockchaininstance.BlockChainInstance method), 115
set_expiration () (beem.transactionbuilder.TransactionBuilder method), 169
set_mnemonic () (beemgraphenebase.account.MnemonicKey method), 191
set_next_node_on_empty_reply () (beemapi.noderpc.NodeRPC method), 183
set_node_urls () (beemapi.node.Nodes method), 182
set_parameter () (beem.asciichart.AsciiChart method), 96
set_password_storage () (beem.blockchaininstance.BlockChainInstance method), 115
set_path () (beemgraphenebase.account.MnemonicKey sign () (beemgraphenebase.signedtransactions.SignedTransaction
    method), 191
    (beemgraphenebase.account.MnemonicKey method), 191
    191
    set_path_BIP44 () (beemgraphenebase.account.MnemonicKey method), 191
    191
    set_path_BIP48 () (beemgraphenebase.account.MnemonicKey method), 191
    191
    set_session_instance () (in module
        beemapi.graphenerpc), 181
    set_shared_blockchain_instance () (in module
        beem.instance), 141
    set_shared_config () (in module beem.instance), 141
    set_shared_hive_instance () (in module
        beem.instance), 141
    set_shared_steam_instance () (in module
        beem.instance), 141
    set_user_data () (beem.conveyor.Conveyor method), 125
    set_username () (beem.hivesigner.HiveSigner method), 140
    set_username () (beem.steemconnect.SteemConnect method), 164
    set_withdraw_vesting_route () (beem.account.Account method), 90
    setKeys () (beem.wallet.Wallet method), 175
    setPath () (beem.transactionbuilder.TransactionBuilder method), 169
    setproxy () (beem.account.Account method), 90
    SetPublic () (beemgraphenebase.bip32.BIP32Key method), 195
    setToken () (beem.wallet.Wallet method), 175
    shared_blockchain_instance () (in module
        beem.instance), 141
    shared_hive_instance () (in module
        beem.instance), 142
    shared_steam_instance () (in module
        beem.instance), 142
    SharedInstance (class in beem.instance), 141
    sign () (beem.blockchaininstance.BlockChainInstance method), 115
    sign () (beem.message.Message method), 150
    sign () (beem.transactionbuilder.TransactionBuilder method), 169
    sign () (beembase.ledgertransactions.Ledger_Transaction method), 189
    sign () (beembase.signedtransactions.Signed_Transaction method), 188
    sign () (beemgraphenebase.signedtransactions.Signed_Transaction
        method), 188

```

method), 197
sign_message() (in module graphenebase.ecdsasig), 196
Signed_Transaction (class in beem.base.signedtransactions), 188
Signed_Transaction (class in beem.graphenebase.signedtransactions), 197
SIGNING_KEY
 beempy-witnessenable command line option, 53
sleep_and_check_retries()
 (beemapi.node.Nodes method), 182
SocialActionCommentCreate (class in beem.base.objects), 187
SocialActionCommentDelete (class in beem.base.objects), 187
SocialActionCommentUpdate (class in beem.base.objects), 187
SocialActionVariant (class in beembase.objects), 187
sp (beem.account.Account attribute), 90
sp_to_rshares() (beem.steem.Steem method), 160
sp_to_sbd() (beem.steem.Steem method), 161
sp_to_vests() (beem.steem.Steem method), 161
space_id (beem.blockchainobject.BlockchainObject attribute), 105
sqlDataBaseFile (beem.storage.DataDir attribute), 165
sqlite3_backup() (beem.storage.DataDir method), 165
sqlite3_copy() (beem.storage.DataDir method), 165
Steem (class in beem.steem), 158
steem_btc_ticker() (beem.market.Market static method), 146
steem_symbol (beem.steem.Steem attribute), 161
steem_usd_implied() (beem.market.Market method), 147
SteemConnect (class in beem.steemconnect), 162
stop() (beemapi.websocket.NodeWebsocket method), 184
storageDatabase (beem.storage.DataDir attribute), 165
str_to_bytes() (beem.aes.AESCipher static method), 94
stream() (beem.blockchain.Blockchain method), 103
suggest() (beemgraphenebase.account.BrainKey method), 190
switch_blockchain()
 (beem.blockchaininstance.BlockChainInstance method), 115
symbol (beem.amount.Amount attribute), 95
symbol (beem.asset.Asset attribute), 97
symbols() (beem.price.Price method), 154

T

beem-
test() (in module beemgraphenebase.bip32), 195
test_valid_objectid()
 (beem.blockchainobject.BlockchainObject method), 105
testid() (beem.blockchainobject.BlockchainObject method), 105
ticker() (beem.market.Market method), 147
time (beem.vote.Vote attribute), 172
time() (beem.block.Block method), 98
time() (beem.block.BlockHeader method), 99
time_elapsed() (beem.comment.Comment method), 122
TimeoutException, 179
title (beem.comment.Comment attribute), 122
TO
 beempy-powerdownroute command line option, 42
 beempy-transfer command line option, 48
TO_ACCOUNT
 beempy-delegate command line option, 28
to_entropy()
 (beem-graphenebase.account.Mnemonic method), 191
to_mnemonic()
 (beem-graphenebase.account.Mnemonic method), 191
to_seed()
 (beemgraphenebase.account.Mnemonic class method), 191
toJson()
 (beemgraphenebase.objects.GrapheneObject method), 196
toJson()
 (beemgraphenebase.unsignedtransactions.GrapheneObjectASN method), 197
token (beem.wallet.Wallet attribute), 175
Token (class in beem.storage), 166
token_symbol (beem.blockchaininstance.BlockChainInstance attribute), 115
tokenStorage (beem.wallet.Wallet attribute), 175
total_balances (beem.account.Account attribute), 90
tp (beem.account.Account attribute), 90
trade_history() (beem.market.Market method), 147
trades() (beem.market.Market method), 147
TransactionBuilder (class in beem.transactionbuilder), 167
transactions (beem.block.Block attribute), 98
transfer() (beem.account.Account method), 90
transfer() (beem.rc.RC method), 156
transfer_dict() (beem.rc.RC method), 156
transfer_from_savings()
 (beem.account.Account method), 90

transfer_to_savings() (*beem.account.Account method*), 91
 transfer_to_vesting() (*beem.account.Account method*), 91
 Trending_tags (*class in beem.discussions*), 132
 tryUnlockFromEnv() (*beem.wallet.Wallet method*), 176
 tuple() (*beem.amount.Amount method*), 95
 tx() (*beem.blockchaininstance.BlockChainInstance method*), 115
 txbuffer (*beem.blockchaininstance.BlockChainInstance attribute*), 115
 type_id (*beem.account.Account attribute*), 91
 type_id (*beem.asset.Asset attribute*), 97
 type_id (*beem.blockchainobject.BlockchainObject attribute*), 105
 type_id (*beem.comment.Comment attribute*), 122
 type_id (*beem.vote.Vote attribute*), 172
 type_id (*beem.witness.Witness attribute*), 177
 type_ids (*beem.blockchainobject.BlockchainObject attribute*), 106

U

UnauthorizedError, 179
 unCompressed() (*beem-graphenebase.account.PublicKey method*), 193
 UNFOLLOW
 beempy-unfollow command line option, 48
 unfollow() (*beem.account.Account method*), 91
 UnhandledRPCError, 179
 UnkownKey, 179
 unlock() (*beem.blockchaininstance.BlockChainInstance method*), 115
 unlock() (*beem.wallet.Wallet method*), 176
 unlock_wallet() (*beem.memo.Memo method*), 150
 unlocked() (*beem.wallet.Wallet method*), 176
 UnnecessarySignatureDetected, 179
 Unsigned_Transaction (*class in beem-graphenebase.unsignedtransactions*), 197
 update() (*beem.snapshot.AccountSnapshot method*), 157
 update() (*beem.witness.Witness method*), 177
 update_account() (*beem.blockchaininstance.BlockChainInstance method*), 115
 update_account_jsonmetadata() (*beem.account.Account method*), 91
 update_account_keys() (*beem.account.Account method*), 91
 update_account_metadata() (*beem.account.Account method*), 92
 update_account_profile() (*beem.account.Account method*), 92

update_in_vote() (*beem.snapshot.AccountSnapshot method*), 157
 update_memo_key() (*beem.account.Account method*), 92
 update_nodes() (*beem.nodelist.NodeList method*), 151
 update_out_vote() (*beem.snapshot.AccountSnapshot method*), 157
 update_proposal_votes() (*beem.blockchaininstance.BlockChainInstance method*), 116
 update_rewards() (*beem.snapshot.AccountSnapshot method*), 158
 update_user_metadata() (*beem.hivesigner.HiveSigner method*), 140
 update_user_metadata() (*beem.steemconnect.SteemConnect method*), 164
 updateToken() (*beem.storage.Token method*), 167
 updateWif() (*beem.storage.Key method*), 166
 upload() (*beem.imageuploader.ImageUploader method*), 141
 upvote() (*beem.comment.Comment method*), 122
 url (*beemapi.node.Nodes attribute*), 182
 url_from_tx() (*beem.hivesigner.HiveSigner method*), 140
 url_from_tx() (*beem.steemconnect.SteemConnect method*), 164

V

VALUE
 beempy-set command line option, 46
 beempy-setprofile command line option, 46
 VARIABLE
 beempy-delprofile command line option, 29
 beempy-setprofile command line option, 46
 verify() (*beem.message.Message method*), 150
 verify() (*beembase.signedtransactions.Signed_Transaction method*), 188
 verify() (*beemgraphenebase.signedtransactions.Signed_Transaction method*), 197
 verify_account_authority() (*beem.account.Account method*), 92
 verify_authority() (*beem.transactionbuilder.TransactionBuilder method*), 169
 verify_message() (*in module beem-graphenebase.ecdsasig*), 196
 version_string_to_int() (*beemapi.graphenerpc.GrapheneRPC method*),

181
vest_token_symbol
 (*beem.blockchaininstance.BlockChainInstance attribute*), 116
VestingBalanceDoesNotExistException, 134
vests_symbol (*beem.hive.Hive attribute*), 138
vests_symbol (*beem.steem.Steem attribute*), 161
vests_to_hbd() (*beem.hive.Hive method*), 138
vests_to_hp() (*beem.hive.Hive method*), 138
vests_to_rshares()
 (*beem.blockchaininstance.BlockChainInstance method*), 116
vests_to_rshares() (*beem.hive.Hive method*), 138
vests_to_rshares() (*beem.steem.Steem method*), 161
vests_to_sbd() (*beem.steem.Steem method*), 161
vests_to_sp() (*beem.steem.Steem method*), 162
virtual_op_count() (*beem.account.Account method*), 93
volume24h() (*beem.market.Market method*), 147
Vote (*class in beem.vote*), 171
vote() (*beem.blockchaininstance.BlockChainInstance method*), 117
vote() (*beem.comment.Comment method*), 122
vote() (*beem.rc.RC method*), 156
vote_dict() (*beem.rc.RC method*), 156
VotedBeforeWaitTimeReached, 179
VoteDoesNotExistException, 134
votee (*beem.vote.Vote attribute*), 172
voter (*beem.vote.Vote attribute*), 172
VotesObject (*class in beem.vote*), 172
VotingInvalidOnArchivedPost, 134
vp (*beem.account.Account attribute*), 93

W

wait_for_and_get_block()
 (*beem.blockchain.Blockchain method*), 104
Wallet (*class in beem.wallet*), 172
WalletExists, 134
WalletImportFormat()
 (*graphenebase.bip32.BIP32Key 195*)
 (*beem-method*),
 (*beemapi.graphenerpc.GrapheneRPC method*), 181
 (*beemapi.node.Nodes attribute*), 182
 WorkingNodeMissing, 179
 WrongMasterPasswordException, 134
 WrongMemoKey, 134
ws_send() (*beemapi.graphenerpc.GrapheneRPC method*), 181

WIF
 beempy-witnessfeed command line option, 54
 beempy-witnessproperties command line option, 54
wipe() (*beem.storage.Key method*), 166
wipe() (*beem.storage.MasterPassword static method*), 166
wipe() (*beem.storage.Token method*), 167

wipe() (*beem.wallet.Wallet method*), 176
withdraw_vesting() (*beem.account.Account method*), 93

WITNESS

 beempy-approvewitness command line option, 22
 beempy-disappowitness command line option, 31
 beempy-witness command line option, 52
 beempy-witnesscreate command line option, 52
 beempy-witnessdisable command line option, 53
 beempy-witnessenable command line option, 53
 beempy-witnessfeed command line option, 54
 beempy-witnessproperties command line option, 54
Witness (*class in beem.witness*), 176
witness_set_properties()
 (*beem.blockchaininstance.BlockChainInstance method*), 117
witness_update() (*beem.blockchaininstance.BlockChainInstance method*), 117
WitnessDoesNotExistException, 134
Witnesses (*class in beem.witness*), 177
WitnessesObject (*class in beem.witness*), 177
WitnessesRankedByVote (*class in beem.witness*), 178
WitnessesVotedByAccount (*class in beem.witness*), 178
WitnessProps (*class in beembase.objects*), 187
Worker (*class in beem.blockchain*), 105
working_nodes_count (*beemapi.node.Nodes attribute*), 182